

Delock LTE Antenna SMA plug 7 dBi fixed omnidirectional with magnetic base and connection cable RG-58 3 m outdoor black

Description

This LTE antenna by Delock allows the usage of different LTE bands inside and outside. It is completely compatible to GSM, LTE, UMTS, Bluetooth, WLAN 2.4 GHz, ZigBee, DECT and Z-Wave.



Item no. 12428

EAN: 4043619124282 Country of origin: Taiwan, Republic of China

Package: Poly bag

Specification

Connector: 1 x SMA plug

· Frequency range:

700 MHz

850 - 960 MHz

1710 - 2170 MHz

2400 - 2500 MHz

2600 - 2690 MHz

 GSM, LTE, UMTS, Bluetooth, WLAN 2.4 GHz, ZigBee, DECT, Z-Wave, LoRa 868 MHz / 915 MHz

Antenna gain: 7 dBiImpedance: 50 OhmPolarisation: vertical

• VSWR: 2.0

• Transmission power: 50 W

• Operating temperature: -30 °C ~ 70 °C

· Colour: black



• Cable: coaxial

Cable type: RG-58Cable colour: black

• Cable attenuation: 0.6 dB @ 1 GHz per meter

• Cable diameter: ca. 4.95 mm

• Cable length incl. connector: ca. 3 m

• Antenna length including magnetic base: ca. 46.5 cm

• Diameter magnetic base: ca. 80.0 mm


System requirements


• Device with a free SMA jack


Package content


• LTE antenna

Images











General

Mounting type:	magnetic
Protection category:	without

Interface

connector:

Technical characteristics

Frequency range:	1710 - 2690 MHz 700 - 960 MHz
Antenna gain:	7 dBi
Impedance:	50 Ω
Operating temperature:	-30 °C ~ 70 °C
Polarisation:	vertical
Power handling:	50 W
VSWR:	2.0

Physical characteristics

Antenna type:	Rod antenna
Antenna length incl. magnetic base:	465 mm
Diameter magnetical base:	80 mm
Thread length:	5.6 mm
Cable category:	coaxial
Cable type:	RG-58
Cable colour:	black
Cable length incl. connector:	3 m
Colour:	black





Thread type: M3

