

Monitor di sorveglianza 17" 24/7 HD 1280x1024 pixel formato 5:4. 1x HDMI, 1x VGA, 2x ingressi BNC. 1x uscita BNC, 2x altoparlanti

Monitor di sicurezza ad alte prestazioni 24/7 per una durata prolungata del display. Ernitec offre con questo monitor un display all'avanguardia. Abbiamo aggiunto un ingresso BNC per consentire l'integrazione semplice di una telecamera analogica al monitor.

CARATTERISTICHE DEL DISPLAY

Dimensione schermo 17"
Area di visualizzazione attiva (mm) 337.920mm(L)×270.336mm(A)
Modalità di visualizzazione 5:4
Tipo di LED TFT-LED
Risoluzione 1280×1024
Colori del display 16,7M
Passo pixel (mm) 0,264(L)×0,264(A)
Luminosità (nits) 250cd/m²
Rapporto di contrasto 1000:1
Angolo di visione 178(L) / 178(A)
Tempo di risposta 5ms
Retroilluminazione LED

INGRESSI & USCITE

HDMI 2.0 x 1
VGA x 1
Ingresso BNC x 2
Uscita BNC x 1
Altoparlanti 2x 3W (Stereo)

VIDEO

Sistema colore PAL/NTSC/SECAM
Controllo OSD Regolazione automatica, Luminosità, Contrasto, Posizione Orizz./Vert., Orologio, Fase, Colore, Lingua.
Filtro comb 3D Sì
Riduzione del rumore video Sì

ALIMENTAZIONE & MONTAGGIO

Alimentazione DC12V, 50/60Hz
Temperatura di lavoro -30 a +85 °C
Consumo energetico ≤25W
Menu Inglese e altre lingue
Montaggio/peso Supporto da tavolo, montaggio VESA /7,5kg
MTBF 50000 Ore
Dimensione VESA: 75x75

- 2 ingressi BNC + 1 uscita BNC



Specifiche

Design	Detachable stand	Yes
	Front bezel colour	Black
	Market positioning	Industrial
	Product colour	Black
Display	3D	Yes
	Backlight type	LED
	Contrast ratio (typical)	1000:1
	Display brightness	250 cd/m ²
	Display brightness (typical)	250 cd/m ²
	Display diagonal	17 "
	Display resolution	1280 x 1024 Pixel
	Display technology	LCD, LED
	Native aspect ratio	5:4
	Pixel pitch	0.264(H)×0.264(V) mm
	Response time	5 ms
	Viewable size, horizontal	33,7 cm
	Viewable size, vertical	27 cm
	Viewing angle, horizontal	170 °
Viewing angle, vertical	170 °	
Ergonomics	On Screen Display (OSD) languages	English
	Panel mounting interface	75 x 75 mm
	VESA mounting	Yes
Operational conditions	Operating temperature (T-T)	-30-85 °C
Other features	Accessories included	Industrial PSU,Screw, Cable holder, Quick start guide
	Active display area (W x H)	337.920mm(W)×270.336mm(H) mm
	Analog signal format system	PAL, NTSC, SECAM
	Certification	EMC Class A
	Comb filter	3D
	Compatible wall mount	Vesa 100 x 100
	Contrast ratio	1000:1
	Dimensions (WxDxH)	382 x 45 x 315 mm
	Mean time between failures (MTBF)	50000 h
	Mounting	Stand mount, VESA mount 75 x 75 mm
	Noise filter	Yes
	Number of colours	16.78 million colours
	Package dimensions (WxDxH)	442 x 110 x 414 mm
	Picture enhancement	DNle digital image processing
	Power consumption	15 W
	Speakers	2x3W (Stereo)
	Weight	2500 g

Packaging content	Cables included	Power
	HDMI cable length	1 m
	Power adapter included	Yes
	Quick start guide	Yes
	Screws included	Yes
	Stand included	Yes
Ports & interfaces	AC (power) in	No
	BNC input ports	1
	DisplayPorts quantity	0
	DVI-I ports quantity	0
	HDMI	Yes
	HDMI ports quantity	1
	HDMI version	2.0
	VGA (D-Sub) ports quantity	1
Power	Power consumption (average)	15 W
	Power supply type	Industrial
	Socket connector type	C13
Vendor information	Brand Name	Ernitec
	Homepage	http://www.ernitec.coi
	Warranty	