



Product Datasheet

ENGLISH

Stock No: 1236454
1236455
1236456
1236457

RS Pro HANDY OSCILLOSCOPE RSHS800 SERIES



Application Domain

- Outdoor measure
- Circuit measure
- Wind power, PV power and other new energy equipment test
- Automotive electron, electric automobile test
- Electric power system, strong electricity test
- Industry scenes electric debug testing and measuring
- Education and science research
- Quality control

Features & Benefits

- Dual-input, combine oscilloscope, Multimeter and recorder (including TrendPlot and waveform Recorder) in one unit.
- Input voltage: input voltage through BNC is up to CAT II 300V and CAT III 150V
- Standard probe: 10X CAT II 400V
Optional probe: 10X CAT II 1000V and 10X CAT III 600V
- Oscilloscope and multimeter safety grade is up to CAT II 600V and CAT III 300V
- 5.7 inch TFT color LCD display
- Max. 200MHz Bandwidth, 1GSa/s real-time sampling rate single channel, up to 50GSa/s equivalent sampling rate
- With 6000 dots display resolution Multimeter and provides measurements of DCV, ACV, DCI, ACI, Resistance, Diode, Capacitance and Continuity
- Support Scope TrendPlot, Meter TrendPlot and Scope Recorder
- Trigger modes :Automatic , Normal and Single
- Trigger types: Edge, Pulse, Video, Slope and Alternative

- 32 automatic measurements, 3 cursor measure modes
- 4 digital filter mode: Low pass, High pass, Band pass, Band limit
- Math functions: +, -, ×, ÷, FFT operations
- Multiple Language User Interface
- Standard configuration interface: USB Device, USB Host
- Support USB storage and update; support PC remote control and PictBridge print
- Rechargeable Li battery pack, compact, portable, fit for outdoor operation


TrendPlot

Scope TrendPlot records scope measurement data, 800K points capacity, more than 18 hours recording time; Meter TrendPlot records multimeter measurement data, 1.2M points recording length, recording time as long as 6000 hours at 0.05Sa/s

Real-time saving measuring data, which can be outputted to U memory, used for second research and analyzing

Two display modes, 'ALL' and 'NORMAL'; support zoom and cursor

Support recording real time



Scope TrendPlot



Meter TrendPlot

Scope Recorder

- Recording scope waveform continually in scan mode
- Support recording, replay and zoom function
- 7M points memory depth,18 hours recording time
- Maximum 4GB in USB storage mode, 3000hours recording time

Multimeter

- 6000 counts high percison Multimeter
- Providing measurements of DCV, ACV, DCI, ACI, Resistance, Diode, Capacitance, Continuity



Specification

Scope				
Type	RSHS806	RSHS810	RSHS815	RSHS820
Bandwidth	60MHz	100MHz	150MHz	200MHz
Rise Time	≤5.8ns	≤3.5ns	≤2.3ns	≤1.7ns
Input Impedance	1MΩ±2%, 18pf±3pf			
Real Time Sampling Rate	Single Channel: 1GSa/s, Double Channels: 500MSa/s			500MSa/s
Equivalent Sampling Rate	50GSa/s			
Time Base Range	5 ns/ div~50s/ div	2.5 ns/ div~ 50s/ div		
Scan Range	100ms/ div~50s/ div			
Vertical Sensitivity	2mV/div~100V/div(1-2-5 step)			
Vertical Resolution	8 bits			
Trigger Types	Edge, Pulse, Video, Slope, Alternative			
Frequency Counter	6 bits			
Connection	USB Device, USB Host			
Math	+, -, *, /, FFT			
Oscilloscope Trend Plot	800K points			

Meter

Maximum Resolution	6000 counts		
Function	Range	Resolution	accuracy
DC Voltage	60.00 mV	10uV	(±1%±15digit)
	600.0mV	100uV	(±1%±5digit)
	6.000V	1mV	
	60.00V	10mV	
	600.0V	100mV	
	1000 V	1V	
AC Voltage (20Hz～400Hz)	60.00 mV	10uV	(±1%±15digit)
	600.0mV	100uV	(±1%±5digit)
	6.000V	1mV	
	60.00V	10mV	
	600.0V	100mV	
	750 V	1V	(±1.5%±5digit)
DC Current _[1]	60.00 mA	10uA	(±1.5%±5digit)
	600.0mA	100uA	(±2%±5digit)
	6.000 A	1mA	
	10.00 A	10mA	
AC Current _[2] (20Hz～400Hz)	60.00 mA	10uA	(±1.5%±5digit)
	600.0mA	100uA	(±2%±5digit)
	6.000 A	1mA	(±3%±5digit)
	10.00 A	10mA	
Resistance	600.0Ω	0.1Ω	(±1%±5digit)
	6.000KΩ	1Ω	
	60.00KΩ	10Ω	
	600.0KΩ	100Ω	
	6.000MΩ	1kΩ	(±3%±5digit)
	60.00MΩ	10kΩ	(±3%±10digit)
Capacitance	40.00nF	0.01nF	(±4%±5digit)
	400.0nF	0.1nF	
	4.000uF	1nF	
	40.00uF	10nF	
	Diode	0～2V 400.0uF	
Continuity	<50Ω Buzzer sounds		

Note: [1],[2] For rank A range, the measurement time should be less than 10s, the interval time should be more than 15 Minutes

Technical Specifications

Oscilloscope

Acquisition System	
Sampling Types	Real time, Equivalent
Sampling Mode	Sampling, Peak detection, Average
Average Times	4, 16, 32, 64, 128, 256

Input System		
Input Coupling	AC, DC, GND	
Input Impedance	1MΩ±2%, 18pf±3pf	
Probe Attenuation Factor	1X, 10X	
Probe Attenuation Factors Set	1X, 5X , 10X, 50X , 100X , 500X , 1000X	
Max. Voltage From BNC (Reference BNC Cover)	CAT II	300Vrms
	CAT III	150Vrms
Standard Probe 10X	CAT II	400Vrms
Optional Probe 10X	CAT II	1000Vrms
Max. Floating Voltage From Multimeter Reference to Earth Ground	CAT II	600Vrms
	CAT III	300Vrms
Single Channel Common Mode Rejection Ratio	>100:1 50MHz	
Channel-to-Channel Isolation	>35dB	

Horizontal System					
Real time Sample Rate		Single Channel :50Sa/s~1GSa/s Double Channels: 50Sa/s~500MSa/s			
Interaction Mode		x, Sinx			
Memory Depth	RSHS806	Channel Mode	Sample Rate	Normal	Long Memory
		Single Channel	1GSa/s	40kpts	Non-support
	RSHS810 RSHS815	Single Channel	≤ 500MSa/s	20kpts	2 Mpts
		Double Channels	≤ 500MSa/s	20kpts	1 Mpts
	RSHS820	Single Channel:32Kpts; Double Channel:16Kpts			
Display Mode		MAIN, WINDOW ZOOM, SCAN, X-Y			
Time Base Accuracy		±50ppm (measured over 1ms interval)			
Horizontal Scan Range		2.5ns/div~50s/div (RSHS820) 2.5ns/div~50s/div (RSHS815) 2.5ns/div~50s/div (RSHS810) 5.0ns/div~50s/div (RSHS806) Scan mode: 100ms/div~50s/div (1-2.5-5 step)			

Vertical System				
Vertical Sensitivity		2mV/div – 100V/div(1-2-5 step)		
Channel	Voltage	Offset	2mV-200mV: ±1.6V 206mV-10V: ±40V 10.2V-100V: ±400V	
Range				
Vertical Resolution		8 bit		
Channels		2		
Analog Bandwidth		200MHz (RSHS820)	150MHz(RSHS815)	100MHz (RSHS810) 60MHz(RSHS806)
Lower Frequency(AC-3dB)		≤10Hz		
DC Gain Accuracy		5mv/div-100v/div:≤±3% 2mv/div:≤±4% (5mv/div-100v/div:≤±5%, 2mv/div:≤±6%, square wave Vpp)		
DC Measurement Accuracy ≤200mv/div		±[3.0%*(reading + offset)+1% * offset +0.2div+2mV]		
DC Measurement Accuracy > 200mv/div		±[3.0%*(reading + offset)+1% * offset +0.2div+100mV]		
Rise Time		≤1.7ns (RSHS820)		
		≤2.3ns (RSHS815)		
		≤3.5ns (RSHS810)		
		≤5.8ns (RSHS806)		
Vertical Input Coupling		AC, DC, GND		
Math Operation		+, -, * , /, FFT		
FFT		Window Mode: Hanning, Hamming, Blackman, Rectangular		
		Sampling: 1024 points		
Bandwidth Limit		20MHz (-3dB)		

Trigger System			
Trigger Types	Edge, Pulse Width, Video, Slope, Alternative		
Trigger Source	CH1, CH2		
Trigger Modes	Auto, Normal, Single		
Trigger Coupling	AC, DC, LF Reject, HF Reject		
Trigger Level Range	CH1, CH2: ±6 divisions from center of screen		
Trigger Displacement	Pre-trigger: Memory depth/(2*sampling)		
	Delay Trigger: 268.04div		
Holdoff Range	100ns – 1.5s		
Edge Trigger	Edge Type: Rising, Falling, Rising and Falling		
Pulse Width Trigger	Trigger Modes: (>,<,<=) Positive Pulse Width, (>,<,<=)Negative		Pulse Width
	Pulse Width Range: 20ns – 10s		
Video Trigger	Support Signal Formats: PAL/SECAM, NTSC		
	Trigger Condition : Odd Field, Even Field, All Lines, Line Num		
Slope Trigger	(>,<,<=) Positive slope, (>,<,<=) Negative slope		
	Time: 20ns-10s		
Alternative Trigger	CH1 Trigger Type: Edge, Pulse, Video, Slope		
	CH2 Trigger Type: Edge, Pulse, Video, Slope		

X-Y Mode	
X-Pole Input /Y-Pole Input	Channel 1 (CH1) / Channel 2 (CH2)
Sample Frequency	25KSa/s~250MSa/s (1-2.5-5 step)

Measurement System	
Auto Measure (32 Types)	Vpp, Vmax, Vmin, Vamp, Vtop, Vbase, Vavg, Mean, Crms, Vrms, ROVShoot, FOVShoot, RPRESshoot, FPRESshoot, Rise time, Fall time, Freq, Period, + Wid, −Wid, + Dut, −Dut, BWid, Phase, FRR, FRF, FFR, FFF, LRR, LRF, LFR, LFF
Cursor Measure	Manual, Track and Auto

Control Panel Function	
Auto Set	Auto adjusting the Vertical system, Horizontal system and Trigger Position
Save/Recall	2 groups of referenced waveforms, 20 groups of setups,10 groups of captured waveforms internal save/recall function and USB flash driver storage function.

Hard Ware Frequency Counter	
Reading Resolution	1Hz
Range	DC Couple, 10Hz to MAX Bandwidth
Signal Types	Applying to all Trigger signals(Except Video Trigger)

Multimeter

Maximum Resolution	6000 counts
Measure Function	DCV, ACV, DCI, ACI, Resistance, Diode, Capacitance, Continuity
Max Input Voltage	AC(Vrms): 750V (AC frequency :20Hz~400Hz)DC :1000V
Max Input Current	AC (Vrms) : 10A (AC frequency :20Hz~400Hz)DC : 10A
Impedance	10MΩ

Recorder

Scope TrendPlot	
Display	All, Normal
Record Size	800K points, more than 18 hours
Record Channel	2 channels
Cursor, Zoom	Support
Manual Mode	Support

Meter TrendPlot	
Display	All, Normal
Record Size	1.2M points
Record Channel	1 channel
Cursor, Zoom	Support
Manual Mode	Support

Scope Record		
Function	Record scope waveforms, Replay recorded waveforms	
Acquisition Mode	Scan Mode	
Time	Record mode: recording time Replay mode: replay time	
Sets	Viewer: full screen, split screen ; Replay mode: point, frame ;	Record mode: continuous, single Save mode: Internal memory
Default	Viewer: split screen; Replay mode: point ; Total: 7M points	Record mode: continuous Save mode: Internal memory
Record Size	Single channel: 7M points single channel Double channels: 3.5M points per channel	
Record Manual	Start, Pause, Stop, Continue	
Replay Manual	Start, Pause, Stop, Continue, Previous, Next,	

Generic Specification

Display System	
Display Mode	5.7 inch TFT color LCD
Resolution	320 horizontal by 234 vertical pixels
Display Color	24 bits
Display Contrast (Typical state)	150:1
Backlight Intensity (Typical state)	300nit
Waveform Display Range	8 x 12 div
Waveform Display Mode	Point, Vector
Persist	Off, 1 sec, 2 sec, 5 sec, Infinite
Menu Display	2 sec, 5 sec, 10 sec, 20 sec, Infinite
Screen-Saver	Off, 1min, 2min, 5min, 10min, 15min, 30min, 1hour, 2hour, 5hour
Waveform Interpolation	Sin(x), x
Color model	Normal , Invert
Language	Simplified Chinese, Traditional Chinese, English, Arabic, French, German, Russian, Spanish, Portuguese, Japanese, Korean, Italian

Power		
Line Power Adapter	Input voltage	100V-240V 50/60Hz
	Output voltage	9V 4A
Battery	7.4VDC, 5000mAh, persisting 5 hours	
Charge time	About 4 hours	

Environments		
Temperature	Operating	0~40℃
	Storage	−20℃~70℃
Cooling	Natural Cool	
Humidity	85%RH, 40℃	
Height	3000m	
Electromagnetic Compatibility	2004/108/EC Directive	
	Applicable standards EN 61326-1:2006	
	EN 61000-3-2:2006 + A2:2009/ EN 61000-3-3:2008	
Safety	2006/95/EC Low Voltage Directive	
	EN 61010-1:2010/EN 61010-031:2002+A1:2008	

Mechanical		
Size	length	259.5mm
	width	163.2mm
	height	53.3mm
Weight	1.5Kg	