



C&D ELETTRONICA SRL

BERGAMO 24126
Via Oprandi, 17
Tel. 035 199 55 011
Fax 035 199 55 099

E-COMMERCE
www.cedelettronica.com
E-MAIL
mail@cedelettronica.com
cedelettronica@pec.it



LABORATORIO EMC
PROVE DI COMPATIBILITA'
Elettromagnetica



WWW.CEDELETRONICA.COM

WWW.MTEK.IT

C.F. 00895950160
P.IVA IT00895950160

Cap. Soc. 500.000,00 Euro i.v.
R.E.A. BG-180921



Registro A.E.E. n. IT08020000003208
Registro PILE n. IT16010P00003973

Listino prezzi MOXA - www.moxa.com

Prezzi IVA esclusa f.co ns magazzino

Luglio 2026

Per quantità e offerte speciali contattare:

C&D Elettronica srl

tel. **035.19955011** info@mtek.it

www.mtek.it

MODELLO	DESCRIZIONE	LISTINO
3G Antenna Package	3G external antenna with QMA (male) to SMA (female) adapter and 2 50 cm cables, 3G external antenna with 2 SMA connectors, cellular extension cable	291,00 €
45ML-5401	Module for the ioThinx 4530 Series, 4 serial ports (RS-232/422/485 3-in-1), -20 to 60°C operating temperature	773,00 €
45ML-5401-T	Module for the ioThinx 4530 Series, 4 serial ports (RS-232/422/485 3-in-1), -40 to 75°C operating temperature	927,00 €
45MR-1600	Module for the ioThinx 4500 Series, 16 DIs, 24 VDC, PNP, -20 to 60°C operating temperature	243,00 €
45MR-1600-T	Module for the ioThinx 4500 Series, 16 DIs, 24 VDC, PNP, -40 to 75°C operating temperature	328,00 €
45MR-1601	Module for the ioThinx 4500 Series with 16 DIs, 24 VDC, NPN, -20 to 60°C operating temperature	243,00 €
45MR-1601-T	Module for the ioThinx 4500 Series with 16 DIs, 24 VDC, NPN, -40 to 75°C operating temperature	328,00 €
45MR-2404	Module for the ioThinx 4500 Series with 4 relays, form A, -20 to 60°C operating temperature	218,00 €
45MR-2404-T	Module for the ioThinx 4500 Series, 4 relays, form A, -40 to 75°C operating temperature	306,00 €
45MR-2600	Module for the ioThinx 4500 Series, 16 DOs, 24 VDC, sink, -20 to 60°C operating temperature	261,00 €
45MR-2600-T	Module for the ioThinx 4500 Series, 16 DOs, 24 VDC, sink, -40 to 75°C operating temperature	351,00 €
45MR-2601	Module for the ioThinx 4500 Series, 16 DOs, 24 VDC, source, -20 to 60°C operating temperature	261,00 €
45MR-2601-T	Module for the ioThinx 4500 Series, 16 DOs, 24 VDC, source, -40 to 75°C operating temperature	351,00 €
45MR-2606	Module for the ioThinx 4500 Series, 8 DIs, 8 DOs, 24 VDC, PNP, source, -20 to 60°C operating temperature	272,00 €
45MR-2606-T	Module for the ioThinx 4500 Series, 8 DIs, 8 DOs, 24 VDC, PNP, source, -40 to 75°C operating temperature	354,00 €
45MR-3800	Module for the ioThinx 4500 Series, 8 AIs, 0 to 20 mA or 4 to 20 mA, -20 to 60°C operating temperature	578,00 €
45MR-3800-T	Module for the ioThinx 4500 Series, 8 AIs, 0 to 20 mA or 4 to 20 mA, -40 to 75°C operating temperature	756,00 €
45MR-3810	Module for the ioThinx 4500 Series, 8 AIs, -10 to 10 V or 0 to 10 V, -20 to 60°C operating temperature	578,00 €
45MR-3810-T	Module for the ioThinx 4500 Series, 8 AIs, -10 to 10 V or 0 to 10 V, -40 to 75°C operating temperature	756,00 €
45MR-4420	Module for the ioThinx 4500 Series, 4 AOs, 0 to 10 V or 0 to 20 mA or 4 to 20 mA, -20 to 60°C operating temperature	500,00 €
45MR-4420-T	Module for the ioThinx 4500 Series, 4 AOs, 0 to 10 V or 0 to 20 mA or 4 to 20 mA, -40 to 75°C operating temperature	675,00 €
45MR-6600	Module for the ioThinx 4500 Series, 6 RTDs, -20 to 60°C operating temperature	543,00 €
45MR-6600-T	Module for the ioThinx 4500 Series, 6 RTDs, -40 to 75°C operating temperature	707,00 €
45MR-6810	Module for the ioThinx 4500 Series, 8 TCs, -20 to 60°C operating temperature	548,00 €
45MR-6810-T	Module for the ioThinx 4500 Series, 8 TCs, -40 to 75°C operating temperature	707,00 €
45MR-7210	Module for the ioThinx 4500 Series, system and field power inputs, -20 to 60°C operating temperature	264,00 €
45MR-7210-T	Module for the ioThinx 4500 Series, system and field power inputs, -40 to 75°C operating temperature	305,00 €
45MR-7820	Module for the ioThinx 4500 Series, potential distributor module, -20 to 60°C operating temperature	162,00 €
45MR-7820-T	Module for the ioThinx 4500 Series, potential distributor module, -40 to 75°C operating temperature	205,00 €

85M-1602-T	Module for the ioPAC 8500/8600 Series, 16 DIs, 24 VDC, sink/source, -40 to 75°C operating temperature	577,00 €
85M-2600-T	Module for the ioPAC 8500/8600 Series, 16 DOs, 24 VDC, sink, -40 to 75°C operating temperature	577,00 €
85M-3800-T	Module for the ioPAC 8500/8600 Series, 8 AIs, 4 to 20 mA, -40 to 75°C operating temperature	963,00 €
85M-3801-T	Module for the ioPAC 8500/8600 Series, 8 AIs, 4 to 20 mA, 40 kHz, -40 to 75°C operating temperature	1.147,00 €
85M-3810-T	Module for the ioPAC 8500/8600 Series, 8 AIs, 0 to 10 V, -40 to 75°C operating temperature	963,00 €
85M-3811-T	Module for the ioPAC 8500/8600 Series, 8 AIs, 0 to 10 V, 40 kHz, -40 to 75°C operating temperature	1.147,00 €
85M-5401-T	Module for the ioPAC 8500/8600 Series, 4-port serial, DB44 connectors, -40 to 75°C operating temperature	1.285,00 €
85M-6600-T	Module for the ioPAC 8500/8600 Series, 6 RTDs, -40 to 75°C operating temperature	1.086,00 €
85M-6810-T	Module for the ioPAC 8500/8600 Series, 8 TCs, -40 to 75°C operating temperature	1.202,00 €
85M-BKTES	Empty slot cover (3 pieces per package)	76,00 €
86M-1620D-T	Module for the ioPAC 8600 Series, 16 DIs, 24 to 110 VDC, sink, channel LED, -40 to 75°C operating temperature	871,00 €
86M-1620D-T (CV-CT)	Module for the ioPAC 8600 Series, 16 DIs, 24 to 110 VDC, sink, channel LED, -40 to 75°C operating temperature, conformal coating	1.001,00 €
86M-1832D-T	Module for the ioPAC 8600 Series with 8 DIs, 24 VDC, sink/source, channel-to-channel isolation, channel LED, -40 to 75°C operating temperature	782,00 €
86M-2604D-T	Module for the ioPAC 8600 Series, 6 Relays, form A (N.O.), channel LED, -40 to 75°C operating temperature	596,00 €
86M-2821D-T	Module for the ioPAC 8600 Series, 8 DOs, 24 to 110 VDC, source, channel LED, -40 to 75°C operating temperature	1.081,00 €
86M-2830D-T	Module for the ioPAC 8600 Series with 8 DOs, 24 VDC, sink, channel-to-channel isolation, channel LED, -40 to 75°C operating temperature	1.081,00 €
86M-4420-T	Module for the ioPAC 8600 Series, 4 AOs, 0 to 10 V, -10 to 10 V, 0 to 20 mA, or 4 to 20 mA, -40 to 75°C operating temperature	962,00 €
86M-5212U-T	Module for the ioPAC 8600 Series, 2-port 2-wire Ethernet switch, -40 to 75°C operating temperature	1.521,00 €
86M-5250-T	Module for the ioPAC 8600 Series, 2 CAN ports, -40 to 75°C operating temperature	870,00 €
A52-DB25F w/ Adapter	RS-232/422/485 converter with adapter, DB25F cable	71,00 €
A52-DB25F w/o Adapter	RS-232/422/485 converter with DB25F cable	60,00 €
A52-DB9F w/ Adapter	RS-232/422/485 converter with adapter, DB9F cable	71,00 €
A52-DB9F w/o Adapter	RS-232/422/485 converter with DB9F cable	60,00 €
A53-DB25F w/ Adapter	RS-232/422/485 converter with 2 kV isolation, adapter, DB25F cable	131,00 €
A53-DB25F w/o Adapter	RS-232/422/485 converter with 2 kV isolation, DB25F cable	116,00 €
A53-DB9F w/ Adapter	RS-232/422/485 converter with 2 kV isolation, adapter, DB9F cable	131,00 €
A53-DB9F w/o Adapter	RS-232/422/485 converter with 2 kV isolation, DB9F cable	116,00 €
A-ADP-QMAM-RF	Antenna adapter with QMA (male) to SMA (female) connectors	21,00 €
A-ADP-QMAM-SMAM	A-ADP-QMAM-SMAM	84,00 €

A-ADP-RJ458P-DB9F-ABC01	DB9 female to RJ45 connector for the ABC-01 Series	21,00 €
A-ADP-SM-RF Golden	SMA adapter for UC-2104 and UC-5100 Series	11,00 €
ABC-01	Configuration backup and restoration tool for managed Ethernet switches and AWK Series wireless APs/bridges/clients, 0 to 60°C operating temperature	137,00 €
ABC-01-M12	Configuration backup and restoration tool with M12 connector for managed Ethernet switches and wireless APs/Bridges/Clients, 0 to 60°C operating temperature	191,00 €
ABC-01-P-M12-CT-T	Configuration backup and restoration tool with M12 connector for Moxa's ToughNet series of managed Ethernet switches and wireless APs/bridges/clients, -40 to 75°C operating temperature, conformal coating	347,00 €
ABC-02-P-USB-M12-CT-T	USB-based configuration backup and restoration tool with M12 connector for Moxa's ToughNet series of managed Ethernet switches and wireless APs/bridges/clients, -40 to 75°C operating temperature, conformal coating	405,00 €
ABC-02-USB	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, 0 to 60°C operating temperature	284,00 €
ABC-02-USB-T	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, -40 to 75°C operating temperature	330,00 €
ABC-03-microSD-T	MicroSD-based configuration backup and restoration tool, firmware upgrades, and log file storage tool for managed Ethernet switches and WLAN products, -40 to 85°C operating temperature	114,00 €
A-CAP-M12F-M	Metal cap for M12 female connector	11,00 €
A-CAP-M12F-M-PP	Metal cap for M12 female push-pull connector	6,00 €
A-CAP-M12M-M	Metal cap for M12 male connector	11,00 €
A-CAP-M30M-MIP67	Metal cap for M30 male connector	21,00 €
A-CAP-NM-MIP67	A-CAP-NM-MIP67	15,00 €
A-CAP-WPRJ45-MC	Metal cap with chain for RJ45 connector	28,00 €
A-CRF-CTPSF-R2-50	GPS Extension Cable TNC to SMA (female) adapter with 50 cm cable x 1	71,00 €
A-CRF-MHFQMAF-D1.13-14.2	Digital Interface Mini card internal antenna with QMA connector x 1,locking washer x 1, O-ring x 1, nut x 1	18,00 €
A-CRF-NMNM-LL4-300	N-type (male) to N-type (male) LMR-400 Lite cable, 3 m	121,00 €
A-CRF-NMNM-LL4-600	N-type (male) to N-type (male) LMR-400 Lite cable, 6 m	179,00 €
A-CRF-NMNM-LL4-900	N-type (male) to N-type (male) LMR-400 Lite cable, 9 m	282,00 €
A-CRF-QMAMNM-R2-50	QMA (male) to N-type (male) RG-316 cable, 0.5 m	96,00 €
A-CRF-RFRM-C2-300	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, CFD-200 type, 3 m	39,00 €
A-CRF-RFRM-C2-500	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, CFD-200 type, 5 m	53,00 €
A-CRF-RFRM-R4-150	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, magnetic base, RG-174 type, 1.5 m	49,00 €

A-CRF-RFRM-R5-60	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, RG-402 type, 0.6 m	94,00 €
A-CRF-RMNM-L1-300	N-type (male) to RP SMA (male) LMR-195 Lite cable, 3 m	118,00 €
A-CRF-RMNM-L1-600	N-type (male) to RP SMA (male) LMR-195 Lite cable, 6 m	174,00 €
A-CRF-RMNM-L1-900	N-type (male) to RP SMA (male) LMR-195 Lite cable, 9 m	272,00 €
A-CRF-SMIF-100	Wireless antenna cable package with 2 100-cm cables (SMA connectors)	12,00 €
A-CRF-SMSF-C2-300	Wireless antenna cable with SMA (male) to SMA (female) connectors, CFD-200 type, 3 m	39,00 €
A-CRF-SMSF-C2-500	Wireless antenna cable with SMA (male) to SMA (female) connectors, CFD-200 type, 5 m	53,00 €
A-CRF-SMSF-L1-300	Wireless antenna cable with SMA (male) to SMA (female) connectors, magnetic base, LMR195 type, 3 m	64,00 €
A-CRF-SMSF-R3-100	Wireless antenna cable with SMA (male) to SMA (female) connectors, magnetic base, RG-174 type, 1 m	42,00 €
ADP-DB9M-DB9M	DB9 to DB9 male connector	8,00 €
ADP-RJ458P-DB9F	DB9 female to RJ45 connector	11,00 €
ADP-RJ458P-DB9M	RJ45 to DB9 male connector	11,00 €
ADP-SCm-STf-M	Multi-mode male SC to female ST duplex adapter, grey color	86,00 €
ADP-SCm-STf-S	Single-mode male SC to female ST duplex adapter, blue color	86,00 €
AIG-101-T	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with -40 to 70°C operating temperature	1.138,00 €
AIG-101-T-AP	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with built-in LTE Cat. 1 module for the Asia-Pacific region, -40 to 70°C operating temperature	1.512,00 €
AIG-101-T-EU	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with built-in LTE Cat. 1 module for the EU region, -40 to 70°C operating temperature	1.512,00 €
AIG-101-T-US	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with built-in LTE Cat. 1 module for the U.S. region, -40 to 70°C operating temperature	1.512,00 €
AIG-301-AP-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for Asia-Pacific region, -20 to 70°C operating temperature	2.241,00 €
AIG-301-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, -20 to 70°C operating temperature	1.476,00 €
AIG-301-EU-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for EU region, -20 to 70°C operating temperature	2.241,00 €
AIG-301-T-AP-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for Asia-Pacific region, -40 to 70°C operating temperature	2.408,00 €
AIG-301-T-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, -40 to 70°C operating temperature	1.622,00 €
AIG-301-T-EU-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for EU region, -40 to 70°C operating temperature	2.408,00 €
AIG-301-T-US-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for U.S. region, -40 to 70°C operating temperature	2.408,00 €

AIG-301-US-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for U.S. region, -20 to 70°C operating temperature	2.241,00 €
AIG-302-T-AP-AZU-LX	2-port Modbus RTU/ASCII/TCP to MQTT/Azure cloud-ready gateway for the Asia-Pacific region with Arm® Cortex™-A7 dual-core 1GHz processor, Azure IoT Edge software, -40 to 70°C operating temperature	2.428,00 €
AIG-302-T-AZU-LX	2-port Modbus RTU/ASCII/TCP to MQTT/Azure cloud-ready gateway with Arm® Cortex™-A7 dual-core 1GHz processor, Azure IoT Edge software, -40 to 85°C operating temperature	1.641,00 €
AIG-302-T-EU-AZU-LX	2-port Modbus RTU/ASCII/TCP to MQTT/Azure cloud-ready gateway for the EU region with Arm® Cortex™-A7 dual-core 1GHz processor, Azure IoT Edge software, -40 to 70°C operating temperature	2.428,00 €
AIG-302-T-US-AZU-LX	2-port Modbus RTU/ASCII/TCP to MQTT/Azure cloud-ready gateway for the U.S. region with LTE Cat. 4 support, Arm® Cortex™-A7 dual-core 1GHz processor, Azure IoT Edge software, -40 to 70°C operating temperature.	2.428,00 €
AIG-501-T-AP-AZU-LX	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, LTE Cat. 4 module for Asia-Pacific region, -40 to 70°C operating temperature	4.112,00 €
AIG-501-T-AZU-LX	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, -40 to 70°C operating temperature	3.267,00 €
AIG-501-T-EU-AZU-LX	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, LTE Cat. 4 module for EU region, -40 to 70°C operating temperature	4.112,00 €
AIG-501-T-US-AZU-LX	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, LTE Cat. 4 module for U.S. region, -40 to 70°C operating temperature	4.112,00 €
AIG-502-T-AZU-LX	Advanced IIoT gateways with Intel® Core™ i7 processor, Azure IoT Edge software, -40 to 70°C operating temperature	8.185,00 €
AIG-502-T-EU-AZU-LX	Advanced IIoT gateways with Intel® Core™ i7 processor, Azure IoT Edge software, LTE Cat. 4 module for EU region, -40 to 70°C operating temperature	8.494,00 €
ANT-5G-ASM-02	2 dBi LTE/5G NR dipole antenna with SMA (male) connector	29,00 €
ANT-5G-ASM-03	3 dBi GSM/UMTS/LTE/5G NR dipole antenna with SMA (male) connector	27,00 €
ANT-5G-ASM-07	7 dBi, omnidirectional rubber-duck antenna for GSM, UMTS, LTE, and 5G NR applications	56,00 €
ANT-5G-OSM-03-1.5m	3 dBi LTE/5G NR omnidirectional adhesive antenna, 1.5 m cable	46,00 €
ANT-5G-OSM-03-1m	3 dBi LTE/5G NR omnidirectional adhesive antenna, 1 m cable	44,00 €
ANT-5G-OSM-03-2m	3 dBi LTE/5G NR omnidirectional adhesive antenna, 2 m cable	48,00 €
ANT-5G-OSM-04	4 dBi LTE/5G NR dipole antenna with SMA (male) connector	14,00 €
ANT-GNSS-CSM-02-3m	2 dBic GNSS antenna with SMA (male) connector, 3 m cable	363,00 €
ANT-GPS-CSM-04-0.2m BK	1575 MHz active GPS/GLONASS 4 dBi antenna with SMA (male) connector and 20-cm cable	54,00 €
ANT-GPS-CSM-04-3m BK	20 dBi at 1575 to 1605 MHz, SMA (male), right-hand circular polarization (RHCP), active GPS antenna, 3-meter cable	56,00 €
ANT-GPS-OSM-05-3M	26 dBi at 1575.42 MHz, SMA (male), omnidirectional active GPS antenna, 3 m cable	96,00 €
ANT-LTE-ASM-02	GPRS/EDGE/UMTS/HSPA/LTE, 2 dBi, omnidirectional rubber-duck antenna	27,00 €
ANT-LTE-ASM-04 BK	704 to 960/1710 to 2620 MHz, LTE omnidirectional stick antenna, 4.5 dBi	43,00 €

ANT-LTE-ASM-05 BK	704-960/1710-2620 MHz, LTE stick antenna, 5 dBi	72,00 €
ANT-LTE-OSM-03-3m BK	700-2700 MHz, multiband antenna, specifically designed for 2G, 3G, and 4G applications, 3 m cable	100,00 €
ANT-LTE-OSM-06-3m BK MIMO	Multiband antenna with screw-fastened mounting option for 700-2700/2400-2500/5150-5850 MHz frequencies	229,00 €
ANT-LTEUS-ASM-01	GSM/GPRS/EDGE/UMTS/HSPA/LTE, 1 dBi, omnidirectional rubber-duck antenna	32,00 €
ANT-LTEUS-OSM-02	698 to 960/1710 to 2700 MHz, 1/4 λ omnidirectional 1.5 dBi antenna with SMA (male) connector	14,00 €
ANT-WDB6-ARM-05	2 dBi at 2.4 GHz or 2 dBi at 5 GHz or 3 dBi at 6 GHz, tri-band dipole antenna with RP-SMA (female) connector	12,00 €
ANT-WDB-ANM-0306	3 dBi at 2.4 GHz or 6 dBi at 5 GHz, N-type (male), omnidirectional antenna	46,00 €
ANT-WDB-ANM-0502	5 dBi at 2.4 GHz or 2 dBi at 5 GHz, N-type (male), omnidirectional antenna	31,00 €
ANT-WDB-ARM-02	2 dBi at 2.4 GHz or 2 dBi at 5 GHz, RP-SMA (male) omnidirectional rubber-duck antenna	8,00 €
ANT-WDB-ARM-0202	2 dBi at 2.4 GHz or 2 dBi at 5 GHz, RP-SMA (male), dual-band, omnidirectional antenna	9,00 €
ANT-WDB-ARM-0202 plus ADP	2.4/5 GHz omni-directional antenna, 2/2 dBi, RP-SMA-type (male) connector	14,00 €
ANT-WDB-ARM-0405	2.4/5 GHz 1/2 λ 4 to 5 dBi omnidirectional antenna with RP-SMA (female) connector	14,00 €
ANT-WDB-ONF-0709	7 dBi at 2.4 GHz or 9 dBi at 5 GHz, N-type (female), dual-band, omnidirectional antenna	192,00 €
ANT-WDB-ONM-0707	07 dBi at 2.4 GHz and 07 dBi at 5 GHz, N-type (male), dual-band omnidirectional antenna	159,00 €
ANT-WDB-PNF-1011	10 dBi at 2.4 GHz and 11 dBi at 5 GHz, N-type (female), dual-band directional antenna	419,00 €
ANT-WSB5-PNF-16	16 dBi at 5 GHz, N-type (female), single-band directional antenna	342,00 €
ANT-WSB-AHRM-05-1.5m	5 dBi at 2.4 GHz, RP-SMA (male), omnidirectional/dipole antenna, 1.5 m cable	27,00 €
ANT-WSB-PNF-12-02	12 dBi at 2.4 GHz, N-type (female), single-band directional antenna	328,00 €
A-PLG-WPM23-01-IP67	Crimp type M23 connector, female 6-pin, IP67-rated	147,00 €
A-PLG-WPM30IP67-01	Field-Installation for M30 plug	79,00 €
A-PLG-WPRJ	Field-installation RJ-type plug	11,00 €
A-SA-NFNF-02	0 to 6 GHz, N-type (female) to N-type (female) surge arrester	89,00 €
A-SA-NMNF-02	0 to 6 GHz, N-type (male) to N-type (female) surge arrester	89,00 €
A-TRM-50-NM	50-ohm termination resistor with N-type male connector	38,00 €
A-TRM-50-RM	50-ohm terminating resistor with RP-SMA male connector	41,00 €
AVK-17	Anti-vibration wiring kit	18,00 €
AWK-1131A-EU	Industrial Wi-Fi 4 (802.11n) wireless AP/client, EU band, 0 to 60°C operating temperature	807,00 €
AWK-1131A-EU-T	Industrial Wi-Fi 4 (802.11n) wireless AP/client, EU band, -40 to 75°C operating temperature	911,00 €
AWK-1131A-JP	Industrial Wi-Fi 4 (802.11n) wireless AP/client, JP band, 0 to 60°C operating temperature	807,00 €
AWK-1131A-JP-T	Industrial Wi-Fi 4 (802.11n) wireless AP/client, JP band, -40 to 75°C operating temperature	911,00 €

AWK-1131A-US	Industrial Wi-Fi 4 (802.11n) wireless AP/client, US band, 0 to 60°C operating temperature	807,00 €
AWK-1131A-US-T	Industrial Wi-Fi 4 (802.11n) wireless AP/client, US band, -40 to 75°C operating temperature	911,00 €
AWK-1137C-EU	Industrial Wi-Fi 4 (802.11n) wireless client, EU band, 0 to 60°C operating temperature	716,00 €
AWK-1137C-EU-T	Industrial Wi-Fi 4 (802.11n) wireless client, EU band, -40 to 75°C operating temperature	802,00 €
AWK-1137C-JP	Industrial Wi-Fi 4 (802.11n) wireless client, JP band, 0 to 60°C operating temperature	716,00 €
AWK-1137C-JP-T	Industrial Wi-Fi 4 (802.11n) wireless client, JP band, -40 to 75°C operating temperature	802,00 €
AWK-1137C-US	Industrial Wi-Fi 4 (802.11n) wireless client, US band, 0 to 60°C operating temperature	716,00 €
AWK-1137C-US-T	Industrial Wi-Fi 4 (802.11n) wireless client, US band, -40 to 75°C operating temperature	802,00 €
AWK-1151C-UN	Industrial Wi-Fi 5 (802.11ac) wireless client, IP30, UN band, 0 to 60°C operating temperature	751,00 €
AWK-1151C-UN-T	Industrial Wi-Fi 5 (802.11ac) wireless client, IP30, UN band, -40 to 75°C operating temperature	856,00 €
AWK-1151C-US	Industrial Wi-Fi 5 (802.11ac) wireless client, IP30, US band, 0 to 60°C operating temperature	751,00 €
AWK-1151C-US-T	Industrial Wi-Fi 5 (802.11ac) wireless client, IP30, US band, -40 to 75°C operating temperature	856,00 €
AWK-1161A-UN	Industrial Wi-Fi 6 (802.11ax) wireless AP with 1 10/100/1000BaseT(X) port, IP30, UN band, -25 to 60°C operating temperature	956,00 €
AWK-1161A-UN-T	Industrial Wi-Fi 6 (802.11ax) wireless AP with 1 10/100/1000BaseT(X) port, IP30, UN band, -40 to 75°C operating temperature	1.101,00 €
AWK-1161A-US	Industrial Wi-Fi 6 (802.11ax) wireless AP with 1 10/100/1000BaseT(X) port, IP30, US band, -25 to 60°C operating temperature	956,00 €
AWK-1161A-US-T	Industrial Wi-Fi 6 (802.11ax) wireless AP with 1 10/100/1000BaseT(X) port, IP30, US band, -40 to 75°C operating temperature	1.101,00 €
AWK-1161C-UN	Industrial Wi-Fi 6 (802.11ax) wireless client with 1 10/100/1000BaseT(X) port, IP30, UN band, -25 to 60°C operating temperature	833,00 €
AWK-1161C-UN-T	Industrial Wi-Fi 6 (802.11ax) wireless client with 1 10/100/1000BaseT(X) port, IP30, UN band, -40 to 75°C operating temperature	956,00 €
AWK-1161C-US	Industrial Wi-Fi 6 (802.11ax) wireless client with 1 10/100/1000BaseT(X) port, IP30, US band, -25 to 60°C operating temperature	833,00 €
AWK-1161C-US-T	Industrial Wi-Fi 6 (802.11ax) wireless client with 1 10/100/1000BaseT(X) port, IP30, US band, -40 to 75°C operating temperature	956,00 €
AWK-1165A-UN	Industrial Wi-Fi 6 (802.11ax) wireless AP with 5 10/100/1000BaseT(X) ports, IP30, UN band, -25 to 60°C operating temperature	1.072,00 €
AWK-1165A-UN-T	Industrial Wi-Fi 6 (802.11ax) wireless AP with 5 10/100/1000BaseT(X) ports, IP30, UN band, -40 to 75°C operating temperature	1.267,00 €
AWK-1165A-US	Industrial Wi-Fi 6 (802.11ax) wireless AP with 5 10/100/1000BaseT(X) ports, IP30, US band, -25 to 60°C operating temperature	1.072,00 €
AWK-1165A-US-T	Industrial Wi-Fi 6 (802.11ax) wireless AP with 5 10/100/1000BaseT(X) ports, IP30, US band, -40 to 75°C operating temperature	1.267,00 €
AWK-1165C-UN	Industrial Wi-Fi 6 (802.11ax) wireless client with 5 10/100/1000BaseT(X) ports, IP30, UN band, -25 to 60°C operating temperature	942,00 €
AWK-1165C-UN-T	Industrial Wi-Fi 6 (802.11ax) wireless client with 5 10/100/1000BaseT(X) ports, IP30, UN band, -40 to 75°C operating temperature	1.130,00 €
AWK-1165C-US	Industrial Wi-Fi 6 (802.11ax) wireless client with 5 10/100/1000BaseT(X) ports, IP30, US band, -25 to 60°C operating temperature	942,00 €
AWK-1165C-US-T	Industrial Wi-Fi 6 (802.11ax) wireless client with 5 10/100/1000BaseT(X) ports, IP30, US band, -40 to 75°C operating temperature	1.130,00 €

AWK-3131A-EU	Industrial Wi-Fi 4 (802.11n) wireless AP/bridge/client, EU band, -25 to 60°C operating temperature	963,00 €
AWK-3131A-EU-T	Industrial Wi-Fi 4 (802.11n) wireless AP/bridge/client, EU band, -40 to 75°C operating temperature	1.132,00 €
AWK-3131A-JP	Industrial Wi-Fi 4 (802.11n) wireless AP/bridge/client, JP band, -25 to 60°C operating temperature	963,00 €
AWK-3131A-JP-T	Industrial Wi-Fi 4 (802.11n) wireless AP/bridge/client, JP band, -40 to 75°C operating temperature	1.132,00 €
AWK-3131A-M12-RTG-EU-CT-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, M12 connectors, IP30, EU band, -40 to 75°C operating temperature, conformal coating	2.519,00 €
AWK-3131A-M12-RTG-EU-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, M12 connectors, IP30, EU band, -40 to 75°C operating temperature	2.178,00 €
AWK-3131A-M12-RTG-JP-CT-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, M12 connectors, IP30, JP band, -40 to 75°C operating temperature, conformal coating	2.519,00 €
AWK-3131A-M12-RTG-JP-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, M12 connectors, IP30, JP band, -40 to 75°C operating temperature	2.178,00 €
AWK-3131A-M12-RTG-US-CT-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, M12 connectors, IP30, US band, -40 to 75°C operating temperature, conformal coating	2.519,00 €
AWK-3131A-M12-RTG-US-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, M12 connectors, IP30, US band, -40 to 75°C operating temperature	2.178,00 €
AWK-3131A-SSC-RTG-EU-CT-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, SC connectors, IP30, EU band, -40 to 75°C operating temperature, conformal coating	2.837,00 €
AWK-3131A-SSC-RTG-EU-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, SC connectors, IP30, EU band, -40 to 75°C operating temperature	2.486,00 €
AWK-3131A-SSC-RTG-JP-CT-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, SC connectors, IP30, JP band, -40 to 75°C operating temperature, conformal coating	2.837,00 €
AWK-3131A-SSC-RTG-JP-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, SC connectors, IP30, JP band, -40 to 75°C operating temperature	2.486,00 €
AWK-3131A-SSC-RTG-US-CT-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, SC connectors, IP30, US band, -40 to 75°C operating temperature, conformal coating	2.837,00 €
AWK-3131A-SSC-RTG-US-T	Wi-Fi 4 (802.11n) railway onboard train-to-ground single-radio AP/client, SC connectors, IP30, US band, -40 to 75°C operating temperature	2.486,00 €
AWK-3131A-US	Industrial Wi-Fi 4 (802.11n) wireless AP/bridge/client, US band, -25 to 60°C operating temperature	963,00 €
AWK-3131A-US-T	Industrial Wi-Fi 4 (802.11n) wireless AP/bridge/client, US band, -40 to 75°C operating temperature	1.132,00 €
AWK-3251A-M12-RCC-UN	Wi-Fi 5 (802.11ac) railway onboard wireless AP/client, IP30, UN band, -25 to 60°C operating temperature	2.702,00 €
AWK-3251A-M12-RCC-UN-CT-T	Wi-Fi 5 (802.11ac) railway onboard wireless AP/client, IP30, UN band, -40 to 75°C operating temperature, conformal coating	3.452,00 €
AWK-3251A-M12-RCC-UN-T	Wi-Fi 5 (802.11ac) railway onboard wireless AP/client, IP30, UN band, -40 to 75°C operating temperature	2.927,00 €
AWK-3251A-M12-RCC-US	Wi-Fi 5 (802.11ac) railway onboard wireless AP/client, IP30, US band, -25 to 60°C operating temperature	2.702,00 €
AWK-3251A-M12-RCC-US-CT-T	Wi-Fi 5 (802.11ac) railway onboard wireless AP/client, IP30, US band, -40 to 75°C operating temperature, conformal coating	3.452,00 €
AWK-3251A-M12-RCC-US-T	Wi-Fi 5 (802.11ac) railway onboard wireless AP/client, IP30, US band, -40 to 75°C operating temperature	2.927,00 €

AWK-3252A-UN	Industrial Wi-Fi 5 (802.11ac) wireless AP/bridge/client, UN band, -25 to 60°C operating temperature	1.159,00 €
AWK-3252A-UN-T	Industrial Wi-Fi 5 (802.11ac) wireless AP/bridge/client, UN band, -40 to 75°C operating temperature	1.364,00 €
AWK-3252A-US	Industrial Wi-Fi 5 (802.11ac) wireless AP/bridge/client, US band, -25 to 60°C operating temperature	1.159,00 €
AWK-3252A-US-T	Industrial Wi-Fi 5 (802.11ac) wireless AP/bridge/client, US band, -40 to 75°C operating temperature	1.364,00 €
AWK-3262A-UN	Advanced industrial Wi-Fi 6 (802.11ax) wireless AP/bridge/client with 1 10/100/1000/2500BaseT(X) and 1 10/100/1000BaseT(X) port, IP30, UN band, -25 to 60°C operating temperature	1.325,00 €
AWK-3262A-UN-T	Advanced industrial Wi-Fi 6 (802.11ax) wireless AP/bridge/client with 1 10/100/1000/2500BaseT(X) and 1 10/100/1000BaseT(X) port, IP30, UN band, -40 to 75°C operating temperature	1.557,00 €
AWK-3262A-US	Advanced industrial Wi-Fi 6 (802.11ax) wireless AP/bridge/client with 1 10/100/1000/2500BaseT(X) and 1 10/100/1000BaseT(X) port, IP30, US band, -25 to 60°C operating temperature	1.325,00 €
AWK-3262A-US-T	Advanced industrial Wi-Fi 6 (802.11ax) wireless AP/bridge/client with 1 10/100/1000/2500BaseT(X) and 1 10/100/1000BaseT(X) port, IP30, US band, -40 to 75°C operating temperature	1.557,00 €
AWK-4131A-EU-T	Outdoor industrial Wi-Fi 4 (802.11n) wireless AP/bridge/client, IP68, EU band, -40 to 75°C operating temperature	2.045,00 €
AWK-4131A-JP-T	Outdoor industrial Wi-Fi 4 (802.11n) wireless AP/bridge/client, IP68, JP band, -40 to 75°C operating temperature	2.045,00 €
AWK-4131A-US-T	Outdoor industrial Wi-Fi 4 (802.11n) wireless AP/bridge/client, IP68, US band, -40 to 75°C operating temperature	2.045,00 €
AWK-4252A-UN-T	Outdoor industrial Wi-Fi 5 (802.11ac) wireless AP/bridge/client, IP68, UN band, -40 to 75°C operating temperature	2.469,00 €
AWK-4252A-US-T	Outdoor industrial Wi-Fi 5 (802.11ac) wireless AP/bridge/client, IP68, US band, -40 to 75°C operating temperature	2.469,00 €
AWK-4262A-UN-T	Advanced industrial outdoor Wi-Fi 6 (802.11ax) wireless AP/bridge/client with 1 M12 10/100/1000/2500BaseT(X) and 1 M12 10/100/1000BaseT(X) port, IP68, UN band, -40 to 75°C operating temperature	2.824,00 €
AWK-4262A-US-T	Advanced industrial outdoor Wi-Fi 6 (802.11ax) wireless AP/bridge/client with 1 M12 10/100/1000/2500BaseT(X) and 1 M12 10/100/1000BaseT(X) port, IP68, US band, -40 to 75°C operating temperature	2.824,00 €
BKT-DB44L	Cannot find any data	10,00 €
BKT-PWR	Chassis converter rackmount kit accessory package, 2 L-shaped metal plates, 8 screws (FMS M4 x 6 mm)	44,00 €
BST-1110-T	Industrial 5G signal booster, n78 and n48 bands, IP30, -40°C to 70°C operating temperature	628,00 €
BST-1220-T	Industrial 5G signal booster, n79 band, IP30, -40°C to 70°C operating temperature.	649,00 €
BXP-A100-E2-2L3C-T	Box computer with Intel Atom® x6211E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.195,00 €
BXP-A100-E2-8C-T	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.146,00 €
BXP-A100-E2-8L-T	Box computer with Intel Atom® x6211E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.684,00 €
BXP-A100-E2-T	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	2.608,00 €

BXP-A100-E2-T-Win10	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	3.504,00 €
BXP-A100-E4-2L3C-T	Box computer with Intel Atom® x6425E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.292,00 €
BXP-A100-E4-8C-T	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.260,00 €
BXP-A100-E4-8L-T	Box computer with Intel Atom® x6425E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.700,00 €
BXP-A100-E4-T	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	2.869,00 €
BXP-A100-E4-T-Win10	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	3.569,00 €
BXP-A101-E2-DR-T	DIN-rail box computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 70°C operating temperature	1.781,00 €
BXP-A101-E2-M2-DR-T	DIN-rail box computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 CFast slot, 1 SD slot, 1 M.2 M-key 2242 slot, 12/24 VDC power input, -30 to 70°C operating temperature	1.884,00 €
BXP-A101-E2-M2-T	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 CFast slot, 1 SD slot, 1 M.2 M-key 2242 slot, 12/24 VDC power input, -30 to 70°C operating temperature	1.884,00 €
BXP-A101-E2-T	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 70°C operating temperature	1.781,00 €
BXP-A101-E4-DR-T	DIN-rail box computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 70°C operating temperature	1.995,00 €
BXP-A101-E4-M2-DR-T	DIN-rail box computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 CFast slot, 1 SD slot, 1 M.2 M-key 2242 slot, 12/24 VDC power input, -30 to 70°C operating temperature	2.098,00 €
BXP-A101-E4-M2-T	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 CFast slot, 1 SD slot, 1 M.2 M-key 2242 slot, 12/24 VDC power input, -30 to 70°C operating temperature	2.098,00 €
BXP-A101-E4-T	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 70°C operating temperature	1.995,00 €
BXP-C100-C1-2L3C-T	Box computer with Intel® Celeron® 6305E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.244,00 €
BXP-C100-C1-8C-T	Box computer with Intel® Celeron® 6305E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.211,00 €
BXP-C100-C1-8L-T	Box computer with Intel® Celeron® 6305E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.602,00 €
BXP-C100-C1-T	Box computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	2.918,00 €

BXP-C100-C1-T-Win10	Box computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	4.042,00 €
BXP-C100-C5-2L3C-T	Box computer with Intel® Core® i5-1145G7E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	4.580,00 €
BXP-C100-C5-8C-T	Box computer with Intel® Core® i5-1145G7E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	4.613,00 €
BXP-C100-C5-8L-T	Box computer with Intel® Core® i5-1145G7E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	4.971,00 €
BXP-C100-C5-T	Box computer with Intel® Core® i5-1145G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	4.124,00 €
BXP-C100-C5-T-Win10	Box computer with Intel® Core® i5-1145G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	5.297,00 €
BXP-C100-C7-2L3C-T	Box computer with Intel® Core® i7-1185G7E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	4.971,00 €
BXP-C100-C7-8C-T	Box computer with Intel® Core® i7-1185G7E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	4.938,00 €
BXP-C100-C7-8L-T	Box computer with Intel® Core® i7-1185G7E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	5.395,00 €
BXP-C100-C7-T	Box computer with Intel® Core® i7-1185G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	4.678,00 €
BXP-C100-C7-T-Win10	Box computer with Intel® Core® i7-1185G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	6.030,00 €
CA-104	PC/104 bus, 4-port RS-232 module, 0 to 55°C operating temperature	173,00 €
CA-104-T	PC/104 bus, 4-port RS-232 module, -40 to 85°C operating temperature	234,00 €
CA-108	PC/104 bus, 8-port RS-232 module, 0 to 55°C operating temperature	287,00 €
CA-108-T	PC/104 bus, 8-port RS-232 module, -40 to 85°C operating temperature	388,00 €
CA-114	PC/104 bus, 4-port RS-232/422/485 module, 0 to 55°C operating temperature	287,00 €
CA-114-T	PC/104 bus with 4-port RS-232/422/485 module, -40 to 85°C operating temperature	388,00 €
CA-132	PC/104 bus, 2-port RS-422/485 module, 0 to 55°C operating temperature	193,00 €
CA-132I	PC/104 bus, 2-port RS-422/485 module with 2 kV optical isolation	287,00 €
CA-132I-T	PC/104 bus, 2-port RS-422/485 module with 2 kV optical isolation, -40 to 85°C operating temperature	388,00 €
CA-132-T	PC/104 bus, 2-port RS-422/485 module, -40 to 85°C operating temperature	251,00 €
CA-134I	PC/104 bus, 4-port RS-422/485 module with 2 kV optical isolation, 0 to 55°C operating temperature	522,00 €
CA-134I-T	PC/104 bus, 4-port RS-422/485 module with 2 kV optical isolation, -40 to 85°C operating temperature	688,00 €
CB-108	PC/104-Plus bus, 8-port RS-232 module, 0 to 55°C operating temperature	388,00 €
CB-108-T	PC/104-Plus bus, 8-port RS-232 module, -40 to 85°C operating temperature	493,00 €
CB-114	PC/104-Plus bus, 4-port RS-232/422/485 module, 0 to 55°C operating temperature	419,00 €

CB-114-T	PC/104-Plus bus, 4-port RS-232/422/485 module, -40 to 85°C operating temperature	537,00 €
CB-134I	PC/104-Plus bus, 4-port RS-422/485 module with 2 kV optical isolation, 0 to 55°C operating temperature	688,00 €
CB-134I-T	PC/104-Plus bus, 4-port RS-422/485 module with 2 kV optical isolation, -40 to 85°C operating temperature	880,00 €
CB-602I w/o Cable	2-port CAN bus PC/104-Plus module, with isolation, 0 to 55°C operating temperature	562,00 €
CB-602I-T w/o Cable	2-port CAN bus PC/104-Plus module, with isolation, -40 to 85°C operating temperature	645,00 €
CBL-F37M37-1M	DB37 female to 4 x DB37 male serial cable, 1 m	29,00 €
CBL-F9DPF1x4-BK-100	Console cable with 4-pin connector, 1 m	6,00 €
CBL-F9M9-150	DB9 female to DB9 male serial cable, 1.5 m	21,00 €
CBL-F9M9-20	DB9 female to DB9 male serial cable, 20 cm	15,00 €
CBL-HSF2x10-15	20-pin female to 20-pin female serial cable, 15 cm	14,00 €
CBL-M12(FF4P)/Open-BK-100-IP68	A-coded female M12-to-4-pin open cable, black, IP68-rated, 1 m	79,00 €
CBL-M12(FF5P)/OPEN-100 IP67	A-coded female M12-to-5-pin open wire cable, black, IP67-rated, 1 m	31,00 €
CBL-M12(FF5P)OPEN-200-IP67	M12 IP67 5 pin to Open 200m cable	42,00 €
CBL-M12BMM5PF9-BK-150-IP68	B-coded male M12-to-5-pin DB9 console cable, black, IP68-rated, 1.5 m	89,00 €
CBL-M12D(MM4P)/RJ45-100 IP67	D-coded male M12-to-RJ45 Ethernet cable, black, IP67-rated, 1 m	31,00 €
CBL-M12DFF4PRJ45-BK-10-IP67	M12 D-coded IP67 to RJ45 10m cable	58,00 €
CBL-M12DMM4PM12DMM4P-BK-100-IP67	D-coded male M12-to-D-coded female M12 Ethernet cable, black, IP67-rated, 1 m	125,00 €
CBL-M12FF4POPEN-150 IP67	M12-Open power cable, 4-pin A-coded female connector, IP67, 1.5 m	84,00 €
CBL-M12FF4POPEN-300 IP67	M12-Open power cable, 4-pin A-coded female connector, IP67, 3 m	103,00 €
CBL-M12FF5PF9-BK-150-IP67	A-coded female M12-to-5-pin DB9 console cable, black, IP67-rated, 1.5 m	74,00 €
CBL-M12KFF5POPEN-O-150-IP67	K-coded female M12-to-5-pin open wire power cable, orange, IP67-rated, 1.5 m	388,00 €
CBL-M12MM8PRJ45-BK-100-IP67	M12 IP67 to RJ45 100m cable	65,00 €

CBL-M12XMM8PRJ45-BK-100-IP67	M12-to-RJ45 Cat-5E UTP gigabit Ethernet cable, 8-pin X-coded male connector, IP67, 1 m	416,00 €
CBL-M12XMM8PRJ45-BK-200-IP67	M12-to-RJ45 Cat-5E UTP gigabit Ethernet cable, 8-pin X-coded male connector, IP67, 2 m	229,00 €
CBL-M12XMM8PRJ45-Y-200-IP67	X-coded male M12-to-RJ45 Ethernet cable, yellow, IP67-rated, 2 m	224,00 €
CBL-M12XMM8P-Y-100-IP67	X-coded male M12-to-8-pin open wire cable, yellow, IP67-rated, 1 m	352,00 €
CBL-M12XMM8P-Y-300-IP67	X-coded male M12-to-8-pin open wire cable, yellow, IP67-rated, 3 m	395,00 €
CBL-M23(FF6P)/OPEN-BK-100 IP67	M23 female M23-to-6-pin open wire power cable, black, IP67-rated, 1 m	165,00 €
CBL-M25M9x2-50	DB25 male to 2 x DB9 male serial cable, 50 cm	15,00 €
CBL-M44M25x4-50	DB44 male to 4 DB25 male serial cable, 50 cm	29,00 €
CBL-M44M9x4-50	DB44 male to DB9 male serial cable, 50 cm	25,00 €
CBL-M44M9x4-50 (POS)	DB44 male to 4 x DB9 male serial cable, 50 cm	25,00 €
CBL-M62F62-150	DB62 male to DB62 female serial cable, 1.5 m	53,00 €
CBL-M62M25x8-100	DB62 male to 8 x DB25 male serial cable, 1 m	57,00 €
CBL-M62M62-150	DB62 male to DB62 male serial cable, 1.5 m	49,00 €
CBL-M62M9x8-100	DB62 male to 8 x DB9 male serial cable, 1 m	49,00 €
CBL-M68F62-150	DB68 male to DB62 female serial cable, 1.5 m	63,00 €
CBL-M68M25x8-100	SCSI VHDCI 68 to 8 x DB25 male serial cable, 1 m	91,00 €
CBL-M68M62-150	DB68 male to DB62 male serial cable, 1.5 m	84,00 €
CBL-M68M9x8-100	SCSI VHDCI 68 to 8 x DB9 male serial cable, 1 m	87,00 €
CBL-M78M25x8-100	DB78 male to 8 x DB25 male serial cable, 1 m	97,00 €
CBL-M78M9x8-100	DB78 male to 8 x DB9 male serial cable, 1 m	94,00 €
CBL-M9HSF1x10H-15-01	10-pin female to 1 DB9 male serial cable, 15 cm	12,00 €
CBL-M9HSF1x10H-15-02	10-pin female to 1 DB9 male serial cable, 15 cm	12,00 €
CBL-M9x2HSF2x10H-15	20-pin female to 2 DB9 male serial cables, 15 cm	18,00 €

CBL-PJ21NOPEN-BK-30 w/Nut	CBL-PJ21NOPEN-BK-30 w/Nut	11,00 €
CBL-PJTB-10	Non-locking barrel plug to bare-wire cable	6,00 €
CBL-RJ458P-100	8-pin RJ45 CAT5 Ethernet cable, 1 m	8,00 €
CBL-RJ458P-Cisco-BK-180	8-pin RJ45 to 8-pin RJ45 serial cable, 1.8 m, for Cisco console port	15,00 €
CBL-RJ45F25-150	8-pin RJ45 to DB25 female serial cable, 1.5 m	8,00 €
CBL-RJ45F9-150	8-pin RJ45 to DB9 female serial cable, 1.5m	14,00 €
CBL-RJ45M25-150	8-pin RJ45 to DB25 male serial cable, 1.5m	8,00 €
CBL-RJ45M9-150	8-pin RJ45 to DB9 male serial cable, 1.5m	14,00 €
CBL-RJ45SF25-150	8-pin RJ45 to DB25 female serial cable with shielding, 1.5m	15,00 €
CBL-RJ45SF9-150	8-pin RJ45 to DB9 female serial cable with shielding, 1.5m	11,00 €
CBL-RJ45SM25-150	8-pin RJ45 to DB25 male serial cable with shielding, 1.5m	11,00 €
CBL-RJ45SM9-150	8-pin RJ45 to DB9 male serial cable with shielding, 1.5m	11,00 €
CBL-USB3-BA-BK-120	USB 3.2 Gen 1 cable, type A-to-type B, 1.2 m	20,00 €
CBL-USB3-BA-G-028	USB 3.2 Gen 1 cable, type A-to-type B with latch and screw, 0.28 m	31,00 €
CBL-USB3-BA-G-120	USB 3.2 Gen 1 cable, type A-to-type B with latch and screw, 1.2 m	29,00 €
CBL-USBA/B-100	USB 2.0 cable, type A-to-type B, 1 m	6,00 €
CBL-USBAMM12BMM5P-BK-120-IP68	120cm B-coded USB-to-5-pin cable with IP68-rated, 5-pin male M12 connector	94,00 €
CBL-USBAP-50	USB A male/2.1 mm DC Jack cable, 50 cm	6,00 €
CCG-1510-T	Industrial private 5G cellular gateway, n1/n3/n28/n41/n48/n77/n78 bands, 2 10/100/1000BaseT(X) RJ45 ports, IP30, -40 to 70°C operating temperature	2.141,00 €
CM-600-2MSC/2TX	Fast Ethernet interface module with 2 10/100BaseT(X) ports, RJ45 connectors, and 2 100BaseFX multi-mode ports, SC connectors, -40 to 75°C operating temperature	755,00 €
CM-600-2SSC/2TX	Fast Ethernet interface module with 2 10/100BaseT(X) ports, RJ45 connectors, and 2 100BaseFX single-mode ports, SC connectors, -40 to 75°C operating temperature	1.724,00 €
CM-600-3MSC/1TX	Fast Ethernet interface module with 1 10/100BaseT(X) port, RJ45 connector, and 3 100BaseFX multi-mode ports, SC connectors, -40 to 75°C operating temperature	946,00 €
CM-600-3SSC/1TX	Fast Ethernet interface module with 1 10/100BaseT(X) port, RJ45 connector, and 3 100BaseFX single-mode ports, SC connectors, -40 to 75°C operating temperature	2.148,00 €
CM-600-4MSC	Fast Ethernet interface module with 4 100BaseFX multi-mode ports, SC connectors, -40 to 75°C operating temperature	1.147,00 €
CM-600-4MST	Fast Ethernet interface module with 4 100BaseFX multi-mode ports, ST connectors, -40 to 75°C operating temperature	1.147,00 €
CM-600-4SSC	Fast Ethernet interface module with 4 100BaseFX single-mode ports, SC connectors, -40 to 75°C operating temperature	2.755,00 €
CM-600-4TX	Fast Ethernet interface module with 4 10/100BaseT(X) ports, RJ45 connectors, -40 to 75°C operating temperature	355,00 €

CN20030	10-pin RJ45 to DB25 female serial cable	11,00 €
CN20040	10-pin RJ45 to DB25 male serial cable	11,00 €
CN20060	10-pin RJ45 to DB9 male serial cable	11,00 €
CN20070	10-pin RJ50 to DB9 female serial cable	8,00 €
CN2510-16	16-port RS-232 Async Server, 100 to 240 VAC power input	1.657,00 €
CN2510-16-48V	16-port RS-232 Async Server, +/-48 VDC power input	1.756,00 €
CN2510-8	8-port RS-232 Async Server, 100 to 240 VAC power input	1.486,00 €
CN2510-8-48V	8-port RS-232 Async Server, +/-48 VDC power input	1.591,00 €
CN2610-16	Dual-LAN terminal server with 16 RS-232 ports	2.332,00 €
CN2610-16-2AC	Dual-LAN, dual-AC-power terminal server with 16 RS-232 ports	2.501,00 €
CN2610-8	Dual-LAN terminal server with 8 RS-232 ports	1.841,00 €
CN2610-8-2AC	Dual-LAN, dual-AC-power terminal server with 8 RS-232 ports	2.009,00 €
CN2650-16	Dual-LAN terminal server with 16 RS-232/422/485 ports	2.434,00 €
CN2650-16-2AC	Dual-LAN, dual-AC-power terminal server with 16 RS-232/422/485 ports	2.602,00 €
CN2650-16-2AC-T	Dual-LAN, dual-AC-power terminal server with 16 RS-232/422/485 ports, -40 to 75°C operating temperature	3.548,00 €
CN2650-8	Dual-LAN terminal server with 8 RS-232/422/485 ports	1.879,00 €
CN2650-8-2AC	Dual-LAN, dual-AC-power terminal server with 8 RS-232/422/485 ports	2.047,00 €
CN2650-8-2AC-T	Dual-LAN, dual-AC-power terminal server with 8 RS-232/422/485 ports, -40 to 75°C operating temperature	2.786,00 €
CN2650I-16	Dual-LAN terminal server with 16 RS-232/422/485 ports, 2 kV optical isolation	3.367,00 €
CN2650I-16-2AC	Dual-LAN, dual-AC-power terminal server with 16 RS-232/422/485 ports, 2 kV optical isolation	3.530,00 €
CN2650I-16-HV-T	Dual-LAN terminal server with 16 RS-232/422/485 ports, 2 kV optical isolation, 88 to 300 VDC power input, -40 to 85°C operating temperature	4.055,00 €
CN2650I-8	Dual-LAN terminal server with 8 RS-232/422/485 ports, 2 kV optical isolation	2.350,00 €
CN2650I-8-2AC	Dual-LAN, dual-AC-power terminal server with 8 RS-232/422/485 ports, 2 kV optical isolation	2.517,00 €
CN2650I-8-HV-T	Dual-LAN terminal server with 8 RS-232/422/485 ports, 2 kV optical isolation, 88 to 300 VDC power input, -40 to 85°C operating temperature	2.927,00 €
CP-102E	2-port RS-232 PCI Express x1 serial board	139,00 €
CP-102EL-DB9M	2-port RS-232 low-profile PCI Express x1 serial board (includes DB9 male cable)	150,00 €
CP-102N-I-T	2-port RS-232 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	350,00 €
CP-102N-T	2-port RS-232 Mini PCI Express serial board, -40 to 85°C operating temperature	194,00 €
CP-102U	2-port RS-232 Universal PCI serial board, 0 to 55°C operating temperature	86,00 €
CP-102UL-DB9M	2-port RS-232 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	97,00 €
CP-102UL-T	2-port RS-232 low-profile Universal PCI serial board, -40 to 85°C operating temperature	139,00 €
CP-102U-T	2-port RS-232 Universal PCI serial board, -40 to 85°C operating temperature	119,00 €
CP-104EL-A w/o Cable	4-port RS-232 low-profile PCI Express x1 serial board, without cable	254,00 €
CP-104EL-A-DB25M	4-port RS-232 low-profile PCI Express x1 serial board (includes DB25 male cable)	268,00 €
CP-104EL-A-DB9M	4-port RS-232 low-profile PCI Express x1 serial board (includes DB9 male cable)	268,00 €
CP-104JU	4-port RS-232 Universal PCI serial board with RJ45 ports on the board, 0 to 55°C operating temperature	184,00 €
CP-104JU-T	4-port RS-232 Universal PCI serial board with RJ45 ports on the board, -40 to 85°C operating temperature	205,00 €
CP-104N-I-T	4-port RS-232 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	626,00 €
CP-104N-T	4-port RS-232 Mini PCI Express serial board, -40 to 85°C operating temperature	345,00 €
CP-104UL w/o Cable	4-port RS-232 low-profile Universal PCI serial board, without cable	150,00 €

CP-104UL-DB25M	4-port RS-232 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB25 male cable)	162,00 €
CP-104UL-DB9M	4-port RS-232 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	162,00 €
CP-104UL-T	4-port RS-232 low-profile Universal PCI serial board, -40 to 85°C operating temperature	223,00 €
CP-112N-T	2-port RS-232/422/485 Mini PCI Express serial board, -40°C to 85 operating temperature	255,00 €
CP-112UL-DB9M	2-port RS-232/422/485 low-profile Universal PCI board, 0 to 55°C operating temperature (includes DB9 male cable)	183,00 €
CP-112UL-I-DB9M	2-port RS-232/422/485 low-profile Universal PCI board with optical isolation, 0 to 55°C operating temperature (includes DB9 male cable)	322,00 €
CP-112UL-I-T	2-port RS-232/422/485 low-profile Universal PCI board with optical isolation, -40 to 85°C operating temperature	410,00 €
CP-112UL-T	2-port RS-232/422/485 low-profile Universal PCI board, -40 to 85°C operating temperature	275,00 €
CP-114EL	4-port RS-232/422/485 low-profile PCI Express x1 serial board	307,00 €
CP-114EL-DB25M	4-port RS-232/422/485 low-profile PCI Express x1 serial board (includes DB25 male cable)	322,00 €
CP-114EL-DB9M	4-port RS-232/422/485 low-profile PCI Express x1 serial board (includes DB9 male cable)	322,00 €
CP-114EL-I	4-port RS-232/422/485 low-profile PCI Express x1 serial board with optical isolation	630,00 €
CP-114EL-I-DB25M	4-port RS-232/422/485 low-profile PCI Express x1 serial board with optical isolation (includes DB25 male cable)	645,00 €
CP-114EL-I-DB9M	4-port RS-232/422/485 low-profile PCI Express x1 serial board with optical isolation (includes DB9 male cable)	645,00 €
CP-114N-T	4-port RS-232/422/485 Mini PCI Express serial board, -40°C to 85 operating temperature	432,00 €
CP-114UL w/o Cable	4-port RS-232/422/485 low-profile Universal PCI board, 0 to 55°C operating temperature	299,00 €
CP-114UL-DB25M	4-port RS-232/422/485 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB25 male cable)	317,00 €
CP-114UL-DB9M	4-port RS-232/422/485 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	317,00 €
CP-114UL-I	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	661,00 €
CP-114UL-I-DB25M	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature (includes DB25 male cable)	667,00 €
CP-114UL-I-DB9M	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature (includes DB9 male cable)	667,00 €
CP-114UL-I-T	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, -40 to 85°C operating temperature	830,00 €
CP-114UL-T	4-port RS-232/422/485 low-profile Universal PCI serial board, -40 to 85°C operating temperature	332,00 €
CP-116E-A w/o cable	16-port RS-232/422/485 PCI Express board with 4 kV surge protection, 0 to 55°C operating temperature	1.177,00 €
CP-118E-A-I w/o cable	8-port RS-232/422/485 PCI Express x1 serial board with surge protection and electrical isolation	1.289,00 €
CP-118EL-A w/o Cable	8-port RS-232/422/485 low-profile PCI Express x1 serial board	600,00 €
CP-118U	8-port RS-232/422/485 Universal PCI serial board, 0 to 55°C operating temperature	516,00 €
CP-118U-I	8-port RS-232/422/485 Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	1.192,00 €

CP-118U-I-T	8-port RS-232/422/485 Universal PCI serial board with optical isolation, -40 to 85°C operating temperature	1.239,00 €
CP-118U-T	8-port RS-232/422/485 Universal PCI serial board, -40 to 85°C operating temperature	547,00 €
CP-132EL-DB9M	2-port RS-422/485 low-profile PCI Express x1 serial board (includes DB9 male cable)	184,00 €
CP-132EL-I-DB9M	2-port RS-422/485 low-profile PCI Express x1 serial board with optical isolation (includes DB9 male cable)	326,00 €
CP-132N-I-T	2-port RS-422/485 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	365,00 €
CP-132N-T	2-port RS-422/485 Mini PCI Express serial board, -40 to 85°C operating temperature	199,00 €
CP-132UL-DB9M	2-port RS-422/485 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	146,00 €
CP-132UL-I-DB9M	2-port RS-422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature (includes DB9 male cable)	352,00 €
CP-132UL-I-T	2-port RS-422/485 low-profile Universal PCI serial board with optical isolation, -40°C to 85 operating temperature	323,00 €
CP-132UL-T	2-port RS-422/485 low-profile Universal PCI serial board, -40°C to 85 operating temperature	184,00 €
CP-134EL-A-I w/o cable	4-port RS-422/485 low-profile PCI Express x1 serial board with surge protection and electrical isolation	615,00 €
CP-134EL-A-I-DB25M	4-port RS-422/485 low-profile PCI Express board with 4 kV surge protection, 2 kV electrical isolation, DB25 male cable, 0 to 55°C operating temperature	630,00 €
CP-134EL-A-I-DB9M	4-port RS-422/485 low-profile PCI Express board with 4 kV surge protection, 2 kV electrical isolation, DB9 male cable, 0 to 55°C operating temperature	630,00 €
CP-134N-I-T	4-port RS-422/485 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	730,00 €
CP-134U w/o Cable	4-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature	290,00 €
CP-134U-DB25M	4-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature (includes DB25 male cable)	311,00 €
CP-134U-DB9M	4-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	311,00 €
CP-134U-I w/o Cable	4-port RS-422/485 Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	667,00 €
CP-134U-I-DB25M	4-port RS-422/485 Universal PCI board with 2 kV electrical isolation, DB25 male cable, 0 to 55°C operating temperature	695,00 €
CP-134U-I-DB9M	4-port RS-422/485 Universal PCI board with 2 kV electrical isolation, DB9 male cable, 0 to 55°C operating temperature	695,00 €
CP-134U-I-T	4-port RS-422/485 Universal PCI board with 2 kV electrical isolation, -40 to 85°C operating temperature	680,00 €
CP-134U-T	4-port RS-422/485 Universal PCI serial board, -40 to 85°C operating temperature	304,00 €
CP-138E-A-I w/o cable	8-port RS-422/485 PCI Express board with 4 kV surge protection, 2 kV electrical isolation, 0 to 55°C operating temperature	1.114,00 €
CP-138U	8-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature	487,00 €
CP-138U-I	8-port RS-422/485 Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	966,00 €
CP-138U-I-T	8-port RS-422/485 Universal PCI serial board with optical isolation, -40 to 85°C operating temperature	1.032,00 €
CP-138U-T	8-port RS-422/485 Universal PCI serial board, -40 to 85°C operating temperature	499,00 €
CP-168EL-A w/o Cable	8-port RS-232 low-profile PCI Express x1 serial board	326,00 €
CP-168U	8-port RS-232 Universal PCI serial board, 0 to 55°C operating temperature	239,00 €
CP-168U-T	8-port RS-232 Universal PCI serial board, -40 to 85°C operating temperature	304,00 €

CP-602E-I w/o Cable	2-port CAN bus PCI Express board with 2 kV electrical isolation, 0 to 55°C operating temperature	586,00 €
CP-602E-I-T w/o Cable	2-port CAN bus PCI Express board with 2 kV electrical isolation, -40 to 85°C operating temperature	680,00 €
CP-602U-I w/o Cable	2-port CAN bus Universal PCI board with 2 kV electrical isolation, 0 to 55°C operating temperature	522,00 €
CP-602U-I-T w/o Cable	2-port CAN bus Universal PCI board with 2 kV electrical isolation, -40 to 85°C operating temperature	606,00 €
CRF-MHF/SMA(M)-14.2	CRF-MHF/SMA(M)-14.2	11,00 €
CRF-SMA(M)/N(M)-300	N-type (male) to SMA (male) CFD200 cable, 3 m	62,00 €
CSM-200-1213	10/100BaseT(X) to 100BaseFX slide-in module media converter, multi-mode ST connector	349,00 €
CSM-200-1214	10/100BaseT(X) to 100BaseFX slide-in module media converter, multi-mode SC connector	349,00 €
CSM-200-1218	10/100BaseT(X) to 100BaseFX slide-in module media converter, single-mode SC connector	490,00 €
CSM-400-1213	10/100BaseT(X)-to-100BaseFX slide-in management module converter with ST connector, multi-mode, 0 to 55°C operating temperature	394,00 €
CSM-400-1213-T	10/100BaseT(X) to 100BaseFX slide-in management module converter, multi-mode ST connector, -40 to 75°C operating temperature	490,00 €
CSM-400-1214	10/100BaseT(X) to 100BaseFX slide-in management module converter, multi-mode SC connector, -20 to 55°C operating temperature	394,00 €
CSM-400-1214-T	10/100BaseT(X) to 100BaseFX slide-in management module converter, multi-mode SC connector, -40 to 75°C operating temperature	490,00 €
CSM-400-1218	10/100BaseT(X) to 100BaseFX slide-in management module converter, single-mode SC connector, -20 to 55°C operating temperature	522,00 €
CSM-400-1218-T	10/100BaseT(X) to 100BaseFX slide-in management module converter, single-mode SC connector, -40 to 75°C operating temperature	645,00 €
CSM-400-1224	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-A single-mode SC connector, -20 to 55°C operating temperature	522,00 €
CSM-400-1224-T	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-A single-mode SC connector, -40 to 75°C operating temperature	645,00 €
CSM-400-1225	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-B single-mode SC connector, -20 to 55°C operating temperature	522,00 €
CSM-400-1225-T	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-B single-mode SC connector, -40 to 75°C operating temperature	645,00 €
CSM-G200-1221	10/100/1000BaseT(X)-to-100/1000BaseSFP slide-in media converter module	391,00 €
DA-680 SSD/HDD Kit	SSD/HDD kit with SSD/HDD tray, cables, screws for the DA-680 Series	67,00 €
DA-680-I-16-WL3-H	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 16 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC single power input, -25 to 55°C operating temperature	4.359,00 €
DA-680-I-16-WL3-HH	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 16 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC dual power inputs, -25 to 55°C operating temperature	4.474,00 €
DA-680-I-8-WL3-H	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 8 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC single power input, -25 to 55°C operating temperature	3.931,00 €

DA-680-I-8-WL3-HH	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 8 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC dual power inputs, -25 to 55°C operating temperature	4.031,00 €
DA-681C-KL1-HH-T	Intel® 7th Gen Celeron® 3965U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 10 RS-485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 1 SSD slot, dual power, -40 to 70°C operating temperature	5.351,00 €
DA-681C-KL1-H-T	Intel® 7th Gen Celeron® 3965U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 10 RS-485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 1 SSD slot, single power, -40 to 70°C operating temperature	4.425,00 €
DA-681C-KL3-HH-T	Intel® 7th Gen Core™ i3-7100U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 10 RS-485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 1 SSD slot, dual power, -40 to 70°C operating temperature	7.041,00 €
DA-682C-KL1-HH-T	Intel® Celeron® 3965U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	5.703,00 €
DA-682C-KL3-HH-T	Intel® 7th Gen Core™ i3-7100U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	7.132,00 €
DA-682C-KL5-HH-T	Intel® 7th Gen Core™ i5-7300U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	8.321,00 €
DA-682C-KL7-HH-T	Intel® 7th Gen Core™ i7-7600U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	9.384,00 €
DA-720 HDD Kit	DA-720 HDD/SSD kit	58,00 €
DA-720-C5-DPP	Rackmount computer with Core i5-6300U, 2.4 GHz processor, dual-core processor, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 3 PCIe expansion slots, 1 VGA port, 1 DVI-D port, IEC 61850-3 compliant, -25 to 55°C operating temperature	7.505,00 €
DA-720-C5-DPP-LX	Rackmount computer with Core i5-6300U, 2.4 GHz processor, dual-core processor, 4 GB RAM and Linux Debian 8 64-bit, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 1 mSATA slot with 8 GB SSD preinstalled, 3 PCIe expansion slots, 1 VGA port, 1 DVI-D port, IEC 61850-3 compliant, -25 to 55°C operating temperature	8.180,00 €
DA-720-C7-DPP	Rackmount computer with Core i7-6600U, 2.6 GHz processor, dual-core processor, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 3 PCIe expansion slots, 1 VGA port, 1 DVI-D port, IEC 61850-3 compliant, -25 to 55°C operating temperature	8.694,00 €
DA-720-C7-DPP-LX	Rackmount computer with Core i7-6600U, 2.6 GHz processor, dual-core processor, 4 GB RAM and Linux Debian 8 64-bit, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 1 mSATA slot with 8 GB SSD preinstalled, 3 PCIe expansion slots, 1 VGA port, 1 DVI-D port, IEC 61850-3 compliant, -25 to 55°C operating temperature	9.357,00 €
DA-820C-KL3-HH-T	x86 computer with Intel® Core™ i3-7102E processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, dual AC power, -40 to 70°C operating temperature	7.662,00 €
DA-820C-KL3-H-T	x86 computer with Intel® Core™ i3-7102E processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, single AC power, -40 to 70°C operating temperature	7.182,00 €
DA-820C-KL5-HH-T	x86 computer with Intel® Core™ i5-7442EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, dual AC power, -40 to 70°C operating temperature	9.394,00 €
DA-820C-KL5-H-T	x86 computer with Intel® Core™ i5-7442EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, single AC power, -40 to 70°C operating temperature	8.934,00 €

DA-820C-KL7-H	x86 computer with Intel® Core™ i7-7820EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, single AC power, -25 to 55°C operating temperature	9.559,00 €
DA-820C-KL7-HH	x86 computer with Intel® Core™ i7-7820EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual AC power, -25 to 55°C operating temperature	10.042,00 €
DA-820C-KLXL-HH-T	x86 computer with Intel® Core™ Xeon E3-1505L v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, dual AC power, -40 to 70°C operating temperature	10.584,00 €
DA-820C-KLXL-H-T	x86 computer with Intel® Core™ Xeon E3-1505L v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, single AC power, -40 to 70°C operating temperature	10.098,00 €
DA-820C-KLXM-H	x86 computer with Intel® Core™ Xeon E3-1505M v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, single AC power, -25 to 55°C operating temperature	10.425,00 €
DA-820C-KLXM-HH	x86 computer with Intel® Core™ Xeon E3-1505M v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual AC power, -25 to 55°C operating temperature	10.905,00 €
DA-820E-C3-HH-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i3-1320PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-150-HV power modules, -40 to 70°C operating temperature	8.454,00 €
DA-820E-C3-H-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i3-1320PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-150-HV power module, -40 to 70°C operating temperature	7.861,00 €
DA-820E-C3-LL-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i3-1320PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-120-LV power modules, -40 to 70°C operating temperature	8.218,00 €
DA-820E-C3-L-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i3-1320PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-120-LV power module, -40 to 70°C operating temperature	7.747,00 €
DA-820E-C5-HH-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i5-1340PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-150-HV power modules, -40 to 70°C operating temperature	8.633,00 €
DA-820E-C5-H-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i5-1340PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-150-HV power module, -40 to 70°C operating temperature	8.047,00 €
DA-820E-C5-LL-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i5-1340PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-120-LV power modules, -40 to 70°C operating temperature	8.404,00 €
DA-820E-C5-L-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i5-1340PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-120-LV power module, -40 to 70°C operating temperature	7.925,00 €

DA-820E-C7-HH-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i7-1370PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-150-HV power module, -40 to 70°C operating temperature	8.911,00 €
DA-820E-C7-H-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i7-1370PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-150-HV power module, -40 to 70°C operating temperature	8.318,00 €
DA-820E-C7-LL-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i7-1370PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-120-LV power module, -40 to 70°C operating temperature	8.676,00 €
DA-820E-C7-L-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i7-1370PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-120-LV power module, -40 to 70°C operating temperature	8.204,00 €
DA-920E-X08-H	IEC 61850-3 Fanless Server with Xeon D-1834 CPU, w/o RAM, SSD, OS, single 100-240VAC/VDC PSU	8.335,00 €
DA-920E-X08-HH	IEC 61850-3 Fanless Server with Xeon D-1834 CPU, w/o RAM, SSD, OS, dual 100-240VAC/VDC PSU	9.107,00 €
DA-920E-X08-HH (Custom)	IEC 61850-3 Fanless Server with Xeon D-1834 CPU, w/o RAM, SSD, OS, dual 100-240VAC/VDC PSU	9.107,00 €
DA-920E-X08-HW	IEC 61850-3 Fanless Server with Xeon D-1834 CPU, w/o RAM, SSD, OS, 1 x 100-240VAC/VDC, 1 x 24-110VDC PSU	9.266,00 €
DA-920E-X08-W	IEC 61850-3 Fanless Server with Xeon D-1834 CPU, w/o RAM, SSD, OS, single 24-110VDC PSU	8.495,00 €
DA-920E-X08-WW	IEC 61850-3 Fanless Server with Xeon D-1834 CPU, w/o RAM, SSD, OS, dual 24-110VDC PSU	9.426,00 €
DA-GX02-SFP-T	2-port 100/1000 Mbps fiber card with 2 SFP slots, 1 PCIe interface	829,00 €
DA-IRIG-B-S-02-T	IRIG-B expansion module, PCI interface, 1 fiber IRIG-B input, 1 DB9M input/output, 1 DB9M output, -40 to 75°C operating temperature	480,00 €
DA-PRP-HSR-I210	PRP/HSR expansion card with RJ45 and SFP combo port	2.267,00 €
DA-PWR-120-LV	Hot-swappable power-supply module (48 VDC) with system power input and terminal block for DA-820E computers	479,00 €
DA-PWR-150-HV	Hot-swappable power-supply module (100 to 240 VAC/VDC) with system power input and terminal block for DA-820E computers	594,00 €
DE-211	1-port RS-232/422/485 device server with 10 Mbps Ethernet connection	227,00 €
DE-2-IRIGB-4-DI/DO	2-port IRIG-B time synchronization module with 4DI/DO	700,00 €
DE-2-SATA	Expansion module with 2 2.5-inch SSD/HDD slots	759,00 €
DE-311	1-port RS-232/422/485 device server with 10/100 Mbps Ethernet connection	238,00 €
DE-FX02-SFP-T	2-port 100 Mbps fiber card, 2 SFP slots, PCIe interface, -40 to 75°C operating temperature (SFP module excluded)	864,00 €
DE-LN04-RJ	4-port 10/100/1000 Mbps PCIe LAN module	539,00 €
DE-LN08-RJ	8-port 10/100/1000 Mbps PCIe LAN module	693,00 €
DE-PRP-HSR-EF	2-port 100/1000 Mbps PCIe PRP/HSR LAN module	2.267,00 €
DE-SP08-I-TB	8-port RS-232/422/485 PCIe serial module	717,00 €
DK-107-01	DIN-rail mounting kit with 1 plate (107 x 29 mm) and 5 M3 x 4 mm screws	21,00 €
DK-115-01	DIN-rail mounting kit with 1 plate (89 x 19 mm), 3 M3 x 5 mm screws and SK-115-01 side-mounting kit	52,00 €
DK-25-01	DIN-rail mounting kit, 2 screws	10,00 €
DK35A	DIN-rail mounting kit, 35 mm	6,00 €
DK-43-01	DIN-rail mounting kit with 2 plates (42.5 x 19.3 mm), 4 M3 x 6 mm screws, black, works with the wall-mounting kit of your product	6,00 €
DK-89-01	DIN-rail mounting kit with 1 plate (89 x 19 x 9 mm), 3 M3 x 5 mm screws	15,00 €

DK-DC50131	DIN-rail mounting kit	37,00 €
DK-M12-305	DIN-rail mounting kit for EDS-305-M12	21,00 €
DK-TN-5305A	DIN-rail mounting kit with 1 plate, 3 screws for the TN-5305A Series	26,00 €
DK-TN-5308	DIN-rail mounting kit for the TN-5308 Series	37,00 €
DK-TN-5308A	DIN-rail mounting kit with 1 plate, 3 screws for the TN-5308A non-PoE Series	43,00 €
DK-TN-5308A-PoE	DIN-rail mounting kit with 1 plate, 3 screws for the TN-5308A PoE Series	43,00 €
DK-UC-5000	DIN-rail mounting kit with screws for the UC-5000 Series	24,00 €
DK-UP1200	DIN rail (25x48.3 mm) with 2 screws (FMS M3X6)	22,00 €
DK-UP1400	DIN-rail/wall-mounting kit, 2 plates, 6 screws, and 2 DIN-rail plates, 4 screws	22,00 €
DK-UP1400-G2	DIN Rail mounitng kits for UPort 1400-G2	34,00 €
DK-UP-14168	DIN-rail kit with 2 plates (89 x 19 mm), 6 screws (FMS M3 x 5 mm) for the UPort 1400 (V1.5.0 and after) and 1600-8 (V1.4.0 and after) models	47,00 €
DK-UP1600-G2	DIN Rail mounitng kits for UPort 1600-G2	40,00 €
DK-UP-42A	DIN-rail mounting kit for the UPort 400A/200A Series, 107 x 29 mm (4.21 x 1.14 in), with 4 M3 x 5 mm screws	19,00 €
DN-FX04	4-port 100M/1000M SFP Ethernet module	1.344,00 €
DN-LN04-RJ	4-port 10/100/1000 Mbps PCIe LAN module with RJ45 connectors	952,00 €
DN-PRP-HSR-I210	PRP/HSR expansion module with RJ45 and SFP combo port	2.273,00 €
DN-SP08-I-DB	8-port software-selectable RS-232/422/485 PCIe serial module with DB9 connector	1.145,00 €
DN-SP08-I-TB	8-port software-selectable RS-232/422/485 PCIe serial module with terminal-block connector	1.145,00 €
DRP-A100-E2-2L4C-T	DIN-rail computer with Intel Atom® x6211E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.423,00 €
DRP-A100-E2-6C-T	DIN-rail computer with Intel Atom® x6211E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.292,00 €
DRP-A100-E2-8L-T	DIN-rail computer with Intel Atom® x6211E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.716,00 €
DRP-A100-E2-T	DIN-rail computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	2.714,00 €
DRP-A100-E2-T-Win10	DIN-rail computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	3.602,00 €
DRP-A100-E4-2L4C-T	DIN-rail computer with Intel Atom® x6425E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.553,00 €
DRP-A100-E4-6C-T	DIN-rail computer with Intel Atom® x6425E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.374,00 €
DRP-A100-E4-8L-T	DIN-rail computer with Intel Atom® x6425E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.814,00 €
DRP-A100-E4-T	DIN-rail computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	2.934,00 €
DRP-A100-E4-T-Win10	DIN-rail computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	3.667,00 €

DRP-C100-C1-2L4C-T	DIN-rail computer with Intel® Celeron® 6305E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.537,00 €
DRP-C100-C1-6C-T	DIN-rail computer with Intel® Celeron® 6305E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.407,00 €
DRP-C100-C1-8L-T	DIN-rail computer with Intel® Celeron® 6305E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	3.830,00 €
DRP-C100-C1-T	DIN-rail computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	2.787,00 €
DRP-C100-C1-T-Win10	DIN-rail computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	3.749,00 €
DRP-C100-C5-2L4C-T	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	4.938,00 €
DRP-C100-C5-6C-T	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	4.727,00 €
DRP-C100-C5-8L-T	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	5.069,00 €
DRP-C100-C5-T	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	4.124,00 €
DRP-C100-C5-T-Win10	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	5.167,00 €
DRP-C100-C7-2L4C-T	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	5.688,00 €
DRP-C100-C7-6C-T	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	5.444,00 €
DRP-C100-C7-8L-T	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	5.998,00 €
DRP-C100-C7-T	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	5.020,00 €
DRP-C100-C7-T-Win10	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	6.259,00 €
EDF-G1002-BP	Industrial next-gen LAN firewall with 2 10/100/1000BaseT(X) ports, 1 Ethernet-based management port, Intrusion Prevention System (IPS), Deep Packet Inspection (DPI), Gen3 bypass, centralized management through MXsecurity, -10 to 60°C operating temperature	1.460,00 €
EDF-G1002-BP-CT	Industrial next-gen LAN firewall with 2 10/100/1000BaseT(X) ports, 1 Ethernet-based management port, Intrusion Prevention System (IPS), Deep Packet Inspection (DPI), Gen3 bypass, centralized management through MXsecurity, -10 to 60°C operating temperature, conformal coating	1.816,00 €

EDF-G1002-BP-CT-T	Industrial next-gen LAN firewall with 2 10/100/1000BaseT(X) ports, 1 Ethernet-based management port, Intrusion Prevention System (IPS), Deep Packet Inspection (DPI), Gen3 bypass, centralized management through MXsecurity, -40 to 75°C operating temperature, conformal coating	2.023,00 €
EDF-G1002-BP-T	Industrial next-gen LAN firewall with 2 10/100/1000BaseT(X) ports, 1 Ethernet-based management port, Intrusion Prevention System (IPS), Deep Packet Inspection (DPI), Gen3 bypass, centralized management through MXsecurity, -40 to 75°C operating temperature	1.618,00 €
EDR-8010-2GSFP	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	1.793,00 €
EDR-8010-2GSFP-CT	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -10 to 60°C operating temperature, conformal coating	2.221,00 €
EDR-8010-2GSFP-CT-T	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -40 to 75°C operating temperature, conformal coating	2.419,00 €
EDR-8010-2GSFP-T	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	1.999,00 €
EDR-8010-VPN-2GSFP	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	1.999,00 €
EDR-8010-VPN-2GSFP-CT	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature, conformal coating	2.419,00 €
EDR-8010-VPN-2GSFP-CT-T	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature, conformal coating	2.633,00 €
EDR-8010-VPN-2GSFP-T	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	2.205,00 €
EDR-G9004-VPN-2MGTXSFP	Industrial secure router with 2 Gigabit copper ports with Gen3 Bypass, 2 Gigabit copper/SFP combo ports with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	2.974,00 €
EDR-G9004-VPN-2MGTXSFP-CT	Industrial secure router with 2 Gigabit copper ports with Gen3 Bypass, 2 Gigabit copper/SFP combo ports with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature, conformal coating	3.717,00 €
EDR-G9004-VPN-2MGTXSFP-CT-T	Industrial secure router with 2 Gigabit copper ports with Gen3 Bypass, 2 Gigabit copper/SFP combo ports with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature, conformal coating	3.914,00 €
EDR-G9004-VPN-2MGTXSFP-T	Industrial secure router with 2 Gigabit copper ports with Gen3 Bypass, 2 Gigabit copper/SFP combo ports with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	3.141,00 €
EDR-G9010-VPN-2MGSFP	8 GbE copper + 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	4.242,00 €
EDR-G9010-VPN-2MGSFP-CT	8 GbE copper + 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature, conformal coating	5.158,00 €
EDR-G9010-VPN-2MGSFP-CT-T	8 GbE copper + 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature, conformal coating	5.386,00 €
EDR-G9010-VPN-2MGSFP-HV	8 GbE copper + 2 GbE SFP multiport industrial secure router with Firewall/NAT/VPN, 120/220 VDC/VAC input voltage, -10 to 60°C operating temperature	4.626,00 €

EDR-G9010-VPN-2MGSFP-HV-T	8 GbE copper + 2 GbE SFP multiport industrial secure router with Firewall/NAT/VPN, 120/220 VDC/VAC input voltage, -40 to 75°C operating temperature	4.800,00 €
EDR-G9010-VPN-2MGSFP-T	8 GbE copper + 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	4.645,00 €
EDS-2005-EL	Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	129,00 €
EDS-2005-ELP	Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	111,00 €
EDS-2005-EL-T	Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	195,00 €
EDS-2008-EL	Unmanaged Fast Ethernet switch with 8 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	187,00 €
EDS-2008-EL-M-SC	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connectors, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	298,00 €
EDS-2008-EL-M-SC-T	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connectors, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	371,00 €
EDS-2008-EL-M-ST	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	298,00 €
EDS-2008-EL-M-ST-T	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	371,00 €
EDS-2008-ELP	Unmanaged Fast Ethernet switch with 8 10/100BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	161,00 €
EDS-2008-EL-T	Unmanaged Fast Ethernet switch with 8 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	266,00 €
EDS-2010-ML-2GTXSFP	Unmanaged Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power inputs 12/24/48 VDC, -10 to 60°C operating temperature	679,00 €
EDS-2010-ML-2GTXSFP-T	Unmanaged Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power inputs 12/24/48 VDC, -40 to 75°C operating temperature	802,00 €
EDS-2016-ML	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, dual power inputs 12/24/48 VDC, -10 to 60°C operating temperature	622,00 €
EDS-2016-ML-MM-SC	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, dual power inputs 12/24/48 VDC, -10 to 60°C operating temperature	880,00 €
EDS-2016-ML-MM-SC-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, dual power inputs 12/24/48 VDC, -40 to 75°C operating temperature	981,00 €
EDS-2016-ML-MM-ST	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, dual power inputs 12/24/48 VDC, -10 to 60°C operating temperature	880,00 €
EDS-2016-ML-MM-ST-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, dual power inputs 12/24/48 VDC, -40 to 75°C operating temperature	981,00 €
EDS-2016-ML-SS-SC	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, dual power inputs 12/24/48 VDC, -10 to 60°C operating temperature	1.271,00 €
EDS-2016-ML-SS-SC-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, dual power inputs 12/24/48 VDC, -40 to 75°C operating temperature	1.382,00 €

EDS-2016-ML-T	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, dual power inputs 12/24/48 VDC, -40 to 75°C operating temperature	737,00 €
EDS-2018-ML-2GTXSFP	Unmanaged Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power inputs 12/24/48 VDC, -10 to 60°C operating temperature	1.035,00 €
EDS-2018-ML-2GTXSFP-T	Unmanaged Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power inputs 12/24/48 VDC, -40 to 75°C operating temperature	1.147,00 €
EDS-205	Entry-level unmanaged Ethernet switch with 5 10/100BaseT(X) ports, plastic housing, -10 to 60°C operating temperature	141,00 €
EDS-205A	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, -10 to 60°C operating temperature	166,00 €
EDS-205A-M-SC	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -10 to 60°C operating temperature	345,00 €
EDS-205A-M-SC-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -40 to 75°C operating temperature	473,00 €
EDS-205A-M-ST	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -10 to 60°C operating temperature	345,00 €
EDS-205A-M-ST-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -40 to 75°C operating temperature	473,00 €
EDS-205A-S-SC	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -10 to 60°C operating temperature	573,00 €
EDS-205A-S-SC-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -40 to 75°C operating temperature	702,00 €
EDS-205A-T	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, -40 to 75°C operating temperature	316,00 €
EDS-208	Entry-level unmanaged Ethernet switch with 8 10/100BaseT(X) ports, plastic housing, -10 to 60°C operating temperature	206,00 €
EDS-208A	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, -10 to 60°C operating temperature	242,00 €
EDS-208A-MM-SC	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -10 to 60°C operating temperature	575,00 €
EDS-208A-MM-SC-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	662,00 €
EDS-208A-MM-ST	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -10 to 60°C operating temperature	575,00 €
EDS-208A-MM-ST-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	662,00 €
EDS-208A-M-SC	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -10 to 60°C operating temperature	426,00 €
EDS-208A-M-SC-T	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -40 to 75°C operating temperature	519,00 €
EDS-208A-M-ST	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -10 to 60°C operating temperature	426,00 €
EDS-208A-M-ST-T	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -40 to 75°C operating temperature	519,00 €
EDS-208A-S-SC	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -10 to 60°C operating temperature	654,00 €
EDS-208A-S-SC-T	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -40 to 75°C operating temperature	782,00 €
EDS-208A-SS-SC	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -10 to 60°C operating temperature	927,00 €
EDS-208A-SS-SC-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	1.062,00 €
EDS-208A-T	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, -40 to 75°C operating temperature	400,00 €

EDS-208-M-SC	Entry-level unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, plastic housing, -10 to 60°C operating temperature	358,00 €
EDS-208-M-ST	Entry-level unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, plastic housing, -10 to 60°C operating temperature	358,00 €
EDS-305	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, relay output warning, 0 to 60°C operating temperature	292,00 €
EDS-305-M-SC	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	448,00 €
EDS-305-M-SC-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	555,00 €
EDS-305-M-ST	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, 0 to 60°C operating temperature	448,00 €
EDS-305-M-ST-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, -40 to 75°C operating temperature	555,00 €
EDS-305-S-SC	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	653,00 €
EDS-305-S-SC-80	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector for 80 km transmission, relay output warning, 0 to 60°C operating temperature	1.843,00 €
EDS-305-S-SC-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	722,00 €
EDS-305-T	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, relay output warning, -40 to 75°C operating temperature	361,00 €
EDS-308	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, relay output warning, 0 to 60°C operating temperature	367,00 €
EDS-308-MM-SC	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, 0 to 60°C operating temperature	645,00 €
EDS-308-MM-SC-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	722,00 €
EDS-308-MM-ST	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, relay output warning, 0 to 60°C operating temperature	645,00 €
EDS-308-MM-ST-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connector, -40 to 75°C operating temperature	722,00 €
EDS-308-M-SC	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	531,00 €
EDS-308-M-SC-T	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	581,00 €
EDS-308-S-SC	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	657,00 €
EDS-308-S-SC-80	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector for 80 km transmission, relay output warning, 0 to 60°C operating temperature	1.618,00 €

EDS-308-S-SC-T	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	767,00 €
EDS-308-SS-SC	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, 0 to 60°C operating temperature	915,00 €
EDS-308-SS-SC-80	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, relay output warning, 0 to 60°C operating temperature	2.765,00 €
EDS-308-SS-SC-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	1.035,00 €
EDS-308-T	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, relay output warning, -40 to 75°C operating temperature	429,00 €
EDS-309-3M-SC	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, relay output warning, 0 to 60°C operating temperature	879,00 €
EDS-309-3M-SC-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	967,00 €
EDS-309-3M-ST	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, relay output warning, 0 to 60°C operating temperature	879,00 €
EDS-309-3M-ST-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, relay output warning, -40 to 75°C operating temperature	967,00 €
EDS-316	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, relay output warning, -10 to 60°C operating temperature	775,00 €
EDS-316-MM-SC	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, -10 to 60°C operating temperature	1.111,00 €
EDS-316-MM-SC-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	1.240,00 €
EDS-316-MM-ST	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, relay output warning, -10 to 60°C operating temperature	1.111,00 €
EDS-316-MM-ST-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, relay output warning, -40 to 75°C operating temperature	1.240,00 €
EDS-316-M-SC	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -10 to 60°C operating temperature	989,00 €
EDS-316-M-SC-T	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	1.127,00 €
EDS-316-MS-SC	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, 1 100BaseFX single-mode port with SC connector, relay output warning, -10 to 60°C operating temperature	1.357,00 €
EDS-316-M-ST	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, -10 to 60°C operating temperature	989,00 €
EDS-316-M-ST-T	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, -40 to 75°C operating temperature	1.127,00 €

EDS-316-S-SC	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -10 to 60°C operating temperature	1.169,00 €
EDS-316-S-SC-T	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	1.273,00 €
EDS-316-SS-SC	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, -10 to 60°C operating temperature	1.618,00 €
EDS-316-SS-SC-80	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, relay output warning, -10 to 60°C operating temperature	3.709,00 €
EDS-316-SS-SC-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	1.726,00 €
EDS-316-T	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, relay output warning, -40 to 75°C operating temperature	910,00 €
EDS-4008-2GT-2GS-HV	Managed Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, single power supply, 110/220 VAC/VDC, -10 to 60°C operating temperature	1.867,00 €
EDS-4008-2GT-2GS-HV-T	Managed Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	2.086,00 €
EDS-4008-2GT-2GS-LV	Managed Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -10 to 60°C operating temperature	1.692,00 €
EDS-4008-2GT-2GS-LV-T	Managed Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -40 to 75°C operating temperature	1.909,00 €
EDS-4008-2MSC-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	2.152,00 €
EDS-4008-2MSC-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	2.351,00 €
EDS-4008-2MSC-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	1.991,00 €
EDS-4008-2MSC-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	2.191,00 €
EDS-4008-2MST-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	2.152,00 €
EDS-4008-2MST-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	2.351,00 €
EDS-4008-2MST-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	1.991,00 €
EDS-4008-2MST-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	2.191,00 €
EDS-4008-2SSC-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	2.508,00 €

EDS-4008-2SSC-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	2.700,00 €
EDS-4008-2SSC-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	2.351,00 €
EDS-4008-2SSC-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	2.542,00 €
EDS-4008-4P-2GT-2GS-LVA	Managed Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, 48 VDC for PoE, -10 to 60°C operating temperature	2.200,00 €
EDS-4008-4P-2GT-2GS-LVA-T	Managed Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, 48 VDC for PoE, -40 to 75°C operating temperature	2.408,00 €
EDS-4008-4P-2GT-2GS-LVB	Managed Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -10 to 60°C operating temperature	2.391,00 €
EDS-4008-4P-2GT-2GS-LVB-T	Managed Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -40 to 75°C operating temperature	2.600,00 €
EDS-4008-HV	Managed Ethernet switch with 8 10/100BaseT(X) ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	1.644,00 €
EDS-4008-HV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	1.834,00 €
EDS-4008-LV	Managed Ethernet switch with 8 10/100BaseT(X) ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	1.483,00 €
EDS-4008-LV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	1.677,00 €
EDS-4009-3MSC-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	2.594,00 €
EDS-4009-3MSC-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	2.794,00 €
EDS-4009-3MSC-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	2.433,00 €
EDS-4009-3MSC-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	2.627,00 €
EDS-4009-3MST-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	2.594,00 €
EDS-4009-3MST-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	2.794,00 €
EDS-4009-3MST-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	2.433,00 €
EDS-4009-3MST-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	2.627,00 €
EDS-4009-3SSC-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	3.125,00 €

EDS-4009-3SSC-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	3.316,00 €
EDS-4009-3SSC-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	2.966,00 €
EDS-4009-3SSC-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	3.159,00 €
EDS-4012-4GC-HV	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply, 110/220 VAC/VDC, -10 to 60°C operating temperature	2.225,00 €
EDS-4012-4GC-HV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply, 110/220 VAC/VDC, -40 to 75°C operating temperature	2.417,00 €
EDS-4012-4GC-LV	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -10 to 60°C operating temperature	2.067,00 €
EDS-4012-4GC-LV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -40 to 75°C operating temperature	2.258,00 €
EDS-4012-4GS-HV	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, single power supply, 110/220 VAC/VDC, -10 to 60°C operating temperature	2.067,00 €
EDS-4012-4GS-HV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, single power supply, 110/220 VAC/VDC, -40 to 75°C operating temperature	2.258,00 €
EDS-4012-4GS-LV	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -10 to 60°C operating temperature	1.909,00 €
EDS-4012-4GS-LV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -40 to 75°C operating temperature	2.100,00 €
EDS-4012-8P-4GS-LVA	Managed Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, 48 VDC for PoE, -10 to 60°C operating temperature	2.742,00 €
EDS-4012-8P-4GS-LVA-T	Managed Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, 48 VDC for PoE, -40 to 75°C operating temperature	2.933,00 €
EDS-4012-8P-4GS-LVB	Managed Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -10 to 60°C operating temperature	2.917,00 €
EDS-4012-8P-4GS-LVB-T	Managed Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -40 to 75°C operating temperature	3.108,00 €
EDS-4014-4GS-2QGS-HV	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, single power supply, 110/220 VAC/VDC, -10 to 60°C operating temperature	2.594,00 €
EDS-4014-4GS-2QGS-HV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, single power supply, 110/220 VAC/VDC, -40 to 75°C operating temperature	2.794,00 €
EDS-4014-4GS-2QGS-LV	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, dual power supply, 12/24/48 VDC, -10 to 60°C operating temperature	2.433,00 €
EDS-4014-4GS-2QGS-LV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, dual power supply, 12/24/48 VDC, -40 to 75°C operating temperature	2.627,00 €
EDS-405A	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, -10°C to 60°C operating temperature	514,00 €

EDS-405A-EIP	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, EtherNet/IP enabled, 0 to 60°C operating temperature	514,00 €
EDS-405A-EIP-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, EtherNet/IP enabled, -40 to 75°C operating temperature	646,00 €
EDS-405A-MM-SC	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	923,00 €
EDS-405A-MM-SC-T	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	1.084,00 €
EDS-405A-MM-ST	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	923,00 €
EDS-405A-MM-ST-T	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	1.084,00 €
EDS-405A-PN	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, PROFINET enabled, 0 to 60°C operating temperature	514,00 €
EDS-405A-PN-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, PROFINET enabled, -40 to 75°C operating temperature	646,00 €
EDS-405A-PTP	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, hardware-based IEEE 1588 PTPv2 protocol support, -10°C to 60°C operating temperature	1.454,00 €
EDS-405A-PTP-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, hardware-based IEEE 1588 PTPv2 protocol support, -40°C to 75°C operating temperature	1.622,00 €
EDS-405A-SS-SC	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	1.252,00 €
EDS-405A-SS-SC-T	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	1.386,00 €
EDS-405A-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, -40 to 75°C operating temperature	646,00 €
EDS-408A	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, -10°C to 60°C operating temperature	814,00 €
EDS-408A-1M2S-SC	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 1 100BaseFX multi-mode port, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	1.877,00 €
EDS-408A-1M2S-SC-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 1 100BaseFX multi-mode port, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	2.009,00 €
EDS-408A-2M1S-SC	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports, 1 100BaseFX single-mode port with SC connectors, 0 to 60°C operating temperature	1.708,00 €
EDS-408A-2M1S-SC-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports, 1 100BaseFX single-mode port with SC connectors, -40 to 75°C operating temperature	1.860,00 €
EDS-408A-3M-SC	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	1.556,00 €
EDS-408A-3M-SC-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	1.690,00 €
EDS-408A-3M-ST	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	1.556,00 €
EDS-408A-3M-ST-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	1.690,00 €
EDS-408A-3S-SC	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	2.029,00 €
EDS-408A-3S-SC-48	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, $\pm 24/\pm 48$ VDC input voltage, 0 to 60°C operating temperature	2.384,00 €

EDS-408A-3S-SC-48-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, $\pm 24/\pm 48$ VDC input voltage, -40 to 75°C operating temperature	2.546,00 €
EDS-408A-3S-SC-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	2.162,00 €
EDS-408A-EIP	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, EtherNet/IP enabled, 0 to 60°C operating temperature	814,00 €
EDS-408A-EIP-T	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, EtherNet/IP enabled, -40 to 75°C operating temperature	1.117,00 €
EDS-408A-MM-SC	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	1.184,00 €
EDS-408A-MM-SC-T	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	1.486,00 €
EDS-408A-MM-ST	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	1.184,00 €
EDS-408A-MM-ST-T	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	1.486,00 €
EDS-408A-PN	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, PROFINET enabled, 0 to 60°C operating temperature	814,00 €
EDS-408A-PN-T	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, PROFINET enabled, -40 to 75°C operating temperature	1.117,00 €
EDS-408A-SS-SC	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	1.670,00 €
EDS-408A-SS-SC-T	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	1.808,00 €
EDS-408A-T	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, -40 to 75°C operating temperature	1.117,00 €
EDS-505A	Managed Ethernet switch with 5 10/100BaseT(X) ports, 0 to 60°C operating temperature	930,00 €
EDS-505A-MM-SC	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	1.692,00 €
EDS-505A-MM-SC-T	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	1.923,00 €
EDS-505A-MM-ST	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	1.692,00 €
EDS-505A-MM-ST-T	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	1.923,00 €
EDS-505A-SS-SC	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	2.096,00 €
EDS-505A-SS-SC-T	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	2.297,00 €
EDS-505A-T	Managed Ethernet switch with 5 10/100BaseT(X) ports, -40 to 75°C operating temperature	1.283,00 €
EDS-508A	Managed Ethernet switch with 8 10/100BaseT(X) ports, 0 to 60°C operating temperature	1.283,00 €
EDS-508A-MM-SC	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	1.944,00 €
EDS-508A-MM-SC-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	2.112,00 €
EDS-508A-MM-ST	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	1.944,00 €
EDS-508A-MM-ST-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	2.112,00 €
EDS-508A-SS-SC	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	2.432,00 €

EDS-508A-SS-SC-80	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, 0 to 60°C operating temperature	5.601,00 €
EDS-508A-SS-SC-80-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, -40 to 75°C operating temperature	5.771,00 €
EDS-508A-SS-SC-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	2.598,00 €
EDS-508A-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, -40 to 75°C operating temperature	1.454,00 €
EDS-510A-1GT2SFP	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 1 10/100/1000BaseT(X) port, 2 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	2.196,00 €
EDS-510A-1GT2SFP-T	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 1 10/100/1000BaseT(X) port, 2 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	2.384,00 €
EDS-510A-3GT	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) ports, 0 to 60°C operating temperature	2.196,00 €
EDS-510A-3GT-T	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) ports, -40 to 75°C operating temperature	2.384,00 €
EDS-510A-3SFP	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	2.196,00 €
EDS-510A-3SFP-T	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	2.384,00 €
EDS-510E-3GTXSFP	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -10 to 60°C operating temperature	1.605,00 €
EDS-510E-3GTXSFP-T	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -40 to 75°C operating temperature	1.738,00 €
EDS-516A	Managed Ethernet switch with 16 10/100BaseT(X) ports, 0 to 60°C operating temperature	2.009,00 €
EDS-516A-MM-SC	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	2.532,00 €
EDS-516A-MM-SC-T	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	2.685,00 €
EDS-516A-MM-ST	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	2.532,00 €
EDS-516A-MM-ST-T	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	2.685,00 €
EDS-516A-T	Managed Ethernet switch with 16 10/100BaseT(X) ports, -40 to 75°C operating temperature	2.164,00 €
EDS-518A	Managed Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	2.886,00 €
EDS-518A-MM-SC	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	3.476,00 €
EDS-518A-MM-SC-T	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	3.680,00 €

EDS-518A-MM-ST	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	3.476,00 €
EDS-518A-MM-ST-T	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	3.680,00 €
EDS-518A-SS-SC	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	3.913,00 €
EDS-518A-SS-SC-80	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	7.201,00 €
EDS-518A-SS-SC-T	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	4.134,00 €
EDS-518A-T	Managed Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	3.092,00 €
EDS-518E-4GTXSFP	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -10 to 60°C operating temperature	2.262,00 €
EDS-518E-4GTXSFP-T	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -40 to 75°C operating temperature	2.432,00 €
EDS-518E-MM-SC-4GTXSFP	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX (multi-mode, SC Connector), -10 to 60°C operating temperature	2.739,00 €
EDS-518E-MM-SC-4GTXSFP-T	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX multi-mode ports with SC connector, -40 to 75°C operating temperature	2.899,00 €
EDS-518E-MM-ST-4GTXSFP	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX multi-mode ports with ST connectors, -10 to 60°C operating temperature	2.739,00 €
EDS-518E-MM-ST-4GTXSFP-T	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	2.899,00 €
EDS-518E-SS-SC-4GTXSFP	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX single-mode ports with SC connector, -10 to 60°C operating temperature	3.092,00 €
EDS-518E-SS-SC-4GTXSFP-T	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX single-mode ports with SC connector, -40 to 75°C operating temperature	3.238,00 €
EDS-528E-4GTXSFP-HV	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 110/220 VAC/VDC power input, -10 to 60°C operating temperature	3.326,00 €
EDS-528E-4GTXSFP-HV-T	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 110/220 VAC/VDC power input, -40 to 75°C operating temperature	3.476,00 €
EDS-528E-4GTXSFP-LV	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48/-48 VDC power inputs, -10 to 60°C operating temperature	3.326,00 €

EDS-528E-4GTXSFP-LV-T	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48/-48 VDC power inputs, -40 to 75°C operating temperature	3.476,00 €
EDS-608	Compact managed Ethernet switch system with 2 slots for 4-port Fast Ethernet interface modules, for a total of up to 8 ports, 0 to 60°C operating temperature	1.858,00 €
EDS-608-T	Compact managed Ethernet switch system with 2 slots for 4-port Fast Ethernet interface modules, for a total of up to 8 ports, -40 to 75°C operating temperature	2.129,00 €
EDS-611	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 slots for 4-port fast Ethernet interface modules, for a total of up to 11 ports, 0 to 60°C operating temperature	2.904,00 €
EDS-611-T	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 slots for 4-port fast Ethernet interface modules, for a total of up to 11 ports, -40 to 75°C operating temperature	3.190,00 €
EDS-616	Compact managed Ethernet switch system with 4 slots for 4-port fast Ethernet interface modules, for a total of up to 16 ports, 0 to 60°C operating temperature	3.106,00 €
EDS-616-T	Compact managed Ethernet switch system with 4 slots for 4-port fast Ethernet interface modules, for a total of up to 16 ports, -40 to 75°C operating temperature	3.395,00 €
EDS-619	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 slots for 4-port Fast Ethernet interface modules, for a total of up to 19 ports, 0 to 60°C operating temperature	4.050,00 €
EDS-619-T	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 slots for 4-port Fast Ethernet interface modules, for a total of up to 19 ports, -40 to 75°C operating temperature	4.339,00 €
EDS-G2005-EL	Unmanaged full Gigabit Ethernet switch with 5 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	257,00 €
EDS-G2005-ELP	Unmanaged full Gigabit Ethernet switch with 5 10/100/1000 BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	228,00 €
EDS-G2005-EL-T	Unmanaged full Gigabit Ethernet switch with 5 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	320,00 €
EDS-G2008-EL	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	355,00 €
EDS-G2008-ELP	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000 BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	292,00 €
EDS-G2008-EL-T	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	419,00 €
EDS-G205-1GTXSFP	Unmanaged full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 1 combo 10/100/1000BaseT(X) or 100/1000BaseSFP port, -10 to 60°C operating temperature	332,00 €
EDS-G205-1GTXSFP-T	Unmanaged full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 1 combo 10/100/1000BaseT(X) or 100/1000BaseSFP port, -40 to 75°C operating temperature	442,00 €
EDS-G205A-4PoE	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseT port, 0 to 60°C operating temperature	887,00 €
EDS-G205A-4PoE-1GSFP	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseX (SFP slot) port, 0 to 60°C operating temperature	947,00 €
EDS-G205A-4PoE-1GSFP-T	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseX (SFP slot) port, -40 to 75°C operating temperature	1.042,00 €
EDS-G205A-4PoE-T	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseT port, -40 to 75°C operating temperature	980,00 €
EDS-G308	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 0 to 60°C operating temperature	486,00 €
EDS-G308-2SFP	Unmanaged full Gigabit Ethernet switch with 6 10/100/1000BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, 0 to 60°C operating temperature	600,00 €

EDS-G308-2SFP-T	Unmanaged full Gigabit Ethernet switch with 6 10/100/1000BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, -40 to 75°C operating temperature	702,00 €
EDS-G308-T	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, -40 to 75°C operating temperature	590,00 €
EDS-G4008-HV	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, single power supply, 110/220 VAC/VDC, -10 to 60°C operating temperature	2.491,00 €
EDS-G4008-HV-T	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, single power supply, 110/220 VAC/VDC, -40 to 75°C operating temperature	2.684,00 €
EDS-G4008-LV	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, dual power supply, 12/24/48 VDC, -10 to 60°C operating temperature	2.333,00 €
EDS-G4008-LV-T	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, dual power supply, 12/24/48 VDC, -40 to 75°C operating temperature	2.527,00 €
EDS-G4012-4GC-HV	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply, 110/220 VAC/VDC, -10 to 60°C operating temperature	3.075,00 €
EDS-G4012-4GC-HV-T	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply, 110/220 VAC/VDC, -40 to 75°C operating temperature	3.266,00 €
EDS-G4012-4GC-LV	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -10 to 60°C operating temperature	2.908,00 €
EDS-G4012-4GC-LV-T	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply, 12/24/48 VDC, -40 to 75°C operating temperature	3.108,00 €
EDS-G4012-8P-4QGS-LVA	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply, 12/24/48 VDC, 48 VDC for PoE, -10 to 60°C operating temperature	3.967,00 €
EDS-G4012-8P-4QGS-LVA-T	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply, 12/24/48 VDC, 48 VDC for PoE, -40 to 75°C operating temperature	4.166,00 €
EDS-G4012-8P-4QGS-LVB	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply, 12/24/48 VDC, -10 to 60°C operating temperature	4.149,00 €
EDS-G4012-8P-4QGS-LVB-T	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply, 12/24/48 VDC, -40 to 75°C operating temperature	4.342,00 €
EDS-G4014-6QGS-HV	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, single power supply, 110/220 VAC/VDC, -10 to 60°C operating temperature	4.075,00 €
EDS-G4014-6QGS-HV-T	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, single power supply, 110/220 VAC/VDC, -40 to 75°C operating temperature	4.266,00 €
EDS-G4014-6QGS-LV	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, dual power supply, 12/24/48 VDC, -10 to 60°C operating temperature	3.916,00 €
EDS-G4014-6QGS-LV-T	Managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, dual power supply, 12/24/48 VDC, -40 to 75°C operating temperature	4.116,00 €
EDS-G508E	8-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	1.996,00 €
EDS-G508E-T	8-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, -40 to 75°C operating temperature	2.196,00 €
EDS-G509	Industrial full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 5 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 0 to 60°C operating temperature	2.217,00 €
EDS-G509-T	Industrial full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 5 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, -40 to 75°C operating temperature	2.417,00 €

EDS-G512E-4GSFP	12-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -10 to 60°C operating temperature	2.061,00 €
EDS-G512E-4GSFP-T	12-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -40 to 75°C operating temperature	2.248,00 €
EDS-G512E-8PoE-4GSFP	12-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) PoE/PoE+ ports, 4 100/1000BaseSFP slots, -10 to 60°C operating temperature	3.005,00 €
EDS-G512E-8PoE-4GSFP-T	12-port full Gigabit managed Ethernet switch, 8 10/100/1000BaseT(X) PoE/PoE+ ports with 4 100/1000BaseSFP slots, -40 to 75°C operating temperature	3.258,00 €
EDS-G516E-4GSFP	16-port full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -10 to 60°C operating temperature	2.956,00 €
EDS-G516E-4GSFP-T	16-port full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -40 to 75°C operating temperature	3.160,00 €
EDS-P206A-4PoE	Unmanaged Ethernet switch with 2 10/100BaseT(X) ports, 4 PoE ports, -10 to 60°C operating temperature	547,00 €
EDS-P206A-4PoE-MM-SC	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with SC connectors, -10 to 60°C operating temperature	800,00 €
EDS-P206A-4PoE-MM-SC-T	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	907,00 €
EDS-P206A-4PoE-MM-ST	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with ST connectorss, -10 to 60°C operating temperature	800,00 €
EDS-P206A-4PoE-MM-ST-T	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with ST connectorss, -40 to 75°C operating temperature	907,00 €
EDS-P206A-4PoE-M-SC	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, and 1 100BaseFX multi-mode port with SC connector, -10 to 60°C operating temperature	663,00 €
EDS-P206A-4PoE-M-SC-T	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX multi-mode port with SC connector, -40 to 75°C operating temperature	767,00 €
EDS-P206A-4PoE-M-ST	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX multi-mode port with ST connectors, -10 to 60°C operating temperature	663,00 €
EDS-P206A-4PoE-M-ST-T	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX multi-mode port with ST connectors, -40 to 75°C operating temperature	767,00 €
EDS-P206A-4PoE-S-SC	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX single-mode port with SC connector, -10 to 60°C operating temperature	915,00 €
EDS-P206A-4PoE-S-SC-T	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX single-mode port with SC connector, -40 to 75°C operating temperature	1.003,00 €
EDS-P206A-4PoE-SS-SC	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, and 2 100BaseFX single-mode ports with SC connector, -10 to 60°C operating temperature	1.144,00 €
EDS-P206A-4PoE-SS-SC-T	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX single-mode ports with SC connector, -40 to 75°C operating temperature	1.271,00 €
EDS-P206A-4PoE-T	Unmanaged Ethernet switch with 2 10/100BaseT(X) ports, 4 PoE ports, -40 to 75°C operating temperature	644,00 €
EDS-P506E-4PoE-2GTXSFP	Managed Ethernet switch with 4 PoE+/60W 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	1.876,00 €
EDS-P506E-4PoE-2GTXSFP-T	Managed Ethernet switch with 4 PoE+/60W 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	2.062,00 €
EDS-P510A-8PoE-2GTXSFP	Managed Gigabit Ethernet switch with 8 PoE/PoE+ 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, 0 to 60°C operating temperature	2.397,00 €

EDS-P510A-8PoE-2GTXSFP-T	Managed Gigabit Ethernet switch with 8 PoE/PoE+ 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, -40 to 75°C operating temperature	2.652,00 €
EJS-04	Compact industrial EtherCAT junction with 4 100BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	297,00 €
EJS-04-T	Compact industrial EtherCAT junction with 4 100BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	407,00 €
EJS-08	Compact industrial EtherCAT junction with 8 100BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	476,00 €
EJS-08-T	Compact industrial EtherCAT junction with 8 100BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	656,00 €
EOM-104	Embedded managed Ethernet switch module with 4 10/100BaseT(X) ports, -40 to 75°C operating temperature	371,00 €
EOM-104 20PCS	Embedded managed Ethernet switch module with 4 10/100BaseT(X) ports, 20 pcs, -40 to 75°C operating temperature	7.331,00 €
EOM-104 Evaluation Kit	Evaluation kit with an EOM-104 switch module and evaluation board with 4 10/100BaseT(X) ports for testing and application development	492,00 €
EOM-104-FO	Embedded managed Ethernet switch module with 2 10/100BaseT(X) and 2 100BaseFX ports, -40 to 75°C operating temperature	430,00 €
EOM-104-FO 20PCS	Embedded managed Ethernet switch module with 2 10/100BaseT(X) and 2 100BaseFX ports, -40 to 75°C operating temperature, 20 pcs package	8.553,00 €
EOM-104-FO Evaluation Kit	Evaluation kit with an EOM-104-FO switch module and evaluation board with 2 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connector for testing and application development	979,00 €
EXPC-F2120W-TL1-AC	12.1-inch flat-panel fanless industrial computer with Intel® Celeron® 6305E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	8.027,00 €
EXPC-F2120W-TL1-DC	12.1-inch flat-panel fanless industrial computer with Intel® Celeron® 6305E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	8.027,00 €
EXPC-F2120W-TL3-AC	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	8.599,00 €
EXPC-F2120W-TL3-DC	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	8.599,00 €
EXPC-F2120W-TL7-AC	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	10.028,00 €
EXPC-F2120W-TL7-DC	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	10.028,00 €
EXPC-F2150W-TL3-AC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	9.456,00 €
EXPC-F2150W-TL3-DC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	9.313,00 €

EXPC-F2150W-TL5-AC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i5-1145G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	10.171,00 €
EXPC-F2150W-TL5-DC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i5-1145G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	10.028,00 €
EXPC-F2150W-TL7-AC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	10.885,00 €
EXPC-F2150W-TL7-DC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	10.885,00 €
GPS Antenna Package	External antenna with TNC to SMA (female) adapter and a 50-cm cable, SMA antenna (26 dBi, 1572 MHz, L1 band), GPS extension cable	135,00 €
HDR-60-24	60 W/2.5 A DIN-rail 24 VDC power supply, universal 85 to 264 VAC or 120 to 370 VDC input voltage, -30 to 70°C operating temperature	93,00 €
HS-M.2 2280-RKP-C220	M.2 2280 heatsink for the RKP-C220 Series	33,00 €
ICF-1150I-M-SC	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, 0 to 60°C operating temperature	537,00 €
ICF-1150I-M-SC-IEEX	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, IECEEx, 0 to 60°C operating temperature	621,00 €
ICF-1150I-M-SC-T	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, -40 to 85°C operating temperature	703,00 €
ICF-1150I-M-SC-T-IEEX	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, IECEEx, -40 to 85°C operating temperature	807,00 €
ICF-1150I-M-ST	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, 0 to 60°C operating temperature	537,00 €
ICF-1150I-M-ST-IEEX	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, IECEEx, 0 to 60°C operating temperature	621,00 €
ICF-1150I-M-ST-T	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, -40 to 85°C operating temperature	703,00 €
ICF-1150I-M-ST-T-IEEX	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, IECEEx, -40 to 85°C operating temperature	807,00 €
ICF-1150I-S-SC	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, 0 to 60°C operating temperature	953,00 €
ICF-1150I-S-SC-IEEX	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, IECEEx, 0 to 60°C operating temperature	1.093,00 €
ICF-1150I-S-SC-T	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, -40 to 85°C operating temperature	1.224,00 €
ICF-1150I-S-SC-T-IEEX	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, IECEEx, -40 to 85°C operating temperature	1.399,00 €
ICF-1150I-S-ST	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, 0 to 60°C operating temperature	953,00 €
ICF-1150I-S-ST-IEEX	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, IECEEx, 0 to 60°C operating temperature	1.093,00 €
ICF-1150I-S-ST-T	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, -40 to 85°C operating temperature	1.224,00 €
ICF-1150I-S-ST-T-IEEX	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, IECEEx, -40 to 85°C operating temperature	1.399,00 €
ICF-1150-M-SC	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 0 to 60°C operating temperature	416,00 €

ICF-1150-M-SC- IEX	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, IECEx, 0 to 60°C operating temperature	478,00 €
ICF-1150-M-SC-T	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, -40 to 85°C operating temperature	537,00 €
ICF-1150-M-SC-T- IEX	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, IECEx, -40 to 85°C operating temperature	621,00 €
ICF-1150-M-ST	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 0 to 60°C operating temperature	416,00 €
ICF-1150-M-ST- IEX	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, IECEx, 0 to 60°C operating temperature	478,00 €
ICF-1150-M-ST-T	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, -40 to 85°C operating temperature	537,00 €
ICF-1150-M-ST-T- IEX	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, IECEx, -40 to 85°C operating temperature	621,00 €
ICF-1150-S-SC	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 0 to 60°C operating temperature	725,00 €
ICF-1150-S-SC-IEX	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, IECEx, 0 to 60°C operating temperature	836,00 €
ICF-1150-S-SC-T	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, -40 to 85°C operating temperature	953,00 €
ICF-1150-S-SC-T- IEX	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, IECEx, -40 to 85°C operating temperature	1.093,00 €
ICF-1150-S-ST	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 0 to 60°C operating temperature	725,00 €
ICF-1150-S-ST-IEX	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, IECEx, 0 to 60°C operating temperature	836,00 €
ICF-1150-S-ST-T	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, -40 to 85°C operating temperature	953,00 €
ICF-1150-S-ST-T- IEX	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, IECEx, -40 to 85°C operating temperature	1.093,00 €
ICF-1170I-M-ST	CANbus to fiber converter, multi-mode, ST connector, 0 to 60°C operating temperature	537,00 €
ICF-1170I-M-ST-T	CANbus to fiber converter, multi-mode, ST connector, -40 to 85°C operating temperature	621,00 €
ICF-1171I-M-ST	Industrial CAN-to-fiber converter for distance extension, ST multi-mode	576,00 €
ICF-1171I-M-ST-T	Industrial CAN-to-fiber converter for distance extension, ST multi-mode, -40 to 75°C	659,00 €
ICF-1171I-S-ST	Industrial CAN-to-fiber converter for distance extension, ST single-mode	747,00 €
ICF-1171I-S-ST-T	Industrial CAN-to-fiber converter for distance extension, ST single-mode, -40 to 75°C	858,00 €
ICF-1180I-M-ST	PROFIBUS to fiber converter, multi-mode, ST connector, 0 to 60°C operating temperature	751,00 €
ICF-1180I-M-ST-T	PROFIBUS to fiber converter, multi-mode, ST connector, -40 to 75°C operating temperature	862,00 €
ICF-1180I-S-ST	PROFIBUS to fiber converter, single-mode, ST connector, 0 to 60°C operating temperature	1.305,00 €
ICF-1180I-S-ST-T	PROFIBUS to fiber converter, single-mode, ST connector, -40 to 75°C operating temperature	1.418,00 €
ICF-1280I-M-ST	PROFIBUS to fiber converter, multi-mode, 2 ST connectors, 0 to 60°C operating temperature	1.159,00 €
ICF-1280I-M-ST-T	PROFIBUS to fiber converter, multi-mode, 2 ST connectors, -40 to 75°C operating temperature	1.321,00 €
ICF-1280I-S-ST	PROFIBUS to fiber converter, single-mode, 2 ST connectors, 0 to 60°C operating temperature	1.996,00 €
ICF-1280I-S-ST-T	PROFIBUS to fiber converter, single-mode, 2 ST connectors, -40 to 75°C operating temperature	2.155,00 €

ICS-G7526A-20GSFP-2XG-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	15.526,00 €
ICS-G7526A-2XG-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	15.526,00 €
ICS-G7526A-8GSFP-2XG-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	15.526,00 €
ICS-G7528A-20GSFP-4XG-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	19.390,00 €
ICS-G7528A-4XG-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	19.390,00 €
ICS-G7528A-8GSFP-4XG-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	19.390,00 €
ICS-G7748A-HV-HV	Full Gigabit modular managed Ethernet switch system with 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G ports, -10 to 60°C operating temperature	17.069,00 €
ICS-G7750A-2XG-HV-HV	Full Gigabit modular managed Ethernet switch system with 2 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 2 10GbE ports, -10 to 60°C operating temperature	22.764,00 €
ICS-G7752A-4XG-HV-HV	Full Gigabit modular managed Ethernet switch system with 4 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 4 10GbE ports, -10 to 60°C operating temperature	28.462,00 €
ICS-G7826A-20GSFP-2XG-HV-HV-T	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	16.855,00 €
ICS-G7826A-2XG-HV-HV-T	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	16.855,00 €
ICS-G7826A-8GSFP-2XG-HV-HV-T	Layer 3 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	16.855,00 €
ICS-G7828A-20GSFP-4XG-HV-HV-T	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	20.757,00 €
ICS-G7828A-4XG-HV-HV-T	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	20.757,00 €
ICS-G7828A-8GSFP-4XG-HV-HV-T	Layer 3 Full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	20.757,00 €
ICS-G7848A-HV-HV	Layer 3 full Gigabit modular managed Ethernet switch system with 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G ports, 0 to 60°C operating temperature	19.017,00 €

ICS-G7850A-2XG-HV-HV	Layer 3 full Gigabit modular managed Ethernet switch system with 2 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 2 10GbE ports, 0 to 60°C operating temperature	24.713,00 €
ICS-G7852A-4XG-HV-HV	Layer 3 full Gigabit modular managed Ethernet switch system with 4 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 4 10GbE ports, 0 to 60°C operating temperature	30.411,00 €
IKS-6726A-2GTXSFP-24-24-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (24 VDC), -40 to 75°C operating temperature	2.875,00 €
IKS-6726A-2GTXSFP-24-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (24 VDC), -40 to 75°C operating temperature	2.414,00 €
IKS-6726A-2GTXSFP-48-48-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (48 VDC), -40 to 75°C operating temperature	2.875,00 €
IKS-6726A-2GTXSFP-48-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (48 VDC), -40 to 75°C operating temperature	2.414,00 €
IKS-6726A-2GTXSFP-HV-HV-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	2.294,00 €
IKS-6726A-2GTXSFP-HV-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, and 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (85 to 264 VAC), -40 to 75°C operating temperature	1.858,00 €
IKS-6728A-4GTXSFP-24-24-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (24 VDC), -40 to 75°C operating temperature	3.340,00 €
IKS-6728A-4GTXSFP-24-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (24 VDC), -40 to 75°C operating temperature	2.886,00 €
IKS-6728A-4GTXSFP-48-48-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (48 VDC), -40 to 75°C operating temperature	3.340,00 €
IKS-6728A-4GTXSFP-48-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (48 VDC), -40 to 75°C operating temperature	2.886,00 €
IKS-6728A-4GTXSFP-HV-HV-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	2.805,00 €
IKS-6728A-4GTXSFP-HV-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (85 to 264 VAC), -40 to 75°C operating temperature	2.333,00 €

IKS-6728A-8PoE-4GTXSFP-48-48-T	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 2 isolated power supplies (48 VDC), -40 to 75°C operating temperature	4.630,00 €
IKS-6728A-8PoE-4GTXSFP-48-T	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 1 isolated power supply (48 VDC), -40 to 75°C operating temperature	4.120,00 €
IKS-6728A-8PoE-4GTXSFP-HV-HV-T	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	4.003,00 €
IKS-6728A-8PoE-4GTXSFP-HV-T	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 1 isolated power supply (85 to 264 VAC), -40 to 75°C operating temperature	3.513,00 €
IKS-G6524A-20GSFP-4GTXSFP-HV-HV	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	6.246,00 €
IKS-G6524A-20GSFP-4GTXSFP-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	6.800,00 €
IKS-G6524A-4GTXSFP-HV-HV	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	6.246,00 €
IKS-G6524A-4GTXSFP-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	6.800,00 €
IKS-G6524A-8GSFP-4GTXSFP-HV-HV	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	6.246,00 €
IKS-G6524A-8GSFP-4GTXSFP-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	6.800,00 €
IKS-G6824A-20GSFP-4GTXSFP-HV-HV	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	8.571,00 €
IKS-G6824A-20GSFP-4GTXSFP-HV-HV-T	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	9.089,00 €
IKS-G6824A-4GTXSFP-HV-HV	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	8.571,00 €
IKS-G6824A-4GTXSFP-HV-HV-T	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	9.089,00 €

IKS-G6824A-8GSFP-4GTXSFP-HV-HV	Layer 3 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	8.571,00 €
IKS-G6824A-8GSFP-4GTXSFP-HV-HV-T	Layer 3 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	9.089,00 €
IM-6700A-2MSC4TX	Fast Ethernet module with 2 multi-mode 100BaseFX ports with SC connector, 4 10/100BaseT(X) ports	489,00 €
IM-6700A-2MST4TX	Fast Ethernet module with 2 multi-mode 100BaseFX ports with ST connectors, 4 10/100BaseT(X) ports	489,00 €
IM-6700A-2SSC4TX	Fast Ethernet module with 2 single-mode 100BaseFX ports with SC connector, 4 10/100BaseT(X) ports	780,00 €
IM-6700A-4MSC2TX	Fast Ethernet module with 4 multi-mode 100BaseFX ports with SC connector, 2 10/100BaseT(X) ports	686,00 €
IM-6700A-4MST2TX	Fast Ethernet module with 4 multi-mode 100BaseFX ports with ST connectors, 2 10/100BaseT(X) ports	686,00 €
IM-6700A-4SSC2TX	Fast Ethernet module with 4 single-mode 100BaseFX ports with SC connectors, 2 10/100BaseT(X) ports	1.251,00 €
IM-6700A-6MSC	Fast Ethernet module with 6 multi-mode 100BaseFX ports with SC connectors	874,00 €
IM-6700A-6MST	Fast Ethernet module with 6 multi-mode 100BaseFX ports with ST connectors	874,00 €
IM-6700A-6SSC	Fast Ethernet module with 6 single-mode 100BaseFX ports with SC connectors	1.740,00 €
IM-6700A-8PoE	Fast Ethernet PoE+ module with 8 100BaseT(X) PoE/PoE+ ports (for IKS-6728A-8PoE Series only)	865,00 €
IM-6700A-8SFP	Fast Ethernet module with 8 100BaseSFP slots	583,00 €
IM-6700A-8TX	Fast Ethernet module with 8 10/100T(X) ports	260,00 €
IMC-101G	Industrial 10/100/1000BaseT(X) to 1000BaseSX/LX/LHX/ZX media converter, 0 to 60°C operating temperature	656,00 €
IMC-101G-IEEX	Industrial 10/100/1000BaseT(X) to 1000BaseSFP media converter, IECEx, 0 to 60°C operating temperature	756,00 €
IMC-101G-T	Industrial 10/100/1000BaseT(X) to 1000BaseSX/LX/LHX/ZX media converter, -40 to 75°C operating temperature	768,00 €
IMC-101G-T-IEEX	Industrial 10/100/1000BaseT(X) to 1000BaseSFP media converter, IECEx, -40 to 75°C operating temperature	882,00 €
IMC-101-M-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, 0 to 60°C operating temperature	359,00 €
IMC-101-M-SC-IEEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC connector, IECEx, 0 to 60°C operating temperature	410,00 €
IMC-101-M-SC-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, -40 to 75°C operating temperature	499,00 €
IMC-101-M-SC-T-IEEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC connector, IECEx, -40 to 75°C operating temperature	571,00 €
IMC-101-M-ST	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, 0 to 60°C operating temperature	359,00 €
IMC-101-M-ST-IEEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector, IECEx, 0 to 60°C operating temperature	410,00 €
IMC-101-M-ST-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, -40 to 75°C operating temperature	499,00 €
IMC-101-M-ST-T-IEEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector, IECEx, -40 to 75°C operating temperature	571,00 €
IMC-101-S-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, 40 km, 0 to 60°C operating temperature	577,00 €
IMC-101-S-SC-80	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, 80 km, 0 to 60°C operating temperature	2.155,00 €

IMC-101-S-SC-80-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, 80 km, -40 to 75°C operating temperature	2.251,00 €
IMC-101-S-SC-IEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC connector, 40 km, IECEx, 0 to 60°C operating temperature	661,00 €
IMC-101-S-SC-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, -40 to 75°C operating temperature	680,00 €
IMC-101-S-SC-T-IEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC connector, 40 km, IECEx, -40 to 75°C operating temperature	783,00 €
IMC-21A-M-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, -10 to 60°C operating temperature	260,00 €
IMC-21A-M-SC-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, -40 to 75°C operating temperature	335,00 €
IMC-21A-M-ST	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, -10 to 60°C operating temperature	260,00 €
IMC-21A-M-ST-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, -40 to 75°C operating temperature	335,00 €
IMC-21A-S-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, -10 to 60°C operating temperature	391,00 €
IMC-21A-S-SC-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, -40 to 75°C operating temperature	516,00 €
IMC-21GA	Industrial 10/100/1000BaseT(X) to 100/1000BaseSFP media converter, -10 to 60°C operating temperature	316,00 €
IMC-21GA-LX-SC	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 10 km, -10 to 60°C operating temperature	615,00 €
IMC-21GA-LX-SC-T	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 10 km, -40 to 75°C operating temperature	769,00 €
IMC-21GA-SX-SC	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 0.5 km, -10 to 60°C operating temperature	445,00 €
IMC-21GA-SX-SC-T	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 0.5 km, -40 to 75°C operating temperature	552,00 €
IMC-21GA-T	Industrial 10/100/1000BaseT(X) to 100/1000BaseSFP media converter, -40 to 75°C operating temperature	398,00 €
IMC-21-M-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC connector	260,00 €
IMC-21-M-ST	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector	260,00 €
IMC-21-S-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC connector	367,00 €
IMC-P101-M-SC	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with SC connector, 0 to 60°C operating temperature	704,00 €
IMC-P101-M-SC-T	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with SC connector, -40 to 75°C operating temperature	878,00 €
IMC-P101-M-ST	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with ST connector, 0 to 60°C operating temperature	775,00 €
IMC-P101-M-ST-T	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with ST connector, -40 to 75°C operating temperature	1.031,00 €
IMC-P101-S-SC	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with SC connector, 0 to 60°C operating temperature	983,00 €
IMC-P101-S-SC-T	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with SC connector, -40 to 75°C operating temperature	1.222,00 €
IMC-P101-S-ST	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with ST connector, 0 to 60°C operating temperature	1.062,00 €
IMC-P101-S-ST-T	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with ST connector, -40 to 75°C operating temperature	1.433,00 €
IMC-P21A-G2-M-SC	PoE+ industrial 10/100Base-T(X) to 100Base-FX media converter, multi-mode port with SC connector, -10 to 60°C operating temperature	552,00 €

IMC-P21A-G2-M-ST	PoE+ industrial 10/100Base-T(X) to 100Base-FX media converter, multi-mode port with ST connector, -10 to 60°C operating temperature	552,00 €
IMC-P21A-G2-S-SC	PoE+ industrial 10/100Base-T(X) to 100Base-FX media converter, single-mode port with SC connector, -10 to 60°C operating temperature	669,00 €
IMC-P21GA-G2	PoE+ industrial 10/100/1000Base-T(X) to 100/1000BaseSFP media converter, -10 to 60°C operating temperature	593,00 €
IMC-P21GA-G2-LX-SC	PoE+ industrial 10/100/1000Base-T(X) to 1000Base-LX media converter, single-mode port with SC connector, -10 to 60°C operating temperature	1.007,00 €
IMC-P21GA-G2-SX-SC	PoE+ industrial 10/100/1000Base-T(X) to 1000Base-SX media converter, multi-mode port with SC connector, -10 to 60°C operating temperature	828,00 €
IM-G7000A-4GSFP	Gigabit Ethernet interface module with 4 100/1000BaseSFP slots, -10 to 60°C operating temperature	1.117,00 €
IM-G7000A-4GTX	Gigabit Ethernet interface module with 4 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	1.117,00 €
IM-G7000A-4PoE	Gigabit Ethernet PoE+ interface module with 4 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	1.740,00 €
INJ-24	PoE+ Injector, maximum output of 30 W at 24/48 VDC, 0 to 60°C operating temperature	303,00 €
INJ-24A	Gigabit high-power PoE+ injector, max. output of 36W/60W at 24 or 48 VDC by 2-pair/4-pair mode, 0 to 60°C operating temperature	489,00 €
INJ-24A-T	Gigabit high-power PoE+ injector, max. output of 36W/60W at 24 or 48 VDC by 2-pair/4-pair mode, -40 to 75°C operating temperature	616,00 €
INJ-24-T	PoE+ Injector, maximum output of 30 W at 24/48 VDC, -40 to 75°C operating temperature	410,00 €
ioLogik 2512	Universal controller, 8 DIs, 8 DIOs, Click&Go Plus, -10 to 60°C operating temperature	846,00 €
ioLogik 2512-T	Universal controller, 8 DIs, 8 DIOs, Click&Go Plus, -40 to 75°C operating temperature	1.048,00 €
ioLogik 2542	Universal controller, 4 AIs, 12 DIOs, Click&Go Plus, -10 to 60°C operating temperature	1.131,00 €
ioLogik 2542-T	Universal controller, 4 AIs, 12 DIOs, Click&Go Plus, -40 to 75°C operating temperature	1.319,00 €
ioLogik E1210	Universal I/O, 16 DIs, -10 to 60°C operating temperature	281,00 €
ioLogik E1210-T	Universal I/O, 16 DIs, -40 to 75°C operating temperature	464,00 €
ioLogik E1211	Universal I/O, 16 DOs, -10 to 60°C operating temperature	308,00 €
ioLogik E1211-T	Universal I/O, 16 DOs, -40 to 75°C operating temperature	499,00 €
ioLogik E1212	Universal I/O, 8 DIs, 8 DIOs, -10 to 60°C operating temperature	308,00 €
ioLogik E1212-T	Universal I/O, 8 DIs, 8 DIOs, -40 to 75°C operating temperature	499,00 €
ioLogik E1212-T (CV-CT)	ioLogik E1212-T (CV-CT)	624,00 €
ioLogik E1213	Universal I/O, 8 DIs, 4 DOs, 4 DIOs, -10 to 60°C operating temperature	406,00 €
ioLogik E1213-T	Universal I/O, 8 DIs, 4 DOs, 4 DIOs, -40 to 75°C operating temperature	545,00 €
ioLogik E1214	Universal I/O, 6 DIs, 6 relays, -10 to 60°C operating temperature	318,00 €
ioLogik E1214-T	Universal I/O, 6 DIs, 6 relays, -40 to 75°C operating temperature	526,00 €
ioLogik E1240	Universal I/O, 8 AIs, -10 to 60°C operating temperature	441,00 €
ioLogik E1240-T	Universal I/O, 8 AIs, -40 to 75°C operating temperature	705,00 €
ioLogik E1240-T (CV-CT)	Universal I/O, 8 AIs, -40 to 75°C operating temperature, conformal coating	886,00 €
ioLogik E1241	Universal I/O, 4 AOs, -10 to 60°C operating temperature	576,00 €
ioLogik E1241-T	Universal I/O, 4 AOs, -40 to 75°C operating temperature	821,00 €
ioLogik E1242	Universal I/O, 4 AIs, 4 DIs, 4 DIOs, -10 to 60°C operating temperature	477,00 €
ioLogik E1242-T	Universal I/O, 4 AIs, 4 DIs, 4 DIOs, -40 to 75°C operating temperature	705,00 €
ioLogik E1260	Universal I/O, 6 RTDs, -10 to 60°C operating temperature	526,00 €
ioLogik E1260-T	Universal I/O, 6 RTDs, -40 to 75°C operating temperature	761,00 €
ioLogik E1262	Universal I/O, 8 TCs, -10 to 60°C operating temperature	576,00 €
ioLogik E1262-T	Universal I/O, 8 TCs, -40 to 75°C operating temperature	821,00 €

ioLogik E1510-M12-CT-T	Rugged I/O, 12 DIs, -40 to 85°C operating temperature, conformal coating	2.094,00 €
ioLogik E1510-M12-T	Rugged I/O, 12 DIs, -40 to 85°C operating temperature	1.621,00 €
ioLogik E1512-M12-CT-T	Rugged I/O, 4 DIs, 4 DIOS, -40 to 85°C operating temperature, conformal coating	2.047,00 €
ioLogik E1512-M12-T	Rugged I/O, 4 DIs, 4 DIOS, -40 to 85°C operating temperature	1.588,00 €
ioLogik E2210	Universal controller, 12 DIs, 8 DOs, Click&Go, -10 to 60°C operating temperature	476,00 €
ioLogik E2210-T	Universal controller, 12 DIs, 8 DOs, Click&Go, -40 to 75°C operating temperature	729,00 €
ioLogik E2212	Universal controller, 8 DIs, 8 DOs, 4 DIOS, Click&Go, -10 to 60°C operating temperature	647,00 €
ioLogik E2212-T	Universal controller, 8 DIs, 8 DOs, 4 DIOS, Click&Go, -40 to 75°C operating temperature	938,00 €
ioLogik E2214	Universal controller, 6 DIs, 6 relays, Click&Go, -10 to 60°C operating temperature	706,00 €
ioLogik E2214-T	Universal controller, 6 DIs, 6 relays, Click&Go, -40 to 75°C operating temperature	1.007,00 €
ioLogik E2240	Universal controller, 8 AIs, 2 AOs, Click&Go, -10 to 60°C operating temperature	839,00 €
ioLogik E2240-T	Universal controller, 8 AIs, 2 AOs, Click&Go, -40 to 75°C operating temperature	1.201,00 €
ioLogik E2242	Universal controller, 4 AIs, 12 DIOS, Click&Go, -10 to 60°C operating temperature	899,00 €
ioLogik E2242-T	Universal controller, 4 AIs, 12 DIOS, Click&Go, -40 to 75°C operating temperature	1.133,00 €
ioLogik E2260	Universal controller, 6 RTD, 4 DOs, Click&Go, -10 to 60°C operating temperature	806,00 €
ioLogik E2260-T	Universal controller, 6 RTD, 4 DOs, Click&Go, -40 to 75°C operating temperature	1.133,00 €
ioLogik E2262	Universal controller, 8 TCs, 4 DOs, Click&Go, -10 to 60°C operating temperature	899,00 €
ioLogik E2262-T	Universal controller, 8 TCs, 4 DOs, Click&Go, -40 to 75°C operating temperature	1.270,00 €
ioLogik R1210	Universal I/O, 16 DIs, -10 to 75°C operating temperature	279,00 €
ioLogik R1210-T	Universal I/O, 16 DIs, -40 to 85°C operating temperature	375,00 €
ioLogik R1212	Universal I/O, 8 DIs, 8 DIOS, -10 to 75°C operating temperature	312,00 €
ioLogik R1212-T	Universal I/O, 8 DIs, 8 DIOS, -40 to 85°C operating temperature	399,00 €
ioLogik R1214	Universal I/O, 6 DIs, 6 relays, -10 to 75°C operating temperature	322,00 €
ioLogik R1214-T	Universal I/O, 6 DIs, 6 relays, -40 to 85°C operating temperature	467,00 €
ioLogik R1240	Universal I/O, 8 AIs, -10 to 75°C operating temperature	444,00 €
ioLogik R1240-T	Universal I/O, 8 AIs, -40 to 85°C operating temperature	602,00 €
ioLogik R1241	Universal I/O, 4 AOs, -10 to 75°C operating temperature	550,00 €
ioLogik R1241-T	Universal I/O, 4 AOs, -40 to 85°C operating temperature	617,00 €
ioMirror E3210	Universal Peer-to-Peer I/O, 8 DIs, 8 DOs, -10 to 60°C operating temperature	441,00 €
ioPAC 8600-BM005-T	Module for the ioPAC 8600 Series, 5 slots, -40 to 75°C operating temperature	1.560,00 €
ioPAC 8600-BM009-T	Module for the ioPAC 8600 Series, 9 slots, -40 to 75°C operating temperature	2.655,00 €
ioPAC 8600-BM012-T	Module for the ioPAC 8600 Series, 12 slots, -40 to 75°C operating temperature	3.378,00 €
ioPAC 8600-CPU30-M12-C-T	Rugged controller, 1 GHz CPU, 2-port M12 Ethernet, C/C++, -40 to 75°C operating temperature	2.044,00 €
ioPAC 8600-CPU30-M12-IEC-T	Rugged controller, 1 GHz CPU, 2-port M12 Ethernet, IEC 61131-3, -40 to 75°C operating temperature	2.687,00 €
ioPAC 8600-CPU30-RJ45-C-T	Rugged controller, 1 GHz CPU, 2-port RJ45 Ethernet, C/C++, -40 to 75°C operating temperature	1.926,00 €
ioPAC 8600-CPU30-RJ45-IEC-T	Rugged controller, 1 GHz CPU, 2-port RJ45 Ethernet, IEC 61131-3, -40 to 75°C operating temperature	2.555,00 €
ioPAC 8600-PW10-30W-T	Module for the ioPAC 8600 Series, 24-110 VDC, 30 W, dual-power inputs, -40 to 75°C operating temperature	1.636,00 €
ioThinX 4510	Advanced I/O, Ethernet network adapter, 3-in-1 serial port(s), -20 to 60°C operating temperature	518,00 €

ioThinX 4510-T	Advanced I/O, Ethernet network adapter, 3-in-1 serial port(s), -40 to 75°C operating temperature	644,00 €
ioThinX 4533-LX	Advanced modular controller with built-in serial port, dual-core 1 GHz CPU, Linux, -20 to 60°C operating temperature	1.606,00 €
ioThinX 4533-LX-T	Advanced modular controller with built-in serial port, dual-core 1 GHz CPU, Linux, -40 to 75°C operating temperature	1.796,00 €
ISD-1110-T	7 data line entry surge protector, RS-232, 4 kV surge protection, -40 to 85°C operating temperature	126,00 €
ISD-1130-T	4 data line entry surge protector, RS-422/485, 4 kV surge protection, -40 to 85°C operating temperature	112,00 €
ISD-1210-T	4 data line advanced surge protector, RS-232, 20 kV surge protection, -40 to 85°C operating temperature	310,00 €
ISD-1230-T	4 data line advanced surge protector, RS-422/485, 20 kV surge protection, -40 to 85°C operating temperature	310,00 €
LB-DB9F-G-01	Serial loopback DB9 adaptor	8,00 €
LB-RJ458P-RS232	RS-232 Loopback Header 8-pin RJ45	6,00 €
LB-RJ458P-RS422	RS-422 Loopback Header 8-pin RJ45	6,00 €
LIC-DLM-ONPREM-NEW-XN-SR	DLM on-premises perpetual license (1 node)	144,00 €
LIC-DLM-ONPREM-NEW-XN-SR-3000	DLM on-premises perpetual license (3000 nodes)	137.635,00 €
LIC-DLM-ONPREM-NEW-XN-SR-50	DLM on-premises perpetual license (50 nodes)	5.735,00 €
LIC-DLM-ONPREM-NEW-XN-SR-500	DLM on-premises perpetual license (500 nodes)	45.879,00 €
LIC-IPS-DEVICE-1095Point(3Y)-MR	3-year (1095 points) device-based IPS license for a single device without management software.	2.370,00 €
LIC-IPS-DEVICE-1460Point(4Y)-MR	4-year (1460 points) device-based IPS license for a single device without management software.	3.160,00 €
LIC-IPS-DEVICE-1825Point(5Y)-MR	5-year (1825 points) device-based IPS license for a single device without management software.	3.949,00 €
LIC-IPS-DEVICE-365Point(1Y)-MR	1-year (365 points) device-based IPS license for a single device without management software.	790,00 €
LIC-IPS-DEVICE-730Point(2Y)-MR	2-year (730 points) device-based IPS license for a single device without management software.	1.580,00 €
LIC-IPS-MGMT-[X]Point-SR	IPS license for MXsecurity or MXview Security add-on management software with customizable point balance (minimum 365 points).	3,00 €
LIC-MRCQL-ADD-1Y-XGB-SR	1-year MRC Quick Link add-on license with customizable data volume (minimum 1 GB)	11,00 €
LIC-MRCQL-ADD-1Y-XN-SR	1-year MRC Quick Link add-on license with customizable node quantity (minimum 1 node)	28,00 €
LIC-MRCQLULTRA-ADD-1Y-XGB-SR	LIC-MRCQLULTRA-ADD-1Y-XGB-SR	11,00 €

LIC-MRCQLULTRA-ADD-1Y-XN-SR	LIC-MRCQLULTRA-ADD-1Y-XN-SR	27,00 €
LIC-MXsecurity-NEW-XN-SR	MXsecurity perpetual node license with customizable node quantity (minimum 1 node)	136,00 €
LIC-MXviewOne-ADD-POWER-MR	MXview One add-on license to enable MXview Power module functionality	21.379,00 €
LIC-MXviewOne-ADD-SECURITY-MR	MXview One add-on license to enable MXview Security module functionality	1.501,00 €
LIC-MXviewOne-ADD-WIRELESS-MR	MXview One add-on license to enable MXview Wireless module functionality	1.316,00 €
LIC-MXviewOneCM-ADD-POWER-XS-SR	MXview One Central Manager license to enable the Power add-on for MXview One sites, customizable site quantity (minimum 1 site)	21.379,00 €
LIC-MXviewOneCM-ADD-WIRELESS-XS-SR	MXview One Central Manager license to enable the Wireless add-on for MXview One sites, customizable site quantity (minimum 1 site)	1.316,00 €
LIC-MXviewOneCM-NEW-XS-SR	MXview One Central Manager site license with customizable site quantity (minimum 1 site)	422,00 €
LIC-MXviewOne-NEW-XN-SR	MXview One node license with customizable node quantity (minimum 1 node)	72,00 €
LM-7000H-2GPHR	Gigabit Ethernet module with 2 100/1000BaseT(X) PRP/HSR or 100/1000BaseSFP PRP/HSR combo ports, -40 to 75°C operating temperature	2.676,00 €
LM-7000H-4GPoE	Gigabit Ethernet module with 4 10/100/1000BaseT(X) IEEE 802.3bt PoE++ ports	1.319,00 €
LM-7000H-4GSFP	Gigabit Ethernet module with 4 100/1000BaseSFP slots	905,00 €
LM-7000H-4GTx	Gigabit Ethernet module with 4 10/100/1000BaseT(X) ports	905,00 €
LM-7000H-4PoE	Fast Ethernet module with 4 10/100BaseT(X) IEEE 802.3bt PoE++ ports	900,00 €
LM-7000H-4Tx	Fast Ethernet module with 4 10/100BaseT(X) ports	542,00 €
LM-7000H-DMY	LM-7000H dummy module, 3 pcs	49,00 €
LNA-1120-T	Industrial 5G low-noise amplifier, n48, n78, n79, n1, n3, and n7 bands, IP30, -40°C to 70°C operating temperature	194,00 €
M12A-4PFF-IP67	M12 cable connector, female 4-pin, A-coded	152,00 €
M12A-4PMM-IP67	M12 cable connector, male 4-pin, A-coded	146,00 €
M12A-5PFF-IP67-HTG (5 Pin)	Crimp type M12 connector, female 5-pin, A-coded, IP67-rated	152,00 €
M12A-5P-IP68	Solder type M12 connector, female 5-pin, A-coded, IP68-rated	24,00 €
M12A-5P-IP68-SCREW	Field-installable A-coded M12 screw-in 5-pin (female) connector, IP68	52,00 €

M12A-5PMM-IP68	5-pin male circular threaded D-coded M12 USB connector, IP68	35,00 €
M12A-8PFF-IP68	Field-installation A-coded M12 screw-in 8-pin connector, female connector female PIN	28,00 €
M12A-8PMM-IP67	IDC type M12 connector, male 8-pin, A-coded, IP67-rated	152,00 €
M12A-8PMM-IP68	Field-installation A-coded screw-in Gigabit Ethernet connector, 8-pin male M12 connector, IP68-rated	18,00 €
M12D-4P-IP68	Solder type M12 connector, male 4-pin, D-coded, IP68-rated	25,00 €
M12D-4PMM-IP67	IDC type M12 connector, male 4-pin, D-coded, IP67-rated	106,00 €
M12K-5PFF-IP65-PxC	Crimp type M12 connector, female 5-pin, K-coded, IP65-rated	172,00 €
M12X-8PMM-IP65	M12 cable connector, male 8-pin, X-coded	287,00 €
M12X-8PMM-IP67	8-pin male X-coded circular threaded gigabit Ethernet connector, IP67	254,00 €
M12X-8PMM-IP67-HTG	Crimp type M12 connector, male 8-pin, X-coded, IP67-rated	165,00 €
M12X-M12D-IP68	M12X-M12D-IP68	21,00 €
MAT-5G-PA-SM-2-06-3m	6 dBi MIMO panel antenna with 2 SMA (male) connectors for cellular applications, 3 m cable	569,00 €
MAT-5G-PA-SM-3-06-3m	6 dBi MIMO panel antenna with 3 SMA (male) connectors for cellular and GNSS applications, 3 m cable	711,00 €
MAT-5G-PA-SM-4-05-1m	5 dBi at 3300 to 5925 MHz, LTE/NR MIMO panel antenna with 4 SMA connectors (male), 4 1-meter cables	665,00 €
MAT-WDB-CA-RM-2-0205	2.4/5 GHz, ceiling antenna, 2/5 dBi, MIMO 2x2, RP-SMA-type (male)	102,00 €
MAT-WDB-DA-RM-2-0203-1m	2.4/5 GHz, desktop antenna, 2/3 dBi, MIMO 2x2, RP-SMA-type (male), 1 m cable	102,00 €
MAT-WDB-PA-NF-2-0708	2.4/5 GHz, panel antenna, 7/8 dBi, MIMO 2x2, N-type (female)	339,00 €
MC-1100 DIN-Rail Kit	DIN-rail mounting kit, 4 screws	16,00 €
MC-1100 Wallmount Kit	Wall-mounting kit, 4 screws	20,00 €
MC-1111-E2-T	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 1 CFast socket, 1 SD slot, 1 DisplayPort, 12 to 36 VDC power, -40 to 70°C operating temperature	2.067,00 €
MC-1111-E4-T	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 1 CFast socket, 1 SD slot, 1 DisplayPort, 12 to 36 VDC power, -40 to 70°C operating temperature	2.164,00 €
MC-1112-E2-T	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 2 serial ports, 1 CFast socket, 12 to 36 VDC power, -40 to 70°C operating temperature	2.097,00 €
MC-1112-E4-T	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 2 serial ports, 1 CFast socket, 12 to 36 VDC power, -40 to 70°C operating temperature	2.181,00 €
MC-1121-E2-T	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 CFast socket, 1 SD slot, 1 DisplayPort, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature	2.424,00 €

MC-1121-E4-T	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 CFast socket, 1 SD slot, 1 DisplayPort, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature	2.516,00 €
MC-1121-E4-T-W7E	x86 embedded computer with Intel Atom® quad-core E3845 processor, 1 CFast socket with 32 GB card preinstalled, Windows Embedded Standard 7 preinstalled, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 SD slot, 1 DisplayPort, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature	3.015,00 €
MC-1122-E2-T	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 4 serial ports, 4 DIs, 4 DOs, 1 CFast socket, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature	2.367,00 €
MC-1122-E4-T	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 4 serial ports, 4 DIs, 4 DOs, 1 CFast socket, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature	2.449,00 €
MC-1122-E4-TPM-T	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 4 serial ports, 4 DIs, 4 DOs, 1 CFast socket, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature, TPM 1.2	2.449,00 €
MC-1220 DIN-Rail Kit	DIN-rail mounting kit for MC-1200 with 4 M3 screws	16,00 €
MC-1220 Wallmount Kit	Wall-mounting kit for MC-1200 with 4 M3 screws	20,00 €
MC-1220-KL1-T-S	Intel® Celeron® 3965U 2C/2T 2.2 GHz computer with 8 GB RAM, 2 Gigabit Ethernet ports, 2 RS/232/422/485 3-in-1 serial ports, 3 USB 3.0 ports, 3 Mini PCIe expansion slots, 1 HDMI port, TPM 2.0, 9 to 36 VDC power, -40 to 70°C operating temperature	3.921,00 €
MC-1220-KL5-T-S	Intel® Core™ i5-7300U 2C/4T 2.6 GHz computer with 8 GB RAM, 2 Gigabit Ethernet ports, 2 RS/232/422/485 3-in-1 serial ports, 3 USB 3.0 ports, 3 Mini PCIe expansion slots, 1 HDMI port, TPM 2.0, 9 to 36 VDC power, -40 to 70°C operating temperature	5.483,00 €
MC-1220-KL7-T-S	Intel® Core™ i7-7600U 2C/4T 2.8 GHz computer with 8 GB RAM, 2 Gigabit Ethernet ports, 2 RS/232/422/485 3-in-1 serial ports, 3 USB 3.0 ports, 3 Mini PCIe expansion slots, 1 HDMI port, TPM 2.0, 9 to 36 VDC power, -40 to 70°C operating temperature	6.163,00 €
MC-1220-LTE Cat4-EU	Wireless package for the MC-1200 Series with LE910C4-NF 4G module and mPCIe module for the EU region	265,00 €
MC-1220-WLAN11-AC	Wireless package for the MC-1200 Series with WPEQ-261ACNI(BT) 802.11ac/a/b/g/n Wi-Fi module and mPCIe module	231,00 €
MDR-40-24	DIN-rail 24 VDC power supply with 40W/1.7A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature	109,00 €
MDR-60-24	DIN-rail 24 VDC power supply with 60W/2.5A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature	149,00 €
MDS-G4012	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -10 to 60°C operating temperature	3.325,00 €
MDS-G4012-4XGS-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 8 Gigabit Ethernet ports, -40 to 75°C operating temperature	7.549,00 €
MDS-G4012-L3	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -10 to 60°C operating temperature	5.194,00 €
MDS-G4012-L3-4XGS-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 8 Gigabit Ethernet ports, -40 to 75°C operating temperature	9.915,00 €

MDS-G4012-L3-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -40 to 75°C operating temperature	5.697,00 €
MDS-G4012-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -40 to 75°C operating temperature	3.796,00 €
MDS-G4020	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -10 to 60°C operating temperature	3.612,00 €
MDS-G4020-4XGS-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 16 Gigabit Ethernet ports, -40 to 75°C operating temperature	9.032,00 €
MDS-G4020-L3	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -10 to 60°C operating temperature	5.494,00 €
MDS-G4020-L3-4XGS-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 16 Gigabit Ethernet ports, -40 to 75°C operating temperature	11.380,00 €
MDS-G4020-L3-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -40 to 75°C operating temperature	5.997,00 €
MDS-G4020-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -40 to 75°C operating temperature	4.066,00 €
MDS-G4028	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -10 to 60°C operating temperature	3.868,00 €
MDS-G4028-4XGS-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 24 Gigabit Ethernet ports, -40 to 75°C operating temperature	10.498,00 €
MDS-G4028-L3	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -10 to 60°C operating temperature	5.759,00 €
MDS-G4028-L3-4XGS-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 24 Gigabit Ethernet ports, -40 to 75°C operating temperature	12.864,00 €
MDS-G4028-L3-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -40 to 75°C operating temperature	6.270,00 €
MDS-G4028-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -40 to 75°C operating temperature	4.323,00 €
ME-10-T	1-slot chassis with redundant 12 to 48 VDC power inputs	171,00 €
MGate 4101I-MB-PBS	1-port Modbus-to-PROFIBUS Slave gateway with 2 kV isolation, 12 to 48 VDC, 0 to 60°C operating temperature	1.148,00 €

MGate 4101I-MB-PBS-T	1-port Modbus-to-PROFIBUS Slave gateway with 2 kV isolation, 12 to 48 VDC, -40 to 75°C operating temperature	1.386,00 €
MGate 4101-MB-PBS	1-port Modbus-to-PROFIBUS Slave gateway, 12 to 48 VDC, 0 to 60°C operating temperature	962,00 €
MGate 4101-MB-PBS-T	1-port Modbus-to-PROFIBUS Slave gateway, 12 to 48 VDC, -40 to 75°C operating temperature	1.215,00 €
MGate 5101-PBM-MN	1-port PROFIBUS master-to-Modbus TCP gateway, 12 to 48 VDC, 0 to 60°C operating temperature	1.658,00 €
MGate 5101-PBM-MN-T	1-port PROFIBUS master-to-Modbus TCP gateway, 12 to 48 VDC, -40 to 75°C operating temperature	1.991,00 €
MGate 5102-PBM-PN	1-port PROFIBUS-to-PROFINET gateway, 12 to 48 VDC, 0 to 60°C operating temperature	1.658,00 €
MGate 5102-PBM-PN-T	1-port PROFIBUS-to-PROFINET gateway, 12 to 48 VDC, -40 to 75°C operating temperature	2.078,00 €
MGate 5103	1-port Modbus/EtherNet/IP-to-PROFINET gateway, 0 to 60°C operating temperature	913,00 €
MGate 5103-T	1-port Modbus/EtherNet/IP-to-PROFINET gateway, -40 to 75°C operating temperature	1.132,00 €
MGate 5105-MB-EIP	1-port MQTT-supported Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, 0 to 60°C operating temperature	913,00 €
MGate 5105-MB-EIP-T	1-port MQTT-supported Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -40 to 75°C operating temperature	1.149,00 €
MGate 5109	1-port Modbus-to-DNP3 gateway, 0 to 60°C operating temperature	913,00 €
MGate 5109 (CV-CT)	1-port Modbus-to-DNP3 gateway, 0 to 60°C operating temperature, conformal coating	1.168,00 €
MGate 5109-T	1-port Modbus-to-DNP3 gateway, -40 to 75°C operating temperature	1.149,00 €
MGate 5109-T (CV-CT)	1-port Modbus-to-DNP3 gateway, -40 to 75°C operating temperature, conformal coating	1.456,00 €
MGate 5111	1-port Modbus/PROFINET/EtherNet/IP to PROFIBUS Slave gateway, 0 to 60°C operating temperature	913,00 €
MGate 5111 (CV-CT)	1-port Modbus/PROFINET/EtherNet/IP to PROFIBUS Slave gateway, 0 to 60°C operating temperature, CV-CT, conformal coating	1.168,00 €
MGate 5111-T	1-port Modbus/PROFINET/EtherNet/IP-to-PROFIBUS Slave gateway, -40 to 75°C operating temperature	1.132,00 €
MGate 5111-T (CV-CT)	1-port Modbus/PROFINET/EtherNet/IP-to-PROFIBUS Slave gateway, -40 to 75°C operating temperature, conformal coating	1.456,00 €
MGate 5114	1-port Modbus/IEC101 to IEC104 gateway, 0 to 60°C operating temperature	913,00 €
MGate 5114-T	1-port Modbus/IEC101 to IEC104 gateway, -40 to 75°C operating temperature	1.132,00 €
MGate 5118	1-port J1939 to Modbus/PROFINET/EtherNet/IP gateway, 0 to 60°C operating temperature	913,00 €
MGate 5118-T	1-port J1939 to Modbus/PROFINET/EtherNet/IP gateway, -40 to 75°C operating temperature	1.149,00 €
MGate 5119-T	1-port DNP3/IEC 101/IEC 104/Modbus-to-IEC 61850 gateways, -40 to 75°C operating temperature	1.658,00 €
MGate 5121	1-port CAN-to-Modbus TCP gateways, -10 to 60°C operating temperature	1.086,00 €
MGate 5121-T	1-port CAN-to-Modbus TCP gateways, -40 to 75°C operating temperature	1.354,00 €
MGate 5122	1-port CAN-to-EtherNet/IP gateways, -10 to 60°C operating temperature	1.086,00 €
MGate 5122-T	1-port CAN-to-EtherNet/IP gateways, -40 to 75°C operating temperature	1.354,00 €
MGate 5123	1-port CAN-to-PROFINET gateways, -10 to 60°C operating temperature	1.086,00 €
MGate 5123-T	1-port CAN-to-PROFINET gateways, -40 to 75°C operating temperature	1.354,00 €
MGate 5134	1-port Modbus RTU/ASCII/TCP-to-PROFINET gateways, -10 to 60°C operating temperature	913,00 €
MGate 5134-T	1-port Modbus RTU/ASCII/TCP-to-PROFINET gateways, -40 to 75°C operating temperature	1.132,00 €
MGate 5135	1-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -10 to 60°C operating temperature	913,00 €

MGate 5135-T	1-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -40 to 75°C operating temperature	1.132,00 €
MGate 5192-T	1-port IEC 61850-to-DNP3/IEC 101/IEC 104/Modbus gateway with -40 to 75°C operating temperature	1.695,00 €
MGate 5216	2-port serial/Modbus-to-EtherCAT gateway with 0 to 60°C operating temperature	1.376,00 €
MGate 5216-T	2-port serial/Modbus-to-EtherCAT gateway with -40 to 75°C operating temperature	1.709,00 €
MGate 5217I-1200-T	2-port Modbus-to-BACnet/IP gateway, 1200 points, 2kV isolation, 12 to 48 VDC, 24 VAC, -40 to 75°C operating temperature	1.696,00 €
MGate 5217I-600-T	2-port Modbus-to-BACnet/IP gateway, 600 points, 2kV isolation, 12 to 48 VDC, 24 VAC, -40 to 75°C operating temperature	935,00 €
MGate 5435	4-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -10 to 60°C operating temperature	1.521,00 €
MGate 5435-T	4-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -40 to 75°C operating temperature	1.883,00 €
MGate EIP3170	1-port EtherNet/IP-to-DF1 gateway, 0 to 60°C operating temperature	527,00 €
MGate EIP3170I	1-port EtherNet/IP-to-DF1 gateway with 2 kV isolation, 0 to 60°C operating temperature	605,00 €
MGate EIP3170I-T	1-port EtherNet/IP-to-DF1 gateway with 2 kV isolation, -40 to 75°C operating temperature	795,00 €
MGate EIP3170-T	1-port EtherNet/IP-to-DF1 gateway, -40 to 75°C operating temperature	685,00 €
MGate EIP3270	2-port EtherNet/IP-to-DF1 gateway, 0 to 60°C operating temperature	871,00 €
MGate EIP3270I	2-port EtherNet/IP-to-DF1 gateway with 2 kV isolation, 0 to 60°C operating temperature	1.048,00 €
MGate EIP3270-T	2-port EtherNet/IP-to-DF1 gateway, -40 to 75°C operating temperature	1.132,00 €
MGate MB3170	1-port advanced Modbus gateway, 0 to 60°C operating temperature	517,00 €
MGate MB3170-G2	1-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, -10 to 60°C operating temperature	543,00 €
MGate MB3170-G2-T	1-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, -40 to 75°C operating temperature	724,00 €
MGate MB3170I	1-port advanced Modbus gateway with 2 kV isolation, 0 to 60°C operating temperature	605,00 €
MGate MB3170I-G2	1-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, 2 kV isolation, -10 to 60°C operating temperature	638,00 €
MGate MB3170I-G2-T	1-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, 2 kV isolation, -40 to 75°C operating temperature	840,00 €
MGate MB3170I-M-SC	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 60°C operating temperature	789,00 €
MGate MB3170I-M-SC-T	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	1.048,00 €
MGate MB3170I-S-SC	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 60°C operating temperature	913,00 €
MGate MB3170I-S-SC-T	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	1.201,00 €
MGate MB3170I-T	1-port advanced Modbus gateway with 2 kV isolation, -40 to 75°C operating temperature	879,00 €
MGate MB3170-M-SC	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors), 0 to 60°C operating temperature	676,00 €
MGate MB3170-M-SC-G2	1-port advanced serial-to-Ethernet Modbus gateway with 1 RJ45 + 1 multi-mode SC fiber Ethernet ports, DB9 serial connector, -10 to 60°C operating temperature	703,00 €

MGate MB3170-M-SC-G2-T	1-port advanced serial-to-Ethernet Modbus gateway with 1 RJ45 + 1 multi-mode SC fiber Ethernet ports, DB9 serial connector, -40 to 75°C operating temperature	913,00 €
MGate MB3170-M-SC-T	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors), -40 to 75°C operating temperature	883,00 €
MGate MB3170-M-ST	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (ST connectors), 0 to 60°C operating temperature	676,00 €
MGate MB3170-M-ST-G2	1-port advanced serial-to-Ethernet Modbus gateway with 1 RJ45 + 1 multi-mode ST fiber Ethernet ports, DB9 serial connector, -10 to 60°C operating temperature	703,00 €
MGate MB3170-M-ST-G2-T	1-port advanced serial-to-Ethernet Modbus gateway with 1 RJ45 + 1 multi-mode ST fiber Ethernet ports, DB9 serial connector, -40 to 75°C operating temperature	913,00 €
MGate MB3170-M-ST-T	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (ST connectors), -40 to 75°C operating temperature	883,00 €
MGate MB3170-SFP-G2	1-port advanced serial-to-Ethernet Modbus gateway with 1 RJ45 + 1 SFP Ethernet ports, DB9 serial connector, -10 to 60°C operating temperature	696,00 €
MGate MB3170-SFP-G2-T	1-port advanced serial-to-Ethernet Modbus gateway with 1 RJ45 + 1 SFP Ethernet ports, DB9 serial connector, -40 to 75°C operating temperature	934,00 €
MGate MB3170-S-SC	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors), 0 to 60°C operating temperature	769,00 €
MGate MB3170-S-SC-G2	1-port advanced serial-to-Ethernet Modbus gateway with 1 RJ45 + 1 single-mode SC fiber Ethernet ports, DB9 serial connector, -10 to 60°C operating temperature	811,00 €
MGate MB3170-S-SC-G2-T	1-port advanced serial-to-Ethernet Modbus gateway with 1 RJ45 + 1 single-mode SC fiber Ethernet ports, DB9 serial connector, -40 to 75°C operating temperature	1.058,00 €
MGate MB3170-S-SC-T	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors), -40 to 75°C operating temperature	1.008,00 €
MGate MB3170-T	1-port advanced Modbus gateway, -40 to 75°C operating temperature	745,00 €
MGate MB3180	1-port standard Modbus gateway	384,00 €
MGate MB3270	2-port advanced Modbus gateway, 0 to 60°C operating temperature	962,00 €
MGate MB3270-G2	2-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, -10 to 60°C operating temperature	848,00 €
MGate MB3270-G2-T	2-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, -40 to 75°C operating temperature	1.101,00 €
MGate MB3270I	2-port advanced Modbus gateway with 2 kV isolation, 0 to 60°C operating temperature	1.152,00 €
MGate MB3270I-G2	2-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, 2 kV isolation, -10 to 60°C operating temperature	1.014,00 €
MGate MB3270I-G2-T	2-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, 2 kV isolation, -40 to 75°C operating temperature	1.318,00 €
MGate MB3270I-T	2-port advanced Modbus gateway with 2 kV isolation, -40 to 75°C operating temperature	1.486,00 €
MGate MB3270I-TB-G2	2-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, 5-pin terminal block serial connector, 2 kV isolation, -10 to 60°C operating temperature	1.014,00 €
MGate MB3270I-TB-G2-T	2-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, 5-pin terminal block serial connector, 2 kV isolation, -40 to 75°C operating temperature	1.318,00 €
MGate MB3270-T	2-port advanced Modbus gateway, -40 to 75°C operating temperature	1.253,00 €

MGate MB3270-TB-G2	2-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, 5-pin terminal block serial connector, -10 to 60°C operating temperature	848,00 €
MGate MB3270-TB-G2-T	2-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, 5-pin terminal block serial connector, -40 to 75°C operating temperature	1.101,00 €
MGate MB3280	2-port standard Modbus gateway	677,00 €
MGate MB3470-G2	4-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, -10 to 60°C operating temperature	1.267,00 €
MGate MB3470-G2-T	4-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, -40 to 75°C operating temperature	1.651,00 €
MGate MB3470I-G2	4-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, 2 kV isolation, -10 to 60°C operating temperature	1.521,00 €
MGate MB3470I-G2-T	4-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, DB9 serial connector, 2 kV isolation, -40 to 75°C operating temperature	1.984,00 €
MGate MB3470I-TB-G2	4-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, 5-pin terminal block serial connector, 2 kV isolation, -10 to 60°C operating temperature	1.521,00 €
MGate MB3470I-TB-G2-T	4-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, 5-pin terminal block serial connector, 2 kV isolation, -40 to 75°C operating temperature	1.984,00 €
MGate MB3470-TB-G2	4-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, 5-pin terminal block serial connector, -10 to 60°C operating temperature	1.267,00 €
MGate MB3470-TB-G2-T	4-port advanced serial-to-Ethernet Modbus gateway with 2 RJ45 Ethernet ports, 5-pin terminal block serial connector, -40 to 75°C operating temperature	1.651,00 €
MGate MB3480	4-port standard Modbus gateway	1.032,00 €
MGate MB3660-16-2AC	Modbus gateway with dual LANs, dual AC power inputs, 16 RS-232/422/485 ports, 0 to 60°C operating temperature	2.798,00 €
MGate MB3660-16-2DC	Modbus gateway with dual LANs, dual DC power inputs, 16 RS-232/422/485 ports, 0 to 60°C operating temperature	2.938,00 €
MGate MB3660-16-J-2AC	Modbus gateway with dual LANs, dual AC power inputs, 16 RS-232/422/485 ports, RJ45 serial interface, 0 to 60°C operating temperature	2.988,00 €
MGate MB3660-8-2AC	Modbus gateway with dual LANs, dual AC power inputs, 8 RS-232/422/485 ports, 0 to 60°C operating temperature	2.229,00 €
MGate MB3660-8-2DC	Modbus gateway with dual LANs, dual DC power inputs, 8 RS-232/422/485 ports, 0 to 60°C operating temperature	2.362,00 €
MGate MB3660-8-J-2AC	Modbus gateway with dual LANs, dual AC power inputs, 8 RS-232/422/485 ports, RJ45 serial interface, 0 to 60°C operating temperature	2.362,00 €
MGate MB3660I-16-2AC	Modbus gateway with dual LANs, dual AC power inputs, 16 RS-232/422/485 ports, 0 to 60°C operating temperature, 2 kV isolation	4.050,00 €
MGate MB3660I-8-2AC	Modbus gateway with dual LANs, dual AC power inputs, 8 RS-232/422/485 ports, 0 to 60°C operating temperature, 2 kV isolation	2.717,00 €
MiiNePort E1	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 0 to 55°C operating temperature	89,00 €
MiiNePort E1-H	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 50 bps to 921.6K baudrate, 0 to 55°C operating temperature	110,00 €
MiiNePort E1-H-ST	Starter Kit for the Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 50 bps to 921.6K baudrate, 0 to 55°C operating temperature	274,00 €
MiiNePort E1-H-T	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 50 bps to 921.6K baudrate, -40°C to 85°C operating temperature	160,00 €
MiiNePort E1-SDK	MiiNePort E1 software development kit	453,00 €

MiiNePort E1-ST	Starter kit for the MiiNePort E1 Series, module included	266,00 €
MiiNePort E1-ST (w/o Module)	Starter kit for the MiiNePort E1 Series, module not included	173,00 €
MiiNePort E1-T	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, -40 to 85°C operating temperature	128,00 €
MiiNePort E2	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 230.4 Kbps baudrate, 0 to 55°C operating temperature	78,00 €
MiiNePort E2-H	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 921.6 Kbps baudrate, 0 to 55°C operating temperature	81,00 €
MiiNePort E2-H-ST	Starter kit for the MiiNePort E2-H Series, module included	275,00 €
MiiNePort E2-H-T	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 921.6 Kbps baudrate, -40 to 85°C operating temperature	110,00 €
MiiNePort E2-SDK	MiiNePort E2 software development kit	453,00 €
MiiNePort E2-ST	Starter kit for the MiiNePort E2 Series, module included	269,00 €
MiiNePort E2-T	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 230.4 Kbps baudrate, -40 to 85°C operating temperature	107,00 €
MiiNePort E3	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 230.4 Kbps baudrate, 0 to 55°C operating temperature	81,00 €
MiiNePort E3-H	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 921.6 Kbps baudrate, 0 to 55°C operating temperature	89,00 €
MiiNePort E3-H-ST	Starter kit for the MiiNePort E3-H Series, module included	236,00 €
MiiNePort E3-H-T	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 921.6 Kbps baudrate, -40 to 85°C operating temperature	117,00 €
MiiNePort E3-ST	Starter kit for the MiiNePort E3 Series, module included	232,00 €
MiiNePort E3-T	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 230.4 Kbps baudrate, -40 to 85°C operating temperature	114,00 €
Mini DB9F-to-TB	DB9 female to terminal block connector	15,00 €
Moxa EtherNet/IP Demo Kit	EtherNet/IP Demo Kit	8.250,00 €
Moxa PI Demo Kit	PI Demo Kit	11.355,00 €
Moxa PROFINET Demo Kit	PROFINET Demo Kit	14.954,00 €
MPC-2070-E2-LB-T	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 350-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	3.146,00 €
MPC-2070-E2-LB-T-W7E	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 350-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, W7E OS	4.155,00 €
MPC-2070-E2-T	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	3.473,00 €
MPC-2070-E2-T-W7E	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, W7E OS	4.409,00 €

MPC-2-07-12-VESAMTK	MPC-2-07-12-VESAMTK	46,00 €
MPC-2101-E4-CT-T	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1000-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	7.153,00 €
MPC-2101-E4-CT-T-LX	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 1000-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN50155, -40 to 70°C operating temperature, conformal coating	7.556,00 €
MPC-2101-E4-LB-CT-T	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	6.722,00 €
MPC-2101-E4-LB-CT-T-LX	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 500-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	7.073,00 €
MPC-2120-E2-LB-T	12-inch panel computer with Intel Atom® E3826 1.46 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature	4.122,00 €
MPC-2120-E2-T	12-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	4.627,00 €
MPC-2120-E4-LB-T	12-inch panel computer, Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature	4.411,00 €
MPC-2120-E4-T	12-inch panel computer, Intel Atom® E3845 1.91 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	4.791,00 €
MPC-2121-E4-CT-T	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1000-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	7.584,00 €
MPC-2121-E4-CT-T-LX	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 1000-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	8.102,00 €
MPC-2121-E4-LB-CT-T	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	7.045,00 €
MPC-2121-E4-LB-CT-T-LX	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 500-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	7.556,00 €
MPC-3070W-E2-LB-T	7-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	2.760,00 €
MPC-3070W-E2-T	7-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.010,00 €
MPC-3070W-E4-LB-T	7-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	2.874,00 €
MPC-3070W-E4-T	7-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.117,00 €

MPC-3100-E2-LB-T	10.4-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.282,00 €
MPC-3100-E2-T	10.4-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.532,00 €
MPC-3100-E4-LB-T	10.4-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.403,00 €
MPC-3100-E4-T	10.4-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.639,00 €
MPC-3120-E2-LB-T	12.1-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.589,00 €
MPC-3120-E2-T	12.1-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.832,00 €
MPC-3120-E4-LB-T	12.1-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.689,00 €
MPC-3120-E4-T	12.1-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.946,00 €
MPC-3120W-E2-LB-T	12.1-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.832,00 €
MPC-3120W-E2-T	12.1-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	4.075,00 €
MPC-3120W-E4-LB-T	12.1-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	3.946,00 €
MPC-3120W-E4-T	12.1-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	4.189,00 €
MPC-3150-E2-LB-T	15-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	4.404,00 €
MPC-3150-E2-T	15-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	4.647,00 €
MPC-3150-E4-LB-T	15-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	4.518,00 €
MPC-3150-E4-T	15-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	4.761,00 €
MPC-3150W-E2-LB-T	15.6-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	4.675,00 €
MPC-3150W-E2-T	15.6-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	4.932,00 €

MPC-3150W-E4-LB-T	15.6-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	4.789,00 €
MPC-3150W-E4-T	15.6-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	5.047,00 €
MRX-G4064-L3-8XGS	Layer 3 modular managed Gigabit Ethernet switch with 3 slots for 16-port Gigabit Ethernet modules, 8 10GbE SFP+ slots, 2 isolated power supplies (90 to 264 VAC), -10 to 60°C operating temperature	27.874,00 €
MRX-Q4064-L3-16XGS	Layer 3 modular managed 2.5 Gigabit Ethernet switch with 16 10GbE SFP+ ports, 3 slots for 16-port Gigabit or 2.5 Gigabit Ethernet modules, 2 isolated power supplies (90 to 264 VAC), -10 to 60°C operating temperature	39.241,00 €
MX-AOPC UA Server	OPC UA Server software for converting fieldbus to the OPC UA standard	834,00 €
NAT-102	2-port industrial Network Address Translation (NAT) devices, -10 to 60°C operating temperature	884,00 €
NAT-102-T	2-port industrial Network Address Translation (NAT) devices, -40 to 75°C operating temperature	1.034,00 €
NAT-108	8-port industrial Network Address Translation (NAT) devices, -10 to 60°C operating temperature	1.007,00 €
NAT-108-T	8-port industrial Network Address Translation (NAT) devices, -40 to 75°C operating temperature	1.152,00 €
NDR-120-24	120 W/5.0 A DIN-rail 24 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature	168,00 €
NDR-120-48	120 W/2.5 A DIN-rail 48 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature	168,00 €
NDR-240-48	240 W/5.0 A DIN-rail 48 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature	408,00 €
NE-4100-ST	Starter Kit for NE-4100T, NE-4100T-P	154,00 €
NE-4100T	Device server module for TTL devices, supports 10/100BaseT(x) with DIL package	90,00 €
NE-4100T-P	Programmable 10/100 Mbps embedded serial device servers, wide temp	94,00 €
NE-4100T-T	Device server module for TTL devices, supports 10/100BaseT(x) with DIL package, -40 to 75°C operating temperature	119,00 €
NE-4110A	Device server module for RS-422/485 devices, supports 10/100BaseT(x) with RJ45 connector	97,00 €
NE-4110A-P	Programmable device server module for RS-422/485 devices, supports 10/100BaseT(x) with RJ45 connector	119,00 €
NE-4110A-T	Device server module for RS-422/485 devices, supports 10/100BaseT(x) with RJ45 connector, -40 to 75°C operating temperature	141,00 €
NE-4110S	Device server module for RS-232 devices, supports 10/100BaseT(x) with RJ45 connector	97,00 €
NE-4110S-P	Programmable device server module for RS-232 devices, supports 10/100BaseT(x) with RJ45 connector	109,00 €
NE-4110S-T	Device server module for RS-232 devices, supports 10/100BaseT(X) with RJ45 connector, -40 to 75°C operating temperature	129,00 €
NE-4110-ST	Starter Kit for NE-4110S, NE-4110A, NE-4110S-P, NE-4110A-P	166,00 €
NE-4120A	Device server module for RS-422/485 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header	116,00 €
NE-4120A-P	Programmable device server module for RS-422/485 devices, supports 10/100BaseT(x) with 5-pin Ethernet pin header	116,00 €
NE-4120A-T	Device server module for RS-422/485 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header, -40 to 75°C operating temperature	176,00 €
NE-4120S	Device server module for RS-232 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header	104,00 €
NE-4120S-P	Programmable device server module for RS-232 devices, supports 10/100BaseT(x) with 5-pin Ethernet pin header	104,00 €

NE-4120S-T	Device server module for RS-232 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header, -40 to 75°C operating temperature	163,00 €
NE-4120-ST	Starter Kit for NE-4120S, NE-4120A, NE-4120S-P, NE-4120A-P	173,00 €
NM-FX01-M-SC	1 100BaseFX port, multi-mode, SC connector	173,00 €
NM-FX01-M-SC-T	1 100BaseFX port, multi-mode, SC connector, -40 to 75°C operating temperature	238,00 €
NM-FX01-S-SC	1 100BaseFX port, single-mode, SC connector	216,00 €
NM-FX01-S-SC-T	1 100BaseFX port, single-mode, SC connector, -40 to 75°C operating temperature	291,00 €
NM-FX02-M-SC	2 100BaseFX ports, multi-mode, SC connector	366,00 €
NM-FX02-M-SC-G2	2nd Gen 2 100BaseFX port multi-mode SC connector, -10 to 60°C operating temperature	383,00 €
NM-FX02-M-SC-G2-T	2nd Gen 2 100BaseFX port multi-mode SC connector, -40 to 75°C operating temperature	462,00 €
NM-FX02-M-SC-T	2 100BaseFX ports, multi-mode, SC connector, -40 to 75°C operating temperature	499,00 €
NM-FX02-S-SC	2 100BaseFX ports, single-mode, SC connector	437,00 €
NM-FX02-S-SC-G2	2nd Gen 2 100BaseFX port single-mode SC connector, -10 to 60°C operating temperature	455,00 €
NM-FX02-S-SC-G2-T	2nd Gen 2 100BaseFX port single-mode SC connector, -40 to 75°C operating temperature	557,00 €
NM-FX02-S-SC-T	2 100BaseFX ports, single-mode, SC connector, -40 to 75°C operating temperature	600,00 €
NM-SFP02-G2-T	2nd Gen 2 1000BaseSFP port connector, -40 to 75°C operating temperature	317,00 €
NM-TX01	1 10/100BaseT(X) port	58,00 €
NM-TX01-T	1 10/100BaseT(X) port, -40 to 75°C operating temperature	77,00 €
NM-TX02	2 10/100BaseT(X) ports	114,00 €
NM-TX02-G2	2nd Gen 2 10/100BaseT(x) port connector, -10 to 60°C operating temperature	143,00 €
NM-TX02-G2-T	2nd Gen 2 10/100BaseT(x) port connector, -40 to 75°C operating temperature	169,00 €
NM-TX02-T	2 10/100BaseT(X) ports, -40 to 75°C operating temperature	156,00 €
NP21101	DB25 male to DB9 female cable for RS-232 transmission, 30 cm	15,00 €
NP21102	DB25 male to DB9 male cable for RS-232 transmission, 30 cm	15,00 €
NP21103	DB25 male to terminal block for RS-422/485 transmission	11,00 €
NPort 5110	1-port RS-232 device server, 0 to 55°C operating temperature	208,00 €
NPort 5110 w/o adapter	1-port RS-232 device server without adapter, 0 to 55°C operating temperature	198,00 €
NPort 5110A	1-port RS-232 device server, 0 to 60°C operating temperature	212,00 €
NPort 5110A w/o ADP	1-port RS-232 serial device servers with serial surge protection, without adapter (Custom)	207,00 €
NPort 5110A-T	1-port RS-232 device server with surge protection, -40 to 75°C operating temperature	327,00 €
NPort 5110-T	1-port RS-232 device server, -40 to 75°C operating temperature	305,00 €
NPort 5130	1-port RS-422/485 device server, 0 to 55°C operating temperature	227,00 €
NPort 5130A	1-port RS-422/485 device server, 0 to 60°C operating temperature	246,00 €
NPort 5130A-T	1-port RS-422/485 device server, -40 to 75°C operating temperature	327,00 €
NPort 5150	1-port RS-232/422/485 device server, 0 to 55°C operating temperature	238,00 €
NPort 5150 w/o adapter	1-port RS-232/422/485 device server without adapter, 0 to 55°C operating temperature	231,00 €
NPort 5150A	1-port RS-232/422/485 device server, 0 to 60°C operating temperature	258,00 €
NPort 5150AI-M12	1-port RS-232/422/485 device server with M12 connector, M12 power input, -25 to 55°C operating temperature	1.149,00 €
NPort 5150AI-M12-CT	1-port RS-232/422/485 device server with M12 connector, M12 power input, -25 to 55°C operating temperature, conformal coating	1.489,00 €
NPort 5150AI-M12-CT-T	1-port RS-232/422/485 device server with M12 connector, M12 power input, -40 to 75°C operating temperature, conformal coating	1.674,00 €

NPort 5150AI-M12-T	1-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -40 to 75°C operating temperature	1.437,00 €
NPort 5150A-T	1-port RS-232/422/485 device server, -40 to 75°C operating temperature	338,00 €
NPort 5210	2-port RS-232 device server, 0 to 55°C operating temperature	319,00 €
NPort 5210 w/ adapter	2-port RS-232 device server with adapter, 0 to 55°C operating temperature	339,00 €
NPort 5210A	2-port RS-232 device server, 0 to 60°C operating temperature	343,00 €
NPort 5210A-T	2-port RS-232 device server with surge protection, -40 to 75°C operating temperature	431,00 €
NPort 5210-T	2-port RS-232 device server, -40 to 75°C operating temperature	455,00 €
NPort 5230	2-port device server with 1 RS-232 port and 1 RS-422/485 port, 0 to 55°C operating temperature	319,00 €
NPort 5230 w/ adapter	2-port device server with 1 RS-232 port and 1 RS-422/485 port with adapter, 0 to 55°C operating temperature	339,00 €
NPort 5230A	2-port RS-422/485 device server, 0 to 60°C operating temperature	343,00 €
NPort 5230A-T	2-port RS-422/485 device server, -40 to 75°C operating temperature	431,00 €
NPort 5230-T	2-port device server with 1 RS-232 port and 1 RS-422/485 port, -40 to 75°C operating temperature	445,00 €
NPort 5232	2-port RS-422/485 device server, 0 to 55°C operating temperature	319,00 €
NPort 5232 w/ adapter	2-port RS-422/485 device server with adapter, 0 to 55°C operating temperature	343,00 €
NPort 5232I	2-port RS-422/485 device server with 2 kV optical isolation, 0 to 55°C operating temperature	431,00 €
NPort 5232I w/ adapter	2-port RS-422/485 device server with 2 kV optical isolation, with adapter, -40 to 75°C operating temperature	440,00 €
NPort 5232I-T	2-port RS-422/485 device server with 2 kV optical isolation, -40 to 75°C operating temperature	548,00 €
NPort 5232-T	2-port RS-422/485 device server, -40 to 75°C operating temperature	469,00 €
NPort 5250A	2-port RS-232/422/485 device server, 0 to 60°C operating temperature	384,00 €
NPort 5250A w/o ADP	2-port RS-232/422/485 device server without adapter, 0 to 60°C operating temperature	369,00 €
NPort 5250AI-M12	2-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature	1.352,00 €
NPort 5250AI-M12-CT	2-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature, conformal coating	1.756,00 €
NPort 5250AI-M12-CT-T	2-port RS-232/422/485 device server with M12 connector, M12 power input, -40 to 75°C operating temperature, conformal coating	2.164,00 €
NPort 5250AI-M12-T	2-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -40 to 75°C operating temperature	1.693,00 €
NPort 5250A-T	2-port RS-232/422/485 device server, -40 to 75°C operating temperature	481,00 €
NPort 5410	4-port RS-232 serial device server	814,00 €
NPort 5410 w/ adapter	4-port RS-232 serial device server with adapter	831,00 €
NPort 5430	4-port RS-422/485 serial device server	931,00 €
NPort 5430 w/ adapter	4-port RS-422/485 serial device server without adapter	940,00 €
NPort 5430I	4-port RS-422/485 serial device server with 2 kV isolation	1.234,00 €
NPort 5430I w/ adapter	4-port RS-422/485 serial device server with 2 kV isolation, with adapter	1.252,00 €
NPort 5450	4-port RS-232/422/485 serial device server	976,00 €
NPort 5450 w/ adapter	4-port RS-232/422/485 serial device server with adapter	1.000,00 €
NPort 5450AI-M12	4-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature	1.828,00 €
NPort 5450AI-M12-CT	4-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature, conformal coating	2.367,00 €

NPort 5450AI-M12-CT-T	4-port RS-232/422/485 device server with M12 connector, M12 power input, -40 to 75°C operating temperature, conformal coating	2.667,00 €
NPort 5450AI-M12-T	4-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -40 to 75°C operating temperature	2.281,00 €
NPort 5450I	4-port RS-232/422/485 device server with 2 kV isolation protection	1.387,00 €
NPort 5450I w/ adapter	4-port RS-232/422/485 device server with 2 kV isolation protection, with adapter	1.401,00 €
NPort 5450I-T	4-port RS-232/422/485 device server with 2 kV isolation protection, -40 to 75°C operating temperature	1.454,00 €
NPort 5450-T	4-port RS-232/422/485 device server, -40 to 75°C operating temperature	1.115,00 €
NPort 5610-16	16-port RS-232 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	1.639,00 €
NPort 5610-16-48V	16-port RS-232 rackmount device server with RJ45 connectors and 48 VDC power input	1.792,00 €
NPort 5610-8	8-port RS-232 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	1.269,00 €
NPort 5610-8-48V	8-port RS-232 rackmount device server with RJ45 connectors and 48 VDC power input	1.386,00 €
NPort 5610-8-DT	8-port RS-232 desktop device server with DB9 male connectors and 48 VDC power input	1.269,00 €
NPort 5610-8-DT w/o adaptor	8-port RS-232 desktop device server with DB9 male connectors and 48 VDC power input, without adapter	1.135,00 €
NPort 5610-8-DT-J	8-port RS-232 desktop device server with RJ45 connectors and 48 VDC power input	1.269,00 €
NPort 5610-8-DT-J w/o adaptor	8-port RS-232 desktop device server with RJ45 connectors and 48 VDC power input, without adapter	1.136,00 €
NPort 5610-8-DT-T	8-port RS-232 desktop device server with DB9 male connectors, -40 to 75°C operating temperature	1.312,00 €
NPort 5630-16	16-port RS-422/485 rackmount device server with RJ45 connectors, 100 to 240 VAC power input	1.708,00 €
NPort 5630-8	8-port RS-422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	1.353,00 €
NPort 5650-16	16-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	1.894,00 €
NPort 5650-16-HV-T	16-port RS-232/422/485 rackmount device server with RJ45 connectors and 88 to 300 VDC power input, -40 to 85°C operating temperature	2.971,00 €
NPort 5650-16-M-SC	16-port RS-232/422/485 rackmount device server with multi-mode fiber (SC connector)	2.385,00 €
NPort 5650-16-S-SC	16-port RS-232/422/485 rackmount device server with single-mode fiber (SC connector)	2.486,00 €
NPort 5650-16-T	16-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input, -40 to 75°C operating temperature	2.569,00 €
NPort 5650-8	8-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	1.623,00 €
NPort 5650-8-DT	8-port RS-232/422/485 desktop device server with DB9 male connectors and 48 VDC power input	1.421,00 €
NPort 5650-8-DT w/o adaptor	8-port RS-232/422/485 desktop device server with DB9 male connectors and 48 VDC power input, without adapter	1.275,00 €
NPort 5650-8-DT-J	8-port RS-232/422/485 desktop device server with RJ45 connectors and 48 VDC power input	1.421,00 €
NPort 5650-8-DT-J w/o adaptor	8-port RS-232/422/485 desktop device server with RJ45 connectors and 48 VDC power input, without adapter	1.275,00 €
NPort 5650-8-DT-T	8-port RS-232/422/485 desktop device server with DB9 male connectors, -40 to 75°C operating temperature	1.994,00 €

NPort 5650-8-HV-T	8-port RS-232/422/485 rackmount device server with RJ45 connectors and 88 to 300 VDC power input, -40 to 85°C operating temperature	2.434,00 €
NPort 5650-8-M-SC	8-port RS-232/422/485 rackmount device server with multi-mode fiber (SC connector)	1.910,00 €
NPort 5650-8-S-SC	8-port RS-232/422/485 rackmount device server with single-mode fiber (SC connector)	2.009,00 €
NPort 5650-8-T	8-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input, -40 to 75°C operating temperature	2.030,00 €
NPort 5650I-8-DT	8-port RS-232/422/485 desktop device server with DB9 male connectors, 48 VDC power input, and 2 kV optical isolation	2.163,00 €
NPort 5650I-8-DT w/o adaptor	8-port RS-232/422/485 desktop device server with DB9 male connectors, 48 VDC power input, and 2 kV optical isolation, without adapter	1.968,00 €
NPort 5650I-8-DT-T	8-port RS-232/422/485 desktop device server with DB9 male connectors and 2 KV isolation, -40 to 75°C operating temperature	3.108,00 €
NPort 6150	1-port RS-232/422/485 secure device server	421,00 €
NPort 6150-G2	2nd Gen 1-port RS-232/422/485 secure device server	459,00 €
NPort 6150-G2-T	2nd Gen 1-port RS-232/422/485 secure device server, -40 to 75°C operating temperature	576,00 €
NPort 6150-T	1-port RS-232/422/485 secure device server, -40 to 75°C operating temperature	511,00 €
NPort 6250	2-port RS-232/422/485 to Ethernet secure device server	723,00 €
NPort 6250-G2	2nd Gen 2-port RS-232/422/485 to Ethernet secure device server	734,00 €
NPort 6250-G2-T	2nd Gen 2-port RS-232/422/485 to Ethernet secure device server, -40 to 75°C operating temperature	912,00 €
NPort 6250-M-SC	2-port RS-232/422/485 to multi-mode fiber (SC connector) secure device server	899,00 €
NPort 6250-M-SC-T	2-port RS-232/422/485 to multi-mode fiber (SC connector) secure device server, -40 to 75°C operating temperature	915,00 €
NPort 6250-S-SC	2-port RS-232/422/485 to single-mode fiber (SC connector) secure device server	1.008,00 €
NPort 6250-S-SC-T	2-port RS-232/422/485 to single-mode fiber (SC connector) secure device server, -40 to 75°C operating temperature	1.032,00 €
NPort 6250-T	2-port RS-232/422/485 to Ethernet secure device server, -40 to 75°C operating temperature	814,00 €
NPort 6450	4-port RS-232/422/485 to Ethernet secure serial port server	931,00 €
NPort 6450-2M-SC-G2-T	2nd Gen 4-port RS-232/422/485 secure terminal server with 2 multi-mode SC 100M LAN ports, -40 to 75°C operating temperature	1.735,00 €
NPort 6450-2S-SC-G2-T	2nd Gen 4-port RS-232/422/485 secure terminal server with 2 single-mode SC 100M LAN ports, -40 to 75°C operating temperature	1.832,00 €
NPort 6450-2TX-G2	2nd Gen 4-port RS-232/422/485 secure terminal server with 2 RJ45 100M LAN ports, -10 to 60°C operating temperature	1.123,00 €
NPort 6450-2TX-G2-T	2nd Gen 4-port RS-232/422/485 secure terminal server with 2 RJ45 100M LAN ports, -40 to 75°C operating temperature	1.391,00 €
NPort 6450-G2	2nd Gen 4-port RS-232/422/485 secure terminal server, -10 to 60°C operating temperature	995,00 €
NPort 6450-G2-T	2nd Gen 4-port RS-232/422/485 secure terminal server, -40 to 75°C operating temperature	1.245,00 €
NPort 6450-T	4-port secure device server, RS-232/422/485 to Ethernet, -40 to 75°C operating temperature	1.139,00 €
NPort 6610-16	16-port RS-232 to Ethernet secure device server, 100 to 240 VAC input	2.216,00 €
NPort 6610-16-2AC-G2	2nd Gen dual-LAN dual AC power 16-port RS-232 secure terminal server, -10 to 60°C operating temperature	2.343,00 €
NPort 6610-16-48V	16-port RS-232 to Ethernet secure device server, ±48 VDC input	2.245,00 €
NPort 6610-16-G2	2nd Gen dual-LAN 16-port RS-232 secure terminal server, -10 to 60°C operating temperature	2.186,00 €
NPort 6610-32	32-port RS-232 to Ethernet secure device server, 100 to 240 VAC input	2.759,00 €

NPort 6610-32-2AC-G2	2nd Gen dual-LAN dual AC power 32-port RS-232 secure terminal server, -10 to 60°C operating temperature	3.228,00 €
NPort 6610-32-48V	32-port RS-232 to Ethernet secure device server, ±48 VDC input	3.036,00 €
NPort 6610-32-G2	2nd Gen dual-LAN 32-port RS-232 secure terminal server, -10 to 60°C operating temperature	3.070,00 €
NPort 6610-8	8-port RS-232 to Ethernet secure device server, 100 to 240 VAC input	1.691,00 €
NPort 6610-8-2AC-G2	2nd Gen dual-LAN dual AC power 8-port RS-232 secure terminal server, -10 to 60°C operating temperature	2.006,00 €
NPort 6610-8-48V	8-port RS-232 to Ethernet secure device server, ±48 VDC input	1.776,00 €
NPort 6610-8-G2	2nd Gen dual-LAN 8-port RS-232 secure terminal server, -10 to 60°C operating temperature	1.849,00 €
NPort 6650-16	16-port RS-232/422/485 to Ethernet secure terminal server, 100 to 240 VAC input	2.009,00 €
NPort 6650-16-2AC-G2	2nd Gen dual-LAN dual AC power 16-port RS-232/422/485 secure terminal server, -10 to 60°C operating temperature	2.486,00 €
NPort 6650-16-2AC-G2-T	2nd Gen dual-LAN dual AC power 16-port RS-232/422/485 secure terminal server, -40 to 75°C operating temperature	2.730,00 €
NPort 6650-16-48V	16-port RS-232/422/485 to Ethernet secure terminal server, ±48 VDC input	2.010,00 €
NPort 6650-16-48V-G2	2nd Gen dual-LAN 16-port RS-232/422/485 secure terminal server, ±48 VDC power input, -10 to 60°C operating temperature	2.142,00 €
NPort 6650-16-G2	2nd Gen dual-LAN 16-port RS-232/422/485 secure terminal server, -10 to 60°C operating temperature	2.328,00 €
NPort 6650-16-G2-T	2nd Gen dual-LAN 16-port RS-232/422/485 secure terminal server, -40 to 75°C operating temperature	2.508,00 €
NPort 6650-16-HV-T	16-port RS-232/422/485 to Ethernet secure terminal server, 88 to 300 VDC power input, -40 to 85°C operating temperature	2.784,00 €
NPort 6650-16-T	16-port RS-232/422/485 to Ethernet secure terminal server, -40 to 75°C operating temperature, 100 to 240 VAC input	3.208,00 €
NPort 6650-32	32-port RS-232/422/485 to Ethernet secure terminal server, 100 to 240 VAC input	2.875,00 €
NPort 6650-32-2AC-G2	2nd Gen dual-LAN dual AC power 32-port RS-232/422/485 secure terminal server, -10 to 60°C operating temperature	3.355,00 €
NPort 6650-32-2AC-G2-T	2nd Gen dual-LAN dual AC power 32-port RS-232/422/485 secure terminal server, -40 to 75°C operating temperature	4.052,00 €
NPort 6650-32-48V	32-port RS-232/422/485 to Ethernet secure terminal server, ±48 VDC input	3.024,00 €
NPort 6650-32-48V-G2	2nd Gen dual-LAN 32-port RS-232/422/485 secure terminal server, ±48 VDC power input, -10 to 60°C operating temperature	3.222,00 €
NPort 6650-32-G2	2nd Gen dual-LAN 32-port RS-232/422/485 secure terminal server, -10 to 60°C operating temperature	3.197,00 €
NPort 6650-32-HV-T	32-port RS-232/422/485 to Ethernet secure terminal server, 88 to 300 VDC power input, -40 to 85°C operating temperature	3.309,00 €
NPort 6650-8	8-port RS-232/422/485 to Ethernet secure terminal server, 100 to 240 VAC input	1.978,00 €
NPort 6650-8-2AC-G2	2nd Gen dual-LAN dual AC power 8-port RS-232/422/485 secure terminal server, -10 to 60°C operating temperature	2.089,00 €
NPort 6650-8-2AC-G2-T	2nd Gen dual-LAN dual AC power 8-port RS-232/422/485 secure terminal server, -40 to 75°C operating temperature	2.385,00 €
NPort 6650-8-48V	8-port RS-232/422/485 to Ethernet secure terminal server, ±48 VDC input	1.825,00 €
NPort 6650-8-48V-G2	2nd Gen dual-LAN 8-port RS-232/422/485 secure terminal server, ±48 VDC power input, -10 to 60°C operating temperature	1.934,00 €
NPort 6650-8-G2	2nd Gen dual-LAN 8-port RS-232/422/485 secure terminal server, -10 to 60°C operating temperature	1.931,00 €
NPort 6650-8-G2-T	2nd Gen dual-LAN 8-port RS-232/422/485 secure terminal server, -40 to 75°C operating temperature	2.164,00 €

NPort 6650-8-HV-T	8-port RS-232/422/485 to Ethernet secure terminal server, 88 to 300 VDC power input, -40 to 85°C operating temperature	2.448,00 €
NPort 6650-8-T	8-port RS-232/422/485 to Ethernet secure terminal server, -40 to 75°C operating temperature, 100 to 240 VAC input	2.468,00 €
NPort 6650I-16-2AC-G2	2nd Gen dual-LAN dual AC power 16-port RS-232/422/485 secure terminal server, 2 kV isolation, -10 to 60°C operating temperature	3.746,00 €
NPort 6650I-16-2AC-G2-T	2nd Gen dual-LAN dual AC power 16-port RS-232/422/485 secure terminal server, 2 kV isolation, -40 to 75°C operating temperature	4.008,00 €
NPort 6650I-16-G2	2nd Gen dual-LAN 16-port RS-232/422/485 secure terminal server, 2 kV isolation, -10 to 60°C operating temperature	3.587,00 €
NPort 6650I-16-G2-T	2nd Gen dual-LAN 16-port RS-232/422/485 secure terminal server, 2 kV isolation, -40 to 75°C operating temperature	4.020,00 €
NPort 6650I-8-2AC-G2	2nd Gen dual-LAN dual AC power 8-port RS-232/422/485 secure terminal server, 2 kV isolation, -10 to 60°C operating temperature	2.667,00 €
NPort 6650I-8-2AC-G2-T	2nd Gen dual-LAN dual AC power 8-port RS-232/422/485 secure terminal server, 2kV isolation, -40 to 75°C operating temperature	2.989,00 €
NPort 6650I-8-G2	2nd Gen dual-LAN 8-port RS-232/422/485 secure terminal server, 2 kV isolation, -10 to 60°C operating temperature	2.508,00 €
NPort 6650I-8-G2-T	2nd Gen dual-LAN 8-port RS-232/422/485 secure terminal server, 2 kV isolation, -40 to 75°C operating temperature	2.812,00 €
NPort IA-5150	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), 0 to 55°C operating temperature	455,00 €
NPort IA5150A	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature	494,00 €
NPort IA5150AI	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature, 2 kV isolation	636,00 €
NPort IA5150A-IEEX	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEX, 0 to 60°C operating temperature	563,00 €
NPort IA5150AI-IEEX	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEX, 0 to 60°C operating temperature	714,00 €
NPort IA5150AI-T	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature, 2 kV isolation	806,00 €
NPort IA5150AI-T-IEEX	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEX, -40 to 75°C operating temperature	899,00 €
NPort IA5150A-T	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature	615,00 €
NPort IA5150A-T-IEEX	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEX, -40 to 75°C operating temperature	714,00 €
NPort IA5150-G2	2nd Gen 1-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, -10 to 60°C operating temperature	487,00 €
NPort IA5150-G2-T	2nd Gen 1-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, -40 to 75°C operating temperature	603,00 €
NPort IA-5150I	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP) and 2 KV optical isolation, 0 to 55°C operating temperature	590,00 €
NPort IA5150I-G2	2nd Gen 1-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 kV isolation, -10 to 60°C operating temperature	617,00 €
NPort IA5150I-G2-T	2nd Gen 1-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 kV isolation, -40 to 75°C operating temperature	781,00 €

NPort IA-5150I-M-SC	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 55°C operating temperature	847,00 €
NPort IA-5150I-M-SC-T	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	1.099,00 €
NPort IA-5150I-S-SC	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 55°C operating temperature	940,00 €
NPort IA-5150I-S-SC-T	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	1.217,00 €
NPort IA-5150I-T	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP) and 2 kV optical isolation, -40 to 75°C operating temperature	754,00 €
NPort IA-5150-M-SC	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors), 0 to 55°C operating temperature	636,00 €
NPort IA5150-M-SC-G2	2nd Gen 1-port RS-232/422/485 DIN-rail serial device server with 1 RJ45 port, 1 multi-SC port, -10 to 60°C operating temperature	631,00 €
NPort IA5150-M-SC-G2-T	2nd Gen 1-port RS-232/422/485 DIN-rail serial device server with 1 RJ45 port, 1 multi-SC port, -40 to 75°C operating temperature	823,00 €
NPort IA-5150-M-SC-T	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors), -40 to 75°C operating temperature	892,00 €
NPort IA-5150-M-ST	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (ST connectors), 0 to 55°C operating temperature	636,00 €
NPort IA-5150-M-ST-T	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (ST connectors), -40 to 75°C operating temperature	890,00 €
NPort IA5150-SFP-G2	2nd Gen 1-port RS-232/422/485 DIN-rail serial device server with 1 RJ45 port, 1 SFP port, -10 to 60°C operating temperature	576,00 €
NPort IA5150-SFP-G2-T	2nd Gen 1-port RS-232/422/485 DIN-rail serial device server with 1 RJ45 port, 1 SFP port, -40 to 75°C operating temperature	802,00 €
NPort IA-5150-S-SC	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors), 0 to 55°C operating temperature	714,00 €
NPort IA5150-S-SC-G2	2nd Gen 1-port RS-232/422/485 DIN-rail serial device server with 1 RJ45 port, 1 single-SC port, -10 to 60°C operating temperature	713,00 €
NPort IA5150-S-SC-G2-T	2nd Gen 1-port RS-232/422/485 DIN-rail serial device server with 1 RJ45 port, 1 single-SC port, -40 to 75°C operating temperature	932,00 €
NPort IA-5150-S-SC-T	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors), -40 to 75°C operating temperature	1.016,00 €
NPort IA-5150-T	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), -40 to 75°C operating temperature	606,00 €
NPort IA-5250	2-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), 0 to 55°C operating temperature	502,00 €
NPort IA5250A	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature	548,00 €
NPort IA5250AI	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature, 2 kV isolation	778,00 €
NPort IA5250A-IEEX	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEx, 0 to 60°C operating temperature	630,00 €
NPort IA5250AI-IEEX	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEx, 0 to 60°C operating temperature	794,00 €
NPort IA5250AI-T	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature, 2 kV isolation	962,00 €

NPort IA5250AI-T-IEX	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEx, -40 to 75°C operating temperature	1.086,00 €
NPort IA5250A-T	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature	677,00 €
NPort IA5250A-T-IEX	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEx, -40 to 75°C operating temperature	786,00 €
NPort IA5250-G2	2nd Gen 2-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, -10 to 60°C operating temperature	583,00 €
NPort IA5250-G2-T	2nd Gen 2-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, -40 to 75°C operating temperature	727,00 €
NPort IA-5250I	2-port RS-232/422/485 device server with 2 100BaseT(X) ports (RJ45 connectors, single IP), 2 KV optical isolation, 0 to 55°C operating temperature	680,00 €
NPort IA5250I-G2	2nd Gen 2-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 kV isolation, -10 to 60°C operating temperature	754,00 €
NPort IA5250I-G2-T	2nd Gen 2-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 kV isolation, -40 to 75°C operating temperature	939,00 €
NPort IA-5250I-T	2-port RS-232/422/485 device server with 2 100BaseT(X) ports (RJ45 connectors, single IP), 2 KV optical isolation, -40 to 75°C operating temperature	872,00 €
NPort IA5250I-TB-G2	2nd Gen 2-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 5-pin terminal blocks, 2 kV isolation, -10 to 60°C operating temperature	754,00 €
NPort IA5250I-TB-G2-T	2nd Gen 2-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 5-pin terminal blocks, 2 kV isolation, -40 to 75°C operating temperature	939,00 €
NPort IA-5250-T	2-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), -40 to 75°C operating temperature	671,00 €
NPort IA5250-TB-G2	2nd Gen 2-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 5-pin terminal blocks, -10 to 60°C operating temperature	583,00 €
NPort IA5250-TB-G2-T	2nd Gen 2-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 5-pin terminal blocks, -40 to 75°C operating temperature	727,00 €
NPort IA5450A	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature	924,00 €
NPort IA5450AI	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature, 2 kV isolation protection	1.301,00 €
NPort IA5450AI-T	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature, 2 kV isolation protection	1.641,00 €
NPort IA5450A-T	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature	1.151,00 €
NPort IA5450-G2	2nd Gen 4-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, -10 to 60°C operating temperature	966,00 €
NPort IA5450-G2-T	2nd Gen 4-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, -40 to 75°C operating temperature	1.206,00 €
NPort IA5450I-G2	2nd Gen 4-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 kV isolation, -10 to 60°C operating temperature	1.254,00 €
NPort IA5450I-G2-T	2nd Gen 4-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 kV isolation, -40 to 75°C operating temperature	1.556,00 €
NPort IA5450I-TB-G2	2nd Gen 4-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 5-pin terminal blocks, 2 kV isolation, -10 to 60°C operating temperature	1.254,00 €
NPort IA5450I-TB-G2-T	2nd Gen 4-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 5-pin terminal blocks, 2 kV isolation, -40 to 75°C operating temperature	1.556,00 €

NPort IA5450-TB-G2	2nd Gen 4-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, -10 to 60°C operating temperature	966,00 €
NPort IA5450-TB-G2-T	2nd Gen 4-port RS-232/422/485 DIN-rail serial device server with 2 RJ45 ports, 2 5-pin terminal blocks, -40 to 75°C operating temperature	1.206,00 €
NPort P5150A	1-port RS-232/422/485 PoE device server, 0 to 60°C operating temperature	420,00 €
NPort P5150A-T	1-port RS-232/422/485 PoE device server, -40 to 75°C operating temperature	525,00 €
NPort S8455I	4 RS-232/422/485 ports, 5 10/100BaseT(X) ports, 12 to 48 VDC, 2 kV isolation protection, 0 to 60°C operating temperature	1.776,00 €
NPort S8455I-MM-SC	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, 0 to 60°C operating temperature	2.245,00 €
NPort S8455I-MM-SC-T	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, -40 to 75°C operating temperature	2.445,00 €
NPort S8455I-SS-SC	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, 0 to 60°C operating temperature	2.717,00 €
NPort S8455I-SS-SC-T	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, -40 to 75°C operating temperature	3.138,00 €
NPort S8455I-T	4 RS-232/422/485 ports, 5 10/100BaseT(X) ports, 12 to 48 VDC, 2 kV isolation protection, -40 to 75°C operating temperature	2.193,00 €
NPort S9450I-2M-SC-HV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	3.255,00 €
NPort S9450I-2M-SC-WV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connectors, 24/48 VDC, -40 to 85°C operating temperature	3.255,00 €
NPort S9450I-2M-ST-HV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with ST connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	3.255,00 €
NPort S9450I-2M-ST-WV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with ST connectors, 24/48 VDC, -40 to 85°C operating temperature	3.255,00 €
NPort S9450I-2S-SC-HV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	3.899,00 €
NPort S9450I-2S-SC-WV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connectors, 24/48 VDC, -40 to 85°C operating temperature	3.899,00 €
NPort S9450I-2S-ST-HV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with ST connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	3.899,00 €
NPort S9450I-2S-ST-WV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with ST connectors, 24/48 VDC, -40 to 85°C operating temperature	3.899,00 €
NPort S9450I-HV-T	4-port RS-232/422/485 rugged device server, 5 10/100BaseT(X) ports, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	2.432,00 €
NPort S9450I-WV-T	4-port RS-232/422/485 rugged device server, 5 10/100BaseT(X) ports, 24/48 VDC, -40 to 85°C operating temperature	2.432,00 €
NPort S9650I-16-2HV-E-T	16-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	5.046,00 €
NPort S9650I-16-2HV-MS-SC-T	16-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector fiber module	5.569,00 €
NPort S9650I-16-2HV-SS-SC-T	16-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector fiber module	6.549,00 €

NPort S9650I-16B-2HV-IRIG-T	16-port RS-232/422/485 rugged device server with IRIG-B signal output on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with IRIG-B BNC module	6.008,00 €
NPort S9650I-16F-2HV-E-T	16-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	5.485,00 €
NPort S9650I-16F-2HV-MS-C-T	16-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector fiber module	6.008,00 €
NPort S9650I-16F-2HV-SS-C-T	16-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector fiber module	7.071,00 €
NPort S9650I-8-2HV-E-T	8-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	4.253,00 €
NPort S9650I-8-2HV-MS-C-T	8-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector fiber module	4.691,00 €
NPort S9650I-8-2HV-SS-C-T	8-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector fiber module	5.652,00 €
NPort S9650I-8B-2HV-IRIG-T	8-port RS-232/422/485 rugged device server with IRIG-B signal output on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with IRIG-B BNC module	4.971,00 €
NPort S9650I-8F-2HV-E-T	8-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	4.591,00 €
NPort S9650I-8F-2HV-MS-C-T	8-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector fiber module	5.130,00 €
NPort S9650I-8F-2HV-SS-C-T	8-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector fiber module	5.844,00 €
NPort W2150A-W4-CN	1-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN CN band, CN plug, 12 to 48 VDC, 0 to 55°C operating temperature	514,00 €
NPort W2150A-W4-EU	1-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, EU plug, 12 to 48 VDC, 0 to 55°C operating temperature	514,00 €
NPort W2150A-W4-T-CN	1-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN CN band, 12 to 48 VDC, -40 to 75°C operating temperature	794,00 €
NPort W2150A-W4-T-EU	1-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, 12 to 48 VDC, -40 to 75°C operating temperature	794,00 €
NPort W2150A-W4-T-US	1-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN US band, 12 to 48 VDC, -40 to 75°C operating temperature	794,00 €
NPort W2150A-W4-US	1-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN US band, US plug, 12 to 48 VDC, 0 to 55°C operating temperature	514,00 €
NPort W2250A-W4-EU	2-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, EU plug. 12 to 48 VDC, 0 to 55°C operating temperature	630,00 €
NPort W2250A-W4-T-EU	2-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, 12 to 48 VDC, -40 to 75°C operating temperature	879,00 €

OBU-102-SS-LC	2-channel optical fiber bypass unit with 4 single-mode ports, LC, -20 to 70°C operating temperature	1.926,00 €
OBU-102-SS-SC	2-channel optical fiber bypass unit with 4 single-mode ports, SC, -20 to 70°C operating temperature	1.926,00 €
OBU-102-SS-ST	2-channel optical fiber bypass unit with 4 single-mode ports, ST, -20 to 70°C operating temperature	1.926,00 €
OnCell 3120-LTE-1-AU	Industrial LTE Cat. 1 cellular gateway, B1/B3/B5/B8/B9/B18/B19/B26/B28, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, 0 to 55°C operating temperature	962,00 €
OnCell 3120-LTE-1-AU-T	Industrial LTE Cat. 1 cellular gateway, B1/B3/B5/B8/B9/B18/B19/B26/B28, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, -30 to 70°C operating temperature	1.031,00 €
OnCell 3120-LTE-1-EU	Industrial LTE Cat. 1 cellular gateway, B1/B3/B7/B8/B20/B28A, 1 RS-232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, 0 to 55°C operating temperature	962,00 €
OnCell 3120-LTE-1-EU-T	Industrial LTE Cat. 1 cellular gateway, B1/B3/B7/B8/B20/B28A, 1 RS-232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, -30 to 70°C operating temperature	1.031,00 €
OnCell 3120-LTE-1-US	Industrial LTE Cat. 1 cellular gateway, B2/B4/B5/B12/B13/B14/B66/B71, 1 RS-232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, 0 to 55°C operating temperature	962,00 €
OnCell 3120-LTE-1-US-T	Industrial LTE Cat. 1 cellular gateway, B2/B4/B5/B12/B13/B14/B66/B71, 1 RS-232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, -30 to 70°C operating temperature	1.031,00 €
OnCell G4302-LTE4-AU	Industrial LTE Cat. 4 cellular secure router, B1/B3/B5/B7/B8/B28, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	1.847,00 €
OnCell G4302-LTE4-AU-T	Industrial LTE Cat. 4 cellular secure router, B1/B3/B5/B7/B8/B28, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	1.991,00 €
OnCell G4302-LTE4-EU	Industrial LTE Cat. 4 cellular secure router, B1/B3/B7/B8/B20/B28, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	1.847,00 €
OnCell G4302-LTE4-EU-T	Industrial LTE Cat. 4 cellular secure router, B1/B3/B7/B8/B20/B28, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	1.991,00 €
OnCell G4302-LTE4-JP	Industrial LTE Cat. 4 cellular secure router, B1/B3/B8/B11/B18/B19/B21, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	1.847,00 €
OnCell G4302-LTE4-JP-T	Industrial LTE Cat. 4 cellular secure router, B1/B3/B8/B11/B18/B19/B21, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	1.991,00 €
OnCell G4302-LTE4-US	Industrial LTE Cat. 4 cellular secure router, B2/B4/B5/B12/B13/B14/B17/B66, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	1.847,00 €
OnCell G4302-LTE4-US-T	Industrial LTE Cat. 4 cellular secure router, B2/B4/B5/B12/B13/B14/B17/B66, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	1.991,00 €
OnCell G4308-LTE4-GL	Industrial LTE Cat. 4 cellular secure router, global band support, 8 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	1.991,00 €
OnCell G4308-LTE4-GL-T	Industrial LTE Cat. 4 cellular secure router, global band support, 8 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	2.136,00 €
OPT 8A	M62 to 8 x DB25 female connection box with DB62 male to DB62 female serial cable	144,00 €
OPT 8A+	VHDCI 68 to 8 x DB25 female connection box	150,00 €
OPT 8B	M62 to 8 x DB25 male connection box with DB62 male to DB62 female cable, 1.5 m	144,00 €
OPT 8B+	VHDCI 68 to 8 x DB25 male connection box	150,00 €
OPT 8S	M62 to 8 x DB25 female connection box with surge protection and a DB62 male to DB62 male cable, 1.5 m	307,00 €
OPT 8S+	VHDCI 68 to 8 x DB25 female connection box with surge protection	307,00 €
OPT8-M9	M62 to 8 x DB9 male connection box, DB62 male to DB62 female cable, 1.5 m	156,00 €
OPT8-M9+	VHDCI 68 to 8 x DB9 male connection box	184,00 €
OPT8-RJ45	M62 to 8 x RJ45 (8-pin) connection box, 30 cm	139,00 €
OPT8-RJ45+	VHDCI 68 to 8 x RJ45 (8-pin) connection box	220,00 €
PK-DC2DOF	Pole mounting kit for outdoor AWK Series access points	62,00 €

PK-DC2DOF-02	Pole mounting kit for outdoor AWK Series access points, supports pole diameters 2" to 6"	70,00 €
Plate-1	Chassis converter bracket accessory package, 9 brackets, 9 screws (FMS M3 X 6 mm)	123,00 €
PM-7500-2GTXSFP	Gigabit Ethernet module with 2 100/1000BaseSFP slots or 2 100/1000BaseT(X) ports, compliant with IEC 61850-3, -40 to 85°C operating temperature	382,00 €
PM-7500-2MSC	Fast Ethernet module with 2 100BaseFX multi-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	558,00 €
PM-7500-2MST	Fast Ethernet module with 2 100BaseFX multi-mode ports with ST connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	558,00 €
PM-7500-2SSC	Fast Ethernet module with 2 100BaseFX single-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	838,00 €
PM-7500-4GTXSFP	Gigabit Ethernet module with 4 100/1000BaseSFP slots or 4 100/1000BaseT(X) ports, compliant with IEC 61850-3, -40 to 85°C operating temperature	761,00 €
PM-7500-4MSC	Fast Ethernet module with 4 100BaseFX multi-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	962,00 €
PM-7500-4MST	Fast Ethernet module with 4 100BaseFX multi-mode ports with ST connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	962,00 €
PM-7500-4SSC	Fast Ethernet module with 4 100BaseFX single-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	1.572,00 €
POS-104UL w/o Cable	4-port RS-232 low-profile Universal PCI board with serial port power, 0 to 55°C operating temperature, without cable	179,00 €
POS-104UL-DB9M	4-port RS-232 low-profile Universal PCI board with serial port power, 0 to 55°C operating temperature (DB9 male cable included)	196,00 €
POS-104UL-T	4-port RS-232 low-profile Universal PCI board with serial port power, -40 to 85°C operating temperature	226,00 €
PT-508-MM-LC-24	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with LC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.010,00 €
PT-508-MM-LC-48	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with LC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.010,00 €
PT-508-MM-LC-HV	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with LC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	1.960,00 €
PT-508-MM-SC-24	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with SC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.010,00 €
PT-508-MM-SC-48	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with SC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.010,00 €
PT-508-MM-SC-HV	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with SC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	1.960,00 €
PT-508-MM-ST-24	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with ST connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.010,00 €
PT-508-MM-ST-48	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with ST connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.010,00 €
PT-508-MM-ST-HV	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with ST connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	1.960,00 €
PT-508-SS-LC-24	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with LC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.145,00 €

PT-508-SS-LC-48	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with LC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.145,00 €
PT-508-SS-LC-HV	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with LC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	2.097,00 €
PT-508-SS-SC-24	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with SC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.399,00 €
PT-508-SS-SC-48	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with SC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.399,00 €
PT-508-SS-SC-HV	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with SC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	2.349,00 €
PT-510-3S-SC-24	IEC 61850-3 managed DIN-rail Ethernet switch, with 7 10/100BaseT(X) ports and 3 100BaseFX single-mode ports with SC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.654,00 €
PT-510-3S-SC-48	IEC 61850-3 managed DIN-rail Ethernet switch, with 7 10/100BaseT(X) ports and 3 100BaseFX single-mode ports with SC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.654,00 €
PT-510-3S-SC-HV	IEC 61850-3 managed DIN-rail Ethernet switch, with 7 10/100BaseT(X) ports and 3 100BaseFX single-mode ports with SC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	2.654,00 €
PT-510-4M-ST-24	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 4 100BaseFX multi-mode ports with ST connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.388,00 €
PT-510-4M-ST-48	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 4 100BaseFX multi-mode ports with ST connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.388,00 €
PT-510-4M-ST-HV	IEC 61850-3 managed DIN-rail Ethernet switch, with 6 10/100BaseT(X) ports and 4 100BaseFX multi-mode ports with ST connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	2.388,00 €
PT-510-MM-LC-24	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with LC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.094,00 €
PT-510-MM-LC-48	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with LC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.094,00 €
PT-510-MM-LC-HV	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with LC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	2.094,00 €
PT-510-MM-SC-24	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with SC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.094,00 €
PT-510-MM-SC-48	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with SC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.094,00 €
PT-510-MM-SC-HV	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with SC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	2.094,00 €
PT-510-MM-ST-24	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with ST connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.094,00 €

PT-510-MM-ST-48	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with ST connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.094,00 €
PT-510-MM-ST-HV	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX multi-mode ports with ST connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	2.094,00 €
PT-510-SS-LC-24	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with LC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.233,00 €
PT-510-SS-LC-48	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with LC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.233,00 €
PT-510-SS-LC-HV	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with LC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	2.233,00 €
PT-510-SS-SC-24	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with SC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	2.498,00 €
PT-510-SS-SC-48	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with SC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	2.498,00 €
PT-510-SS-SC-HV	IEC 61850-3 managed DIN-rail Ethernet switch, with 8 10/100BaseT(X) ports and 2 100BaseFX single-mode ports with SC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	2.498,00 €
PT-7528-12MSC-12TX-4GSFP-HV	IEC 61850-3 managed rackmount Ethernet switch with 12 100BaseFX ports (MSC), 12 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	6.428,00 €
PT-7528-12MSC-12TX-4GSFP-HV-HV	IEC 61850-3 managed rackmount Ethernet switch with 12 100BaseFX ports (MSC), 12 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	6.815,00 €
PT-7528-12MSC-12TX-4GSFP-WV	IEC 61850-3 managed rackmount Ethernet switch with 12 100BaseFX ports (MSC), 12 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	6.428,00 €
PT-7528-12MSC-12TX-4GSFP-WV-WV	IEC 61850-3 managed rackmount Ethernet switch with 12 100BaseFX ports (MSC), 12 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	6.815,00 €
PT-7528-12MST-12TX-4GSFP-HV	IEC 61850-3 managed rackmount Ethernet switch with 12 100BaseFX ports (MST), 12 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	6.428,00 €
PT-7528-12MST-12TX-4GSFP-HV-HV	IEC 61850-3 managed rackmount Ethernet switch with 12 100BaseFX ports (MST), 12 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	6.815,00 €
PT-7528-12MST-12TX-4GSFP-WV	IEC 61850-3 managed rackmount Ethernet switch with 12 100BaseFX ports (MST), 12 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	6.428,00 €
PT-7528-12MST-12TX-4GSFP-WV-WV	IEC 61850-3 managed rackmount Ethernet switch with 12 100BaseFX ports (MST), 12 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	6.815,00 €
PT-7528-16MSC-8TX-4GSFP-HV	IEC 61850-3 managed rackmount Ethernet switch with 16 100BaseFX ports (MSC), 8 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	7.165,00 €

PT-7528-16MSC-8TX-4GSFP-HV-HV	IEC 61850-3 managed rackmount Ethernet switch with 16 100BaseFX ports (MSC), 8 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	7.558,00 €
PT-7528-16MSC-8TX-4GSFP-WV	IEC 61850-3 managed rackmount Ethernet switch with 16 100BaseFX ports (MSC), 8 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	7.165,00 €
PT-7528-16MSC-8TX-4GSFP-WV-WV	IEC 61850-3 managed rackmount Ethernet switch with 16 100BaseFX ports (MSC), 8 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	7.558,00 €
PT-7528-16MST-8TX-4GSFP-HV	IEC 61850-3 managed rackmount Ethernet switch with 16 100BaseFX ports (MST), 8 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	7.165,00 €
PT-7528-16MST-8TX-4GSFP-HV-HV	IEC 61850-3 managed rackmount Ethernet switch with 16 100BaseFX ports (MST), 8 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	7.558,00 €
PT-7528-16MST-8TX-4GSFP-WV	IEC 61850-3 managed rackmount Ethernet switch with 16 100BaseFX ports (MST), 8 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	7.165,00 €
PT-7528-16MST-8TX-4GSFP-WV-WV	IEC 61850-3 managed rackmount Ethernet switch with 16 100BaseFX ports (MST), 8 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	7.558,00 €
PT-7528-20MSC-4TX-4GSFP-HV	IEC 61850-3 managed rackmount Ethernet switch with 20 100BaseFX ports (MSC), 4 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	7.943,00 €
PT-7528-20MSC-4TX-4GSFP-HV-HV	IEC 61850-3 managed rackmount Ethernet switch with 20 100BaseFX ports (MSC), 4 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	8.333,00 €
PT-7528-20MSC-4TX-4GSFP-WV	IEC 61850-3 managed rackmount Ethernet switch with 20 100BaseFX ports (MSC), 4 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	7.943,00 €
PT-7528-20MSC-4TX-4GSFP-WV-WV	IEC 61850-3 managed rackmount Ethernet switch with 20 100BaseFX ports (MSC), 4 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	8.333,00 €
PT-7528-20MST-4TX-4GSFP-HV	IEC 61850-3 managed rackmount Ethernet switch with 20 100BaseFX ports (MST), 4 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	7.943,00 €
PT-7528-20MST-4TX-4GSFP-HV-HV	IEC 61850-3 managed rackmount Ethernet switch with 20 100BaseFX ports (MST), 4 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	8.333,00 €
PT-7528-20MST-4TX-4GSFP-WV	IEC 61850-3 managed rackmount Ethernet switch with 20 100BaseFX ports (MST), 4 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	7.943,00 €
PT-7528-20MST-4TX-4GSFP-WV-WV	IEC 61850-3 managed rackmount Ethernet switch with 20 100BaseFX ports (MST), 4 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	8.333,00 €
PT-7528-24TX-HV	IEC 61850-3 managed rackmount Ethernet switch system with 1 slot for a Gigabit Ethernet module or Fast Ethernet module, for a total of up to 28 ports, cabling on front panel, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	3.679,00 €

PT-7528-24TX-HV-HV	IEC 61850-3 managed rackmount Ethernet switch system with 1 slot for a Gigabit Ethernet module or Fast Ethernet module, for a total of up to 28 ports, cabling on front panel, 2 isolated power supplies (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	3.998,00 €
PT-7528-24TX-WV	IEC 61850-3 managed rackmount Ethernet switch system with 1 slot for a Gigabit Ethernet module or Fast Ethernet module, for a total of up to 28 ports, cabling on front panel, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	3.679,00 €
PT-7528-24TX-WV-HV	IEC 61850-3 managed rackmount Ethernet switch system with 1 slot for a Gigabit Ethernet module or Fast Ethernet module, for a total of up to 28 ports, cabling on front panel, 2 isolated power supply (18 to 72 VDC and 88 to 300 VAC or 85 to 364 VDC), -40 to 85°C operating temperature	3.998,00 €
PT-7528-24TX-WV-WV	IEC 61850-3 managed rackmount Ethernet switch system with 1 slot for a Gigabit Ethernet module or Fast Ethernet module, for a total of up to 28 ports, cabling on front panel, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	3.998,00 €
PT-7528-8MSC-16TX-4GSFP-HV	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	5.515,00 €
PT-7528-8MSC-16TX-4GSFP-HV-HV	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	5.904,00 €
PT-7528-8MSC-16TX-4GSFP-WV	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	5.515,00 €
PT-7528-8MSC-16TX-4GSFP-WV-WV	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	5.904,00 €
PT-7528-8MST-16TX-4GSFP-HV	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MST), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	5.515,00 €
PT-7528-8MST-16TX-4GSFP-HV-HV	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MST), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	5.904,00 €
PT-7528-8MST-16TX-4GSFP-WV	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MST), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	5.515,00 €
PT-7528-8MST-16TX-4GSFP-WV-WV	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MST), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	5.904,00 €
PT-7528-8SSC-16TX-4GSFP-HV-HV	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (SSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	7.151,00 €
PT-7528-8SSC-16TX-4GSFP-WV-WV	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (SSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	7.151,00 €
PTC-101-M-LC-HV	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with LC connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	814,00 €

PTC-101-M-LC-LV	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with LC connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	814,00 €
PTC-101-M-SC-HV	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with SC connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	814,00 €
PTC-101-M-SC-LV	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with SC connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	814,00 €
PTC-101-M-ST-HV	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with ST connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	814,00 €
PTC-101-M-ST-LV	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with ST connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	814,00 €
PTC-101-S-LC-HV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with L connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	1.127,00 €
PTC-101-S-LC-LV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with LC connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	1.127,00 €
PTC-101-S-SC-HV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with SC connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	1.127,00 €
PTC-101-S-SC-LV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with SC connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	1.127,00 €
PTC-101-S-ST-HV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with ST connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	1.127,00 €
PTC-101-S-ST-LV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with ST connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	1.127,00 €
PT-G503-PHR-PTP-HV	IEC 61850-3 and IEC 62439-3 full Gigabit managed redundancy box, with 3 10/100/1000BaseT(X) ports or 100/1000Base SFP ports, 1 10/100/1000BaseT(X) Ethernet console port, 1 isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	3.646,00 €
PT-G503-PHR-PTP-WV	IEC 61850-3 and IEC 62439-3 full Gigabit managed redundancy box, with 3 10/100/1000BaseT(X) ports or 100/1000Base SFP ports, 1 10/100/1000BaseT(X) Ethernet console port, 1 isolated dual power supply (24/48 VDC), -40 to 85°C operating temperature	4.223,00 €
PT-G510-4GTx4GSFP-PHR-HV	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature	4.052,00 €
PT-G510-4GTx4GSFP-PHR-HV-CT	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature, conformal coating	5.103,00 €
PT-G510-4GTx4GSFP-PHR-WV	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature	4.052,00 €
PT-G510-4GTx4GSFP-PHR-WV-CT	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature, conformal coating	5.103,00 €

PT-G510-8GSFP-PHR-HV	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature	4.052,00 €
PT-G510-8GSFP-PHR-HV-CT	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature, conformal coating	5.103,00 €
PT-G510-8GSFP-PHR-WV	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature	4.052,00 €
PT-G510-8GSFP-PHR-WV-CT	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature, conformal coating	5.103,00 €
PT-G510-8GTX-PHR-HV	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature	4.052,00 €
PT-G510-8GTX-PHR-HV-CT	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature, conformal coating	5.103,00 €
PT-G510-8GTX-PHR-WV	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature	4.052,00 €
PT-G510-8GTX-PHR-WV-CT	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature, conformal coating	5.103,00 €
PT-G7728	Layer 2 modular managed Ethernet switch with 2 100/1000BaseSFP and 2 10/100/1000BaseT(X), 6 slots for Ethernet modules and 2 slots for power modules, for a maximum of 28G ports total	4.678,00 €
PT-G7828	Layer 3 modular managed Ethernet switch with 2 100/1000BaseSFP and 2 10/100/1000BaseT(X), 6 slots for Ethernet modules and 2 slots for power modules, for a maximum of 28G ports total	5.649,00 €
PWC-C13AU-3B-183	Power cord with AU plug, 1.83 m	11,00 €
PWC-C13CN-3B-183	Power cord with three-prong CN plug, 1.83 m	14,00 €
PWC-C13EU-3B-183	Power cord with EU/KR plug, 1.83 m	11,00 €
PWC-C13JP-3B-183	Power cord with JP plug plug, 7A/125V, 1.83 m	14,00 €
PWC-C13UK-3B-183	Power cord with UK plug, 1.83 m	18,00 €
PWC-C13US-3B-183	Power cord with US plug, 1.83 m	11,00 €
PWC-C15CN-3B-183	Power cord with CN plug, 1.83 m, -40 to 75°C operating temperature	28,00 €
PWC-C15EU-3B-183	Power cord with EU plug, 1.83 m, -40 to 75°C operating temperature	28,00 €
PWC-C15US-3B-183	Power cord with US plug, 1.83 m, -40 to 75°C operating temperature	28,00 €
PWR-100-LV	Power module for the EDS-4000/G4000 Series with 12/24/48 VDC redundant dual inputs, 9.6 to 60 VDC operating voltage	462,00 €
PWR-101-LV-BP-I	Power module for PoE models in the EDS-4000/G4000 Series with 48 VDC redundant dual inputs, power isolation, 44 to 57 VDC operating voltage (>52 VDC for PoE+ output recommended)	616,00 €

PWR-103-LV-VB-I	Power module for PoE models in the EDS-4000/G4000 Series with 12/24/48 VDC redundant dual inputs, power isolation, 12 to 57 VDC operating voltage (>52 VDC for PoE+ output recommended)	1.078,00 €
PWR-105-HV-I	Power module for the EDS-4000/G4000 Series with 110/220 VDC/VAC single input, power isolation, 88 to 300 VDC or 85 to 264 VAC operating voltage	769,00 €
PWR-12050-AU-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-AU-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-CN-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-CN-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-EU-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-EU-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-IN-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, IN plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-KR-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, KR plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-KR-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, KR plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-UK-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-UK-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-USJP-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	42,00 €
PWR-12050-USJP-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-AU-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, AU plug, -40 to 75°C operating temperature	52,00 €
PWR-12150-CN-S2	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, China (CN) plug, 0 to 40°C operating temperature	31,00 €
PWR-12150-CN-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, CN plug, -40 to 75°C operating temperature	52,00 €
PWR-12150-EU-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, EU plug, -40 to 75°C operating temperature	52,00 €
PWR-12150-IN-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, IN plug, -40 to 75°C operating temperature	53,00 €
PWR-12150-UK-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, UK plug, -40 to 75°C operating temperature	52,00 €
PWR-12150-USJP-SA-T	Locking barrel plug, 12 VDC 1.5 A, 100 to 240 VAC, US/JP plug, -40 to 75°C operating temperature	54,00 €
PWR-12150-WPAU-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPAU-S4	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPCN-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPCN-S4	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPEU-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	42,00 €

PWR-12150-WPEU-S4	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPIN-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, IN plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPIN-S4	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, IN plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPKR-S4	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, KR plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPUK-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPUK-S4	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPUSJP-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	42,00 €
PWR-12150-WPUSJP-S4	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	42,00 €
PWR-12300-WPAU-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	75,00 €
PWR-12300-WPCN-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	75,00 €
PWR-12300-WPEU-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	75,00 €
PWR-12300-WPUK-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	75,00 €
PWR-12300-WPUSJP-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	75,00 €
PWR-12500-DT-S1	Desktop power supply (requires power cord), 12 VDC, 5 A, 100 to 240 VAC, 0 to 40°C operating temperature	61,00 €
PWR-190-AC	110 to 240 VAC power supply for the TRC-190-AC	312,00 €
PWR-190-DC-48	36 to 53 VDC power supply for the TRC-190-DC-48	563,00 €
PWR-2190-AC	110 to 240 VAC power supply for the TRC-2190-AC	324,00 €
PWR-2190-DC-48V	36 to 53 VDC power supply for the TRC-2190-DC-48	579,00 €
PWR-24250-DT-S1	Desktop power supply (requires power cord), 24 VDC, 2.5 A, 100 to 240 VAC, 0 to 40°C operating temperature	86,00 €
PWR-300-HVA-IF	Isolated power supply module (110/220 VAC/VDC) with system power input, AC power inlet, intake fan	1.144,00 €
PWR-310-HV	110/220 VAC/VDC power supply module with system power input	1.134,00 €
PWR-310-HVA	110/220 VAC power supply module with system power input, AC power inlet	1.134,00 €
PWR-310-HV-P	110/220 VAC/VDC power supply module with system power input, PoE power input	1.604,00 €
PWR-310-LV	12/24/48 VDC power supply module with system power input	1.134,00 €
PWR-310-LV-P	12/24/48 VDC power supply module with system power input, PoE power input	1.604,00 €
PWR-G7000A-AC	Power supply module (85 to 264 VAC) for ICS-G7748A/G7750A/G7752A/G7848A/G7850A/G7852A Series, -10 to 60°C operating temperature	3.054,00 €
PWR-HV-NP	Power supply module (110/220 VAC/VDC) with system power input, relay	905,00 €
PWR-HV-P48	Power supply module (110/220 VAC/VDC) with system power input, relay, PoE power input	1.047,00 €
PWR-HV-P48-A	110/220 VAC/VDC power supply module with system power, relay, PoE power input, advanced heat sink	1.200,00 €
PWR-LV-NP	Power supply module (24/48 VDC) with system power input, relay	905,00 €
PWR-LV-P48	Power supply module (24/48 VDC) with system power input, relay, PoE power input	1.047,00 €
PWR-LV-P48-A	24/48 VDC power supply module with system power, relay, PoE power input, advanced heat sink	1.200,00 €

PWR-Plug-AU-02	AU plug for the PWR-12150-WPAU and the PWR-12300-WPAU	6,00 €
PWR-Plug-AU-03	AU plug for PWR-12300-WPAU	6,00 €
PWR-Plug-CN-02	CN plug for PWR-12150-WPCN and PWR-12300-WPCN	4,00 €
PWR-Plug-EU-02	EU plug for PWR-12150-WPEU and PWR-12300-WPEU	6,00 €
PWR-Plug-IN-02	Power plug for IN region	6,00 €
PWR-Plug-KR-02	KR plug for the PWR-12150-WPKR and the PWR-12300-WPKR	6,00 €
PWR-Plug-UK-02	UK plug for PWR-12150-WPUK and PWR-12300-WPUK	6,00 €
PWR-Plug-USJP-02	US/JP plug for PWR-12150-WPUSJP and PWR-12300-WPUSJP	4,00 €
PWS-24W24V-OF-01	Open frame power supply	49,00 €
RK-3U-02	Rack-mounting kit with 4 L-shaped plates for the MDS-G4000 and MDS-G4000-4XGS Series	713,00 €
RK-4U	19-inch rack-mounting kit	239,00 €
RKP-A110-E2-2L4C-T	Rackmount 1U computer with Intel Atom® x6211E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	3.700,00 €
RKP-A110-E2-8C-T	Rackmount 1U computer with Intel Atom® x6211E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	3.569,00 €
RKP-A110-E2-8L-T	Rackmount 1U computer with Intel Atom® x6211E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	4.058,00 €
RKP-A110-E2-T	Rackmount 1U computer with Intel Atom® x6211E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	3.276,00 €
RKP-A110-E2-T-Win10	Rackmount 1U computer with Intel Atom® x6211E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	3.993,00 €
RKP-A110-E4-2L4C-T	Rackmount 1U computer with Intel Atom® x6425E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	3.879,00 €
RKP-A110-E4-8C-T	Rackmount 1U computer with Intel Atom® x6425E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	3.749,00 €
RKP-A110-E4-8L-T	Rackmount 1U computer with Intel Atom® x6425E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	4.091,00 €
RKP-A110-E4-T	Rackmount 1U computer with Intel Atom® x6425E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	3.374,00 €
RKP-A110-E4-T-Win10	Rackmount 1U computer with Intel Atom® x6425E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	4.124,00 €
RKP-C110-C1-2HV-T	Rackmount 1U computer with Intel® Celeron® 6305E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 100 to 240 VAC/VDC power input, -30 to 60°C operating temperature	5.517,00 €

RKP-C110-C1-2L4C-T	Rackmount 1U computer with Intel® Celeron® 6305E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	4.262,00 €
RKP-C110-C1-8C-T	Rackmount 1U computer with Intel® Celeron® 6305E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	4.058,00 €
RKP-C110-C1-8L-T	Rackmount 1U computer with Intel® Celeron® 6305E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	4.629,00 €
RKP-C110-C1-T	Rackmount 1U computer with Intel® Celeron® 6305E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	3.684,00 €
RKP-C110-C1-T-Win10	Rackmount 1U computer with Intel® Celeron® 6305E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	4.661,00 €
RKP-C110-C3-2HV-T	Rackmount 1U computer with Intel® Core™ i3-1115G4E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 100 to 240 VAC/VDC power input, -30 to 60°C operating temperature	6.666,00 €
RKP-C110-C3-2L4C-T	Rackmount 1U computer with Intel® Core™ i3-1115G4E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	4.743,00 €
RKP-C110-C3-8C-T	Rackmount 1U computer with Intel® Core™ i3-1115G4E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	4.596,00 €
RKP-C110-C3-8L-T	Rackmount 1U computer with Intel® Core™ i3-1115G4E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	5.036,00 €
RKP-C110-C3-T	Rackmount 1U computer with Intel® Core™ i3-1115G4E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	4.197,00 €
RKP-C110-C3-T-Win10	Rackmount 1U computer with Intel® Core™ i3-1115G4E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	4.922,00 €
RKP-C110-C5-2HV-T	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 100 to 240 VAC/VDC power input, -30 to 60°C operating temperature	7.057,00 €
RKP-C110-C5-2L4C-T	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	5.574,00 €
RKP-C110-C5-8C-T	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	5.460,00 €
RKP-C110-C5-8L-T	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	5.949,00 €
RKP-C110-C5-T	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	4.955,00 €
RKP-C110-C5-T-Win10	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	5.982,00 €

RKP-C110-C7-2HV-T	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 100 to 240 VAC/VDC power input, -30 to 60°C operating temperature	7.807,00 €
RKP-C110-C7-2L4C-T	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	6.242,00 €
RKP-C110-C7-8C-T	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	6.161,00 €
RKP-C110-C7-8L-T	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	6.699,00 €
RKP-C110-C7-T	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	5.688,00 €
RKP-C110-C7-T-Win10	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	6.731,00 €
RKP-C220-C3-2CB6C-T	Rackmount 2U computer with Intel® Core™ i3-13100TE processor, 4 LAN ports, 8 serial ports, 4 DIs, 4 DOs, 2 CAN ports, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	7.994,00 €
RKP-C220-C3-4L-T	Rackmount 2U computer with Intel® Core™ i3-13100TE processor, 8 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	7.839,00 €
RKP-C220-C3-8C-T	Rackmount 2U computer with Intel® Core™ i3-13100TE processor, 4 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	7.693,00 €
RKP-C220-C3-T	Rackmount 2U computer with Intel® Core™ i3-13100TE processor, 4 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 12/24 VDC power input, -30 to 60°C operating temperature	7.253,00 €
RKP-C220-C5-2CB6C-T	Rackmount 2U computer with Intel® Core™ i5-13500TE processor, 4 LAN ports, 8 serial ports, 4 DIs, 4 DOs, 2 CAN ports, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	8.858,00 €
RKP-C220-C5-4L-T	Rackmount 2U computer with Intel® Core™ i5-13500TE processor, 8 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	8.703,00 €
RKP-C220-C5-8C-T	Rackmount 2U computer with Intel® Core™ i5-13500TE processor, 4 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 12/24 VDC power input, -30 to 60°C operating temperature	8.557,00 €
RKP-C220-C5-T	Rackmount 2U computer with Intel® Core™ i5-13500TE processor, 4 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 12/24 VDC power input, -30 to 60°C operating temperature	8.117,00 €
RKP-C220-C7-2CB6C-T	Rackmount 2U computer with Intel® Core™ i7-13700TE processor, 4 LAN ports, 8 serial ports, 4 DIs, 4 DOs, 2 CAN ports, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	9.543,00 €

RKP-C220-C7-4L-T	Rackmount 2U computer with Intel® Core™ i7-13700TE processor, 8 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	9.388,00 €
RKP-C220-C7-8C-T	Rackmount 2U computer with Intel® Core™ i7-13700TE processor, 4 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 12/24 VDC power input, -30 to 60°C operating temperature	9.241,00 €
RKP-C220-C7-T	Rackmount 2U computer with Intel® Core™ i7-13700TE processor, 4 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 12/24 VDC power input, -30 to 60°C operating temperature	8.801,00 €
RKP-C220-C9-2CB6C-T	Rackmount 2U computer with Intel® Core™ i9-13900TE processor, 4 LAN ports, 8 serial ports, 4 DIs, 4 DOs, 2 CAN ports, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	11.376,00 €
RKP-C220-C9-4L-T	Rackmount 2U computer with Intel® Core™ i9-13900TE processor, 8 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	11.229,00 €
RKP-C220-C9-8C-T	Rackmount 2U computer with Intel® Core™ i9-13900TE processor, 4 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	11.083,00 €
RKP-C220-C9-T	Rackmount 2U computer with Intel® Core™ i9-13900TE processor, 4 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 3 USB 3.0 ports, 1 HDMI port, 1 DisplayPort, 2 SSD slots, 1 M.2 M Key 2280 slot, 2 M.2 M Key 2242 slots, 100 to 240 VAC power input, -30 to 60°C operating temperature	10.643,00 €
RKP-FAN	Fan module for the RKP-C220 Series	457,00 €
RKS-G4028-4GS-2HV-T	Layer 2 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	5.008,00 €
RKS-G4028-4GS-2LV-T	Layer 2 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	5.907,00 €
RKS-G4028-4GS-HV-T	Layer 2 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	4.816,00 €
RKS-G4028-4GS-LV-T	Layer 2 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	5.265,00 €
RKS-G4028-4GT-2HV-T	Layer 2 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	4.850,00 €
RKS-G4028-4GT-2LV-T	Layer 2 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	5.740,00 €
RKS-G4028-4GT-HV-T	Layer 2 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	4.657,00 €
RKS-G4028-4GT-LV-T	Layer 2 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	5.108,00 €
RKS-G4028-L3-4GS-2HV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	7.565,00 €

RKS-G4028-L3-4GS-2LV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	8.457,00 €
RKS-G4028-L3-4GS-HV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	7.374,00 €
RKS-G4028-L3-4GS-LV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	7.815,00 €
RKS-G4028-L3-4GT-2HV-T	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	7.407,00 €
RKS-G4028-L3-4GT-2LV-T	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	8.299,00 €
RKS-G4028-L3-4GT-HV-T	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	7.216,00 €
RKS-G4028-L3-4GT-LV-T	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	7.657,00 €
RKS-G4028-L3-PoE-4GS-2HV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	10.115,00 €
RKS-G4028-L3-PoE-4GS-2LV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	11.007,00 €
RKS-G4028-L3-PoE-4GS-HV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	9.923,00 €
RKS-G4028-L3-PoE-4GS-LV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	10.365,00 €
RKS-G4028-PL-12XGS-T	Layer 2 modular managed Ethernet switch with 12 fixed 10GbE SFP+ ports, 2 slots for Ethernet modules, 2 slots for isolated power modules , -40 to 75°C operating temperature	12.127,00 €
RKS-G4028-PL-L3-12XGS-T	Layer 3 modular managed Ethernet switch with 12 fixed 10GbE SFP+ ports, 2 slots for Ethernet modules, 2 slots for isolated power modules , -40 to 75°C operating temperature	14.260,00 €
RKS-G4028-PL-L3-PoE-12XGS-T	Layer 3 modular managed Ethernet switch with 12 fixed 10GbE SFP+, 2 slots for Ethernet modules, PoE Ethernet module support, 2 slots for isolated power modules , -40 to 75°C operating temperature	16.393,00 €
RKS-G4028-PL-PoE-12XGS-T	Layer 2 modular managed Ethernet switch with 12 fixed 10GbE SFP+ ports, 2 slots for Ethernet modules, PoE Ethernet module support, 2 slots for isolated power modules , -40 to 75°C operating temperature	14.260,00 €
RKS-G4028-PoE-4GS-2HV-T	Layer 2 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	7.565,00 €
RKS-G4028-PoE-4GS-2LV-T	Layer 2 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	8.457,00 €
RKS-G4028-PoE-4GS-HV-T	Layer 2 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	7.374,00 €

RKS-G4028-PoE-4GS-LV-T	Layer 2 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	7.815,00 €
RKS-G4030-PL-8QGT-6XGS-T	Layer 2 modular managed Ethernet switch with 8 fixed 2.5GBaseT(X) ports, 6 fixed 10GbE SFP+ ports, 2 slots for Ethernet module, 2 slots for isolated power modules, -40 to 75°C operating temperature	8.311,00 €
RKS-G4030-PL-L3-8QGT-6XGS-T	Layer 3 modular managed Ethernet switch with 8 fixed 2.5GbaseT(X) ports, 6 fixed 10GbE SFP+ ports, 2 slots for Ethernet modules, 2 slots for isolated power modules , -40 to 75°C operating temperature	10.450,00 €
RKS-G4030-PL-L3-PoE-8QGT-6XGS-T	Layer 3 modular managed Ethernet switch with 8 fixed 2.5G BaseT(X) PoE ports, 6 fixed 10GbE SFP+ ports, 2 slots for Ethernet modules, PoE Ethernet module support, 2 slots for isolated power modules , -40 to 75°C operating temperature	12.583,00 €
RKS-G4030-PL-PoE-8QGT-6XGS-T	Layer 2 modular managed Ethernet switch with 8 fixed 2.5G BaseT(X) PoE ports, 6 fixed 10GbE SFP+ ports, 2 slots for Ethernet modules, PoE Ethernet module support, 2 slots for isolated power modules, -40 to 75°C operating temperature	10.450,00 €
RK-UP1600-G2	Rack mounting kits for UPort 1400/1600-G2	96,00 €
RM-G4000-2MSC4TX	Fast Ethernet module with 2 multi-mode 100BaseFX ports with SC connectors, 4 10/100BaseT(X) ports	934,00 €
RM-G4000-2MST4TX	Fast Ethernet module with 2 multi-mode 100BaseFX ports with ST connectors, 4 10/100BaseT(X) ports	1.010,00 €
RM-G4000-2SSC4TX	Fast Ethernet module with 2 single-mode 100BaseFX ports with SC connectors, 4 10/100BaseT(X) ports	1.483,00 €
RM-G4000-4MSC2TX	Fast Ethernet module with 4 multi-mode 100BaseFX ports with SC connectors, 2 10/100BaseT(X) ports	1.425,00 €
RM-G4000-4MST2TX	Fast Ethernet module with 4 multi-mode 100BaseFX ports with ST connectors, 2 10/100BaseT(X) ports	1.583,00 €
RM-G4000-4SSC2TX	Fast Ethernet module with 4 single-mode 100BaseFX ports with SC connectors, 2 10/100BaseT(X) ports	2.527,00 €
RM-G4000-6MSC	Fast Ethernet module with 6 multi-mode 100BaseFX ports with SC connectors	1.919,00 €
RM-G4000-6MST	Fast Ethernet module with 6 multi-mode 100BaseFX ports with ST connectors	2.152,00 €
RM-G4000-6SSC	Fast Ethernet module with 6 single-mode 100BaseFX ports with SC connectors	3.567,00 €
RM-G4000-8GPoE	Gigabit Ethernet module with 8 10/100/1000BaseT(X) IEEE 802.3bt PoE ports	1.767,00 €
RM-G4000-8GSFP	Gigabit Ethernet module with 8 100/1000BaseSFP slots	1.842,00 €
RM-G4000-8GTx	Gigabit Ethernet module with 8 10/100/1000BaseT(X) ports	1.176,00 €
RM-G4000-8PoE	Fast Ethernet module with 8 10/100BaseT(X) IEEE 802.3bt PoE ports	1.176,00 €
RM-G4000-8SFP	Fast Ethernet module with 8 100BaseSFP slots	926,00 €
RM-G4000-8Tx	Fast Ethernet module with 8 10/100BaseT(X) ports	592,00 €
RM-G4000-PL-8GPoE	Gigabit Ethernet module with 8 100/1000BaseT(X) IEEE 802.3bt PoE ports	2.086,00 €
RM-G4000-PL-8GSFP	Gigabit Ethernet module with 8 100/1000BaseSFP ports	1.711,00 €
RM-G4000-PL-8GTx	Gigabit Ethernet module with 8 100/1000BaseT(X) ports	1.657,00 €
S-Cybersecurity_Network Inspection	Order only against quotation! Engineering Service for Cybersecurity Network Inspection. See "S-Cybersecurity Network Inspection" outline document for details. Prior customer agreement required. Price for full day service.	4.130,00 €
SDS-3006	Compact industrial smart Ethernet switch with 6 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	486,00 €

SDS-3006-2GTXSFP	Compact industrial smart Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	833,00 €
SDS-3006-2GTXSFP-T	Compact industrial smart Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	956,00 €
SDS-3006-4PoE-2GTXSFP	Compact industrial smart Ethernet switch with 4 PoE/PoE+ 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	1.188,00 €
SDS-3006-4PoE-2GTXSFP-T	Compact industrial smart Ethernet switch with 4 PoE/PoE+ 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.311,00 €
SDS-3006-T	Compact industrial smart Ethernet switch with 6 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	609,00 €
SDS-3008	Compact industrial smart Ethernet switch with 8 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	609,00 €
SDS-3008 Rackmount Kit	1U-high 19" rack mounting kit for SDS-3008	239,00 €
SDS-3008-T	Compact industrial smart Ethernet switch with 8 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	674,00 €
SDS-3010-2GTXSFP	Compact industrial smart Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	949,00 €
SDS-3010-2GTXSFP-T	Compact industrial smart Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.072,00 €
SDS-3010-8PoE-2GTXSFP	Compact industrial smart Ethernet switch with 8 PoE/PoE+ 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	1.311,00 €
SDS-3010-8PoE-2GTXSFP-T	Compact industrial smart Ethernet switch with 8 PoE/PoE+ 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.434,00 €
SDS-3016	Compact industrial smart Ethernet switch with 16 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	971,00 €
SDS-3016-2GSFP	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	1.072,00 €
SDS-3016-2GSFP-T	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.130,00 €
SDS-3016-2GTX	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	1.072,00 €
SDS-3016-2GTX-T	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.130,00 €
SDS-3016-T	Compact industrial smart Ethernet switch with 16 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.094,00 €
SDS-G3006	Compact industrial full Gigabit smart Ethernet switch with 6 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	638,00 €
SDS-G3006-2GTXSFP	Compact industrial smart Ethernet switch with 4 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	934,00 €

SDS-G3006-2GTXSFP-T	Compact industrial smart Ethernet switch with 4 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.058,00 €
SDS-G3006-4PoE-2GTXSFP	Compact industrial full Gigabit smart Ethernet switch with 4 PoE/PoE+ 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	1.296,00 €
SDS-G3006-4PoE-2GTXSFP-T	Compact industrial full Gigabit smart Ethernet switch with 4 PoE/PoE+ 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.420,00 €
SDS-G3006-T	Compact industrial full Gigabit smart Ethernet switch with 6 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	761,00 €
SDS-G3008	Compact industrial full Gigabit smart Ethernet switch with 8 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	761,00 €
SDS-G3008-T	Compact industrial full Gigabit smart Ethernet switch with 8 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	884,00 €
SDS-G3010-2GTXSFP	Compact industrial smart Ethernet switch with 8 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	1.050,00 €
SDS-G3010-2GTXSFP-T	Compact industrial smart Ethernet switch with 8 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.181,00 €
SDS-G3010-8PoE-2GTXSFP	Compact industrial full Gigabit smart Ethernet switch with 8 PoE/PoE+ 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	1.427,00 €
SDS-G3010-8PoE-2GTXSFP-T	Compact industrial full Gigabit smart Ethernet switch with 8 PoE/PoE+ 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.550,00 €
SDS-G3016	Compact industrial full Gigabit smart Ethernet switch with 16 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	1.181,00 €
SDS-G3016-2GSFP	Compact industrial full Gigabit smart Ethernet switch with 14 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	1.340,00 €
SDS-G3016-2GSFP-T	Compact industrial full Gigabit smart Ethernet switch with 14 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.456,00 €
SDS-G3016-T	Compact industrial full Gigabit smart Ethernet switch with 16 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	1.296,00 €
S-Factory Acceptance Test	Order only against quotation! Engineering Service for Factory Acceptance Test. Organize factory tour, inspection of goods and respective test protocols. Prior customer agreement required. Order full day.	4.130,00 €
SFP-10GERLC-T	SFP+ module with 1 10GBase-ER port, LC connector for 40 km transmission, -40 to 85°C operating temperature	10.822,00 €
SFP-10GLRLC-T	SFP+ module with 1 10GBase-LR port, LC connector for 10 km transmission, -40 to 85°C operating temperature	3.312,00 €
SFP-10GSRLC-T	SFP+ module with 1 10GBase-SR port, LC connector for 33m/82m/300m/400m transmission, -40 to 85°C operating temperature	2.030,00 €
SFP-10GZRLC-T	SFP+ module with 1 10GBase-ZR port, LC connector for 80 km transmission, -40 to 85°C operating temperature	14.355,00 €
SFP-1FELLC-T	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature	1.463,00 €

SFP-1FEMLC-T	SFP module with 1 100Base multi-mode, LC connector for 2/4 km transmission, -40 to 85°C operating temperature	176,00 €
SFP-1FESLC-T	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature	397,00 €
SFP-1G10ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature	461,00 €
SFP-1G10ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature	565,00 €
SFP-1G10BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature	998,00 €
SFP-1G10BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature	1.095,00 €
SFP-1G20ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature	828,00 €
SFP-1G20ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature	917,00 €
SFP-1G20BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature	1.720,00 €
SFP-1G20BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature	1.801,00 €
SFP-1G40ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature	2.143,00 €
SFP-1G40ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature	2.236,00 €
SFP-1G40BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature	2.350,00 €
SFP-1G40BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature	2.444,00 €
SFP-1GEZXLC	SFP module with 1 1000BaseEZ port with LC connector for 110 km transmission, 0 to 60°C operating temperature	2.719,00 €
SFP-1GEZXLC-120	SFP module with 1 1000BaseEZ port with LC connector for 120 km transmission, 0 to 60°C operating temperature	3.262,00 €
SFP-1GLHLC	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature	475,00 €
SFP-1GLHLC-T	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature	539,00 €
SFP-1GLHXLC	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, 0 to 60°C operating temperature	1.143,00 €
SFP-1GLHXLC-T	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature	1.224,00 €
SFP-1GLSXLC	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, 0 to 60°C operating temperature	400,00 €
SFP-1GLSXLC-T	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, -40 to 85°C operating temperature	489,00 €
SFP-1GLXLC	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, 0 to 60°C operating temperature	371,00 €
SFP-1GLXLC-T	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature	437,00 €
SFP-1GSXLC	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, 0 to 60°C operating temperature	210,00 €
SFP-1GSXLC-T	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, -40 to 85°C operating temperature	284,00 €
SFP-1GTXRJ45-T	SFP module with 1 1000BaseT port with RJ45 connector for 100 m transmission, -40 to 75°C operating temperature	461,00 €
SFP-1GZXLC	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, 0 to 60°C operating temperature	1.914,00 €

SFP-1GZXLC-T	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature	1.977,00 €
SFP-2.5GLSLC-T	SFP module with 1 2.5GBaseFX port with LC connector, single-mode, for 20 km transmission, -40 to 85 °C operating temperature	960,00 €
SFP-2.5GMLC-T	SFP module with 1 2.5GBaseFX port with LC connector, multi-mode, for 170, 200, 550, 600 m transmission, -40 to 85 °C operating temperature	387,00 €
SFP-2.5GSLC-T	SFP module with 1 2.5GBaseFX port with LC connector, single-mode, for 5 km transmission, -40 to 85 °C operating temperature	624,00 €
SFP-2.5GSLHLC-T	SFP module with 1 2.5GBaseFX port with LC connector, single-mode, for 45 km transmission, -40 to 85 °C operating temperature	2.862,00 €
S-IIoT-Consulting	Order only against quotation! Engineering Service for IIoT Consulting. See "S-IIOT-Consulting" outline document for details. Prior customer agreement required. Price for full day service.	4.130,00 €
S-IIoT-PoC	Order only against quotation! Two Days workshop with PoC for IIOT . Conditions "S-IIOT-PoC" outline document for details. Price for 2 full days service. UC-8112A or similar included	8.257,00 €
S-IIoT-SLA-Level1	Order only against quotation! Support for Moxa Industrial Linux. . Conditions see "S-IIOT-SLA" outline document for details. Price charged per service year.	#VALORE!
S-IIoT-SLA-Level2	Order only against quotation! Support for Moxa Industrial Linux and ThingsPro Gateway . Conditions see "S-IIOT-SLA" outline document for details. Price charged per service year.	#VALORE!
S-IIoT-SLA-Level3	Order only against quotation! Support for Moxa Industrial Linux and Things pro Edge (incl. cloud-based device management). Conditions see "S-IIOT-SLA" outline document for details. Price charged per service year.	#VALORE!
SK-115-01	Side-mounting kit with T-shaped mounting bracket (81.2 x 115.0 mm), 4 M3 x 6 mm screws	40,00 €
S-MRC-PoC	Order only against quotation! One Day workshop with PoC for MRC . Conditions "S-MRC-PoC" outline document for details. Price for full day service.	4.130,00 €
S-Network Consulting-Addresses	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	3.304,00 €
S-Network Consulting-Audit	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	4.130,00 €
S-Network Consulting-Configuration	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	3.304,00 €
S-Network Consulting-Design	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	3.304,00 €
S-Network Consulting-Onsite	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	3.304,00 €
S-Network Consulting-Preparation	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	3.304,00 €
S-Network Consulting-Test Plan	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	3.304,00 €
S-Network Inspection	Order only against quotation! Engineering Service for Network Inspection. See "S-Network Inspection" outline document for details. Prior customer agreement required. Price for full day service.	3.304,00 €
S-Onsite Support	Order only against quotation! Engineering Service for Onsite Support. Prior customer agreement required. Travel & accomodation excluded. Price for full day service. See onsite outline document for details.	2.754,00 €

SPL-24	PoE splitter with maximum output of 12.95 W at 24 VDC, 0 to 60°C operating temperature	226,00 €
SPL-24-T	PoE splitter with maximum output of 12.95 W at 24 VDC, -40 to 75°C operating temperature	337,00 €
S-Project Management-Execution	Order only against quotation! Project Management Service. See "S-Project Management" outline document for details. Prior customer agreement required. Price charged per service hour.	551,00 €
S-Project Management-Preparation	Order only against quotation! Project Management Service. See "S-Project Management" outline document for details. Prior customer agreement required. Price charged per service hour.	551,00 €
S-Sample Provisioning	Order only against quotation! Samples from MEU stock are loaned to customers for evaluation purpose. Conditions see "S-Sample Provisioning" outline document for details.. Price charged per service week.	#VALORE!
S-Technical Support-SLA Basic Post-Warranty	Order only against quotation! Technical Support service commitment based on deployed hardware/software after warranty. Respective Customer declaration and contract required. Conditions see "S-Technical Support-SLA" outline document for details. Price charged per service year.	#VALORE!
S-Technical Support-SLA Basic Warranty	Order only against quotation! Technical Support service commitment based on deployed hardware/software under warranty. Respective Customer declaration and contract required. Conditions see "S-Technical Support-SLA" outline document for details. Price charged per service year.	#VALORE!
S-Training-IES-Standard-Classroom	Order only against quotation! IES Standard Training. See Training Modules as IES-F1, IES-L2, IES-OM, IES-L3, IES-W1, IES-CS1, IES-CS2. Order per participant and day. Provide number of participants in comment field. Classroom training is hosted in Munich.	826,00 €
S-Training-IES-Standard-onsite	Order only against quotation! IES Standard Training. See Training Modules as IES-F1, IES-L2, IES-OM, IES-L3, IES-W1, IES-CS1, IES-CS2. Order for 4* participants and by day. Provide number of participants in comment field and location. Travel & accomodation excluded.	2.754,00 €
S-Training-IIoT-Classroom	Order only against quotation! IIoT Special Training. See Training Modules as embedded computing & edge connectivity, in addition . Order per participant and day. Provide number of participants in comment field.	1.101,00 €
S-Training-IIoT-onsite	Order only against quotation! IIoT Special Training. See Training Modules as embedded computing & edge connectivity, in addition . Order for 4* participants and day. Provide number of participants in comment field and location. Travel & accomodation excluded.	4.130,00 €
S-Training-Power-classroom	Order only against quotation! Power Special Training. See Training Module for power with PRP, HSR and IEEE 1588. Order per participant and day. Provide number of participants in comment field. Classroom training in Munich.	1.101,00 €
S-Training-Power-onsite	Order only against quotation! Power Special Training. See Training Module for power with PRP, HSR and IEEE 1588. Order for 4* participants and by day. Provide number of participants in comment field and location. Travel & accomodation excluded.	4.130,00 €
TAP-213-EU-CT-T	Wi-Fi 4 (802.11n) railway onboard outdoor train-to-ground single-radio wireless AP/client, M12 connectors, IP68, EU band, -40 to 75°C operating temperature, conformal coating	4.723,00 €
TAP-213-JP-CT-T	Wi-Fi 4 (802.11n) railway onboard outdoor train-to-ground single-radio wireless AP/client, M12 connectors, IP68, JP band, -40 to 75°C operating temperature, conformal coating	4.723,00 €
TAP-213-US-CT-T	Wi-Fi 4 (802.11n) railway onboard outdoor train-to-ground single-radio wireless AP/client, M12 connectors, IP68, US band, -40 to 75°C operating temperature, conformal coating	4.723,00 €
TAP-323-EU-CT-T	Wi-Fi 4 (802.11n) railway wayside outdoor train-to-ground dual-radio wireless AP, IP68, EU band, -40 to 75°C operating temperature, conformal coating	11.033,00 €
TAP-323-JP-CT-T	Wi-Fi 4 (802.11n) railway wayside outdoor train-to-ground dual-radio wireless AP, IP68, JP band, -40 to 75°C operating temperature, conformal coating	11.033,00 €

TAP-323-US-CT-T	Wi-Fi 4 (802.11n) railway wayside outdoor train-to-ground dual-radio wireless AP, IP68, US band, -40 to 75°C operating temperature, conformal coating	11.033,00 €
TAP-M310R-1P1R1S-EU-CT-T	Wi-Fi 6 (802.11ax) railway wayside wireless AP/client with one radio and one switch module, one M12 K-coded 110/220 VAC input, EU band, -40 to 75°C operating temperature, conformal coating	7.804,00 €
TAP-M310R-1P1R1S-US-CT-T	Wi-Fi 6 (802.11ax) railway wayside wireless AP/client with one radio and one switch module, one M12 K-coded 110/220 VAC input, US band, -40 to 75°C operating temperature, conformal coating	7.804,00 €
TAP-M310R-1P2R1S-EU-CT-T	Wi-Fi 6 (802.11ax) railway wayside wireless AP/client with two radios and one switch module, one M12 K-coded 110/220 VAC input, EU band, -40 to 75°C operating temperature, conformal coating	12.006,00 €
TAP-M310R-1P2R1S-US-CT-T	Wi-Fi 6 (802.11ax) railway wayside wireless AP/client with two radios and one switch module, one M12 K-coded 110/220 VAC input, US band, -40 to 75°C operating temperature, conformal coating	12.006,00 €
TAP-M310R-NPS-1P1R-EU-CT-T	Wi-Fi 6 (802.11ax) railway onboard wireless AP/client with one radio module, no power splitters, one M12 K-coded 24 to 110 VDC input, EU band, -40 to 75°C operating temperature, conformal coating	5.253,00 €
TAP-M310R-NPS-1P1R-US-CT-T	Wi-Fi 6 (802.11ax) railway onboard wireless AP/client with one radio module, no power splitters, one M12 K-coded 24 to 110 VDC input, US band, -40 to 75°C operating temperature, conformal coating	5.253,00 €
TAP-M310R-NPS-1R-EU-CT-T	Wi-Fi 6 (802.11ax) railway onboard wireless AP/client with one radio module, no power splitters, one M12 A-coded 24 VDC input, EU band, -40 to 75°C operating temperature, conformal coating	3.715,00 €
TAP-M310R-NPS-1R-US-CT-T	Wi-Fi 6 (802.11ax) railway onboard wireless AP/client with one radio module, no power splitters, one M12 A-coded 24 VDC input, US band, -40 to 75°C operating temperature, conformal coating	3.715,00 €
TB-F25	DB25 female DIN-rail wiring terminal	70,00 €
TB-F9	DB9 female DIN-rail wiring terminal	53,00 €
TB-M25	DB25 male DIN-rail wiring terminal	70,00 €
TB-M9	DB9 male DIN-rail wiring terminal	53,00 €
TCC-100	RS-232 to RS-422/485 converter	116,00 €
TCC-100I	RS-232 to RS-422/485 converter with optical isolation	186,00 €
TCC-100I-T	RS-232 to RS-422/485 converter with optical isolation, -40 to 85°C operating temperature	234,00 €
TCC-100-T	RS-232 to RS-422/485 converter, -40 to 85°C operating temperature	152,00 €
TCC-120	RS-422/485 converter/repeater	152,00 €
TCC-120I	RS-422/485 converter/repeater with optical isolation	202,00 €
TCC-80	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection and terminal block on the RS-422/485 side	64,00 €
TCC-80-DB9	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection and DB9 male connector on the RS-422/485 side	64,00 €
TCC-80I	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection, terminal block on the RS-422/485 side, and 2.5 kV optical isolation	134,00 €
TCC-80I-DB9	Port-powered RS-232 to RS-422/485 converter with 15 KV serial ESD protection, DB9 male connector on the RS-422/485 side, and 2.5 KV optical isolation	134,00 €
TCC-82	Port-powered RS-232 isolator with 4 kV isolation and 15 KV serial ESD protection	107,00 €
TCF-142-M-SC	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and SC connector, 0 to 60°C operating temperature	292,00 €
TCF-142-M-SC-RM	RS-232/422/485 to multi-mode fiber slide-in module converter, SC connector	285,00 €
TCF-142-M-SC-T	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and SC connector, -40 to 75°C operating temperature	379,00 €
TCF-142-M-ST	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and ST connector, 0 to 60°C operating temperature	292,00 €
TCF-142-M-ST-RM	RS-232/422/485 to multi-mode fiber slide-in module converter, ST connector	285,00 €

TCF-142-M-ST-T	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and ST connector, -40 to 75°C operating temperature	379,00 €
TCF-142-S-SC	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and SC connector, 0 to 60°C operating temperature	703,00 €
TCF-142-S-SC-RM	RS-232/422/485 to single-mode fiber slide-in module converter, SC connector	600,00 €
TCF-142-S-SC-T	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and SC connector, -40 to 75°C operating temperature	930,00 €
TCF-142-S-ST	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and ST connector, 0 to 60°C operating temperature	703,00 €
TCF-142-S-ST-RM	RS-232/422/485 to single-mode fiber slide-in module converter, ST connector	600,00 €
TCF-142-S-ST-T	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and ST connector, -40 to 75°C operating temperature	930,00 €
TCF-90-M-ST	RS-232 to multi-mode ST fiber optic converter, port powered	234,00 €
TCF-90-S-ST	RS-232 to single-mode ST fiber optic converter, port powered	394,00 €
TN-4508B-CT-T	EN 50155 8-port L2 switch with 8 FE ports, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	3.242,00 €
TN-4512A-WV-CT-T	12 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	3.281,00 €
TN-4512A-WV-T	12 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	3.039,00 €
TN-4512B-4G-8GP-CT-T	EN 50155 12-port L2 switch with 4 Gigabit ports, 8 Gigabit PoE ports, 80 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42 rating, conformal coating	7.292,00 €
TN-4512B-8P-4G-CT-T	EN 50155 12-port L2 switch including 8 FE PoE ports, 4 Gigabit ports, 80 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	5.253,00 €
TN-4512B-CT-T	EN 50155 12-port L2 switch with 12 FE ports, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	3.827,00 €
TN-4516A-12PoE-2GPoE-2GODC-WV-CT-T	12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	9.519,00 €
TN-4516A-12PoE-2GPoE-2GODC-WV-T	12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	8.811,00 €
TN-4516A-12PoE-2GPoE-2GTXPB-WV-CT-T	Layer 2 managed Ethernet switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector and bypass relay, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	7.510,00 €
TN-4516A-12PoE-2GPoE-2GTXPB-WV-T	Layer 2 managed Ethernet switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector and bypass relay, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	6.974,00 €
TN-4516A-12PoE-4GPoE-WV-CT-T	Layer 2 managed Ethernet switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	7.480,00 €
TN-4516A-12PoE-4GPoE-WV-T	Layer 2 managed switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, 12 PoE 10/100BaseT(X) ports with M12 connector, -40 to 75°C operating temperature	6.924,00 €

TN-4516A-4GTXP-WV-CT-T	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, 4 Gigabit Ethernet ports with bypass relay function support, dual redundant power inputs (24 to 110 VDC), -40 to 75°C operating temperature, conformal coating	5.046,00 €
TN-4516A-4GTXP-WV-T	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, 4 Gigabit Ethernet ports with bypass relay function support, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature	4.670,00 €
TN-4516A-4GTXP-WV-CT-T	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, dual redundant power inputs (24 to 110 VDC), -40 to 75°C operating temperature, conformal coating	4.687,00 €
TN-4516A-4GTXP-WV-T	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature	4.343,00 €
TN-4516A-WV-CT-T	Layer 2 managed Ethernet switch with 16 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature, conformal coating	4.378,00 €
TN-4516A-WV-T	Layer 2 managed Ethernet switch with 16 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature	4.058,00 €
TN-4516B-12GP-4GBP-CT-T	EN 50155 16-port L2 switch with 4 Gigabit ports (with bypass relay), 12 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42 rating, conformal coating	9.781,00 €
TN-4516B-4G-12GP-CT-T	EN 50155 16-port L2 switch with 4 Gigabit ports, 12 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42 rating, conformal coating	9.416,00 €
TN-4516B-8G-CT-T	EN 50155 16-port L2 switch including 8 FE ports, 8 Gigabit ports, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	6.153,00 €
TN-4516B-8P-4G-4GP-CT-T	EN 50155 16-port L2 switch including 8 FE PoE ports, 4 Gigabit ports, 4 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	7.053,00 €
TN-4516B-8P-4GP-4GBP-CT-T	EN 50155 16-port L2 switch including 8 FE PoE ports, 4 Gigabit ports with bypass relay, 4 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	7.429,00 €
TN-4516B-CT-T	EN 50155 16-port L2 switch with 16 FE ports, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	4.833,00 €
TN-4520A-16PoE-4GPoE-WV-CT-T	Layer 2 managed Ethernet switch with 16 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature, conformal coating	7.313,00 €
TN-4520A-16PoE-4GPoE-WV-T	Layer 2 managed Ethernet switch with 16 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature	6.770,00 €
TN-4520B-12P-4G-4GP-CT-T	EN 50155 20-port L2 switch including 12 FE PoE ports, 4 Gigabit ports, 4 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	8.404,00 €
TN-4520B-12P-4GP-4GBP-CT-T	EN 50155 20-port L2 switch including 12 FE PoE ports, 4 Gigabit PoE ports, 4 Gigabit ports with bypass relay, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	8.779,00 €
TN-4524A-16PoE-WV-CT-T	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	7.510,00 €
TN-4524A-16PoE-WV-T	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	6.974,00 €

TN-4524B-16P-4G-4GP-CT-T	EN 50155 24-port L2 switch with 16 FE PoE ports, 4 Gigabit ports, 4 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42 rating, conformal coating	9.605,00 €
TN-4524B-16P-4GP-4GBP-CT-T	EN 50155 24-port L2 switch with 16 FE PoE ports, 4 Gigabit ports (with bypass relay), 4 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42 rating, conformal coating	9.980,00 €
TN-4528A-16PoE-2GPoE-2GODC-WV-CT-T	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	12.372,00 €
TN-4528A-16PoE-2GPoE-2GODC-WV-T	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	11.443,00 €
TN-4528A-16PoE-2GPoE-2GTXPB-WV-CT-T	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector with bypass relay, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	10.359,00 €
TN-4528A-16PoE-2GPoE-2GTXPB-WV-T	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector with bypass relay, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	9.608,00 €
TN-4528A-16PoE-4GPoE-WV-CT-T	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	10.332,00 €
TN-4528A-16PoE-4GPoE-WV-T	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	9.558,00 €
TN-4528B-20P-4G-4GP-CT-T	EN 50155 28-port L2 switch including 20 FE PoE ports, 4 Gigabit ports, 4 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	9.950,00 €
TN-4528B-20P-4GP-4GBP-CT-T	EN 50155 28-port L2 switch including 20 FE PoE ports, 4 Gigabit ports with bypass relay, 4 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	10.310,00 €
TN-4908-4GPoE-4GTX-WV-CT-T	Industrial secure router with 8 Gigabit Ethernet ports including 4 Gigabit PoE+ ports, total 50 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	8.524,00 €
TN-4908-4GTX-WV-CT-T	Industrial secure router with 4 Fast Ethernet ports, 4 Gigabit Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	6.453,00 €
TN-4908-8GTX-WV-CT-T	Industrial secure router with 8 Gigabit Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	7.631,00 €
TN-4908-ETBN-4GPoE-4GTXPB-WV-CT-T	IEC 61375 ETBN industrial secure router with 8 Gigabit Ethernet ports including 4 Gigabit PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 50 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	10.310,00 €
TN-4908-ETBN-4GTX-4GTXPB-WV-CT-T	IEC 61375 ETBN industrial secure router with 8 Gigabit Ethernet ports including 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	9.229,00 €
TN-4908-ETBN-4GTXPB-WV-CT-T	IEC 61375 ETBN industrial secure router with 4 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	8.029,00 €
TN-4908-ETBN-4TXBP-WV-CT-T	IEC 61375 ETBN industrial secure router with 4 Fast Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	6.798,00 €

TN-4908-ETBN-F-4GPoE-4GTXBP-WV-CT-T	IEC 61375 ETBN industrial secure firewall router with 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 50 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	10.625,00 €
TN-4908-ETBN-F-4GTX-4GTXBP-WV-CT-T	IEC 61375 ETBN industrial secure firewall router with 8 Gigabit Ethernet ports including 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	9.529,00 €
TN-4908-ETBN-F-4GTXBP-WV-CT-T	IEC 61375 ETBN industrial secure firewall router with 4 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	8.329,00 €
TN-4908-ETBN-F-4TXBP-WV-CT-T	IEC 61375 ETBN industrial secure firewall router with 4 Fast Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	7.098,00 €
TN-4908-WV-CT-T	Industrial secure router with 8 Fast Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	5.178,00 €
TN-4916-12PoE-4GTX-WV-CT-T	Industrial secure router with 12 Fast Ethernet PoE+ ports, 4 Gigabit Ethernet ports, total 95 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	7.654,00 €
TN-4916-4GTX-WV-CT-T	Industrial secure router with 12 Fast Ethernet ports, 4 Gigabit Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	7.173,00 €
TN-4916-8PoE-4GPoE-4GTX-WV-CT-T	Industrial secure router with 8 Fast Ethernet PoE+ ports, 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, total 95 W power budget for PoE+, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	9.514,00 €
TN-4916-ETBN-12PoE-4GTXBP-WV-CT-T	IEC 61375 ETBN industrial secure router with 12 Fast Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	9.304,00 €
TN-4916-ETBN-4GTXBP-WV-CT-T	IEC 61375 ETBN industrial secure router with 12 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	8.704,00 €
TN-4916-ETBN-8PoE-4GPoE-4GTXBP-WV-CT-T	IEC 61375 ETBN industrial secure router with 8 Fast Ethernet PoE+ ports, 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget for PoE+, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	11.150,00 €
TN-4916-ETBN-F-12PoE-4GTXBP-WV-CT-T	IEC 61375 ETBN industrial secure firewall router with 12 Fast Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	9.605,00 €
TN-4916-ETBN-F-4GTXBP-WV-CT-T	IEC 61375 ETBN industrial secure firewall router with 12 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	9.004,00 €
TN-4916-ETBN-F-8PoE-4GPoE-4GTXBP-WV-CT-T	IEC 61375 ETBN industrial secure firewall router with 8 Fast Ethernet PoE+ ports, 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget for PoE+, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	11.480,00 €
TN-5305A-WV-CT-T	EN 50155 unmanaged Ethernet switch with 5 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	644,00 €
TN-5305A-WV-T	EN 50155 unmanaged Ethernet switch with 5 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature	598,00 €
TN-5308A-8PoE-WV-CT-T	EN 50155 unmanaged Ethernet switch with 8 10/100BaseT(X) PoE ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	1.758,00 €
TN-5308A-8PoE-WV-T	EN 50155 unmanaged Ethernet switch with 8 10/100BaseT(X) PoE ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature	1.630,00 €

TN-5308A-WV-CT-T	EN 50155 unmanaged Ethernet switch with 8 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	1.265,00 €
TN-5308A-WV-T	EN 50155 unmanaged Ethernet switch with 8 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature	1.172,00 €
TN-5508A-8PoE-WV-CT-T	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	3.904,00 €
TN-5508A-8PoE-WV-T	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature	3.614,00 €
TN-5508A-WV-CT-T	Managed Ethernet switch with 8 10/100BaseT(X) ports with M12 connector, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature, conformal coating	3.066,00 €
TN-5508A-WV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature	2.838,00 €
TN-5510A-2GLSX-ODC-WV-CT-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 1000 BaseLSX Q-ODC® ports, 24 to 110 VDC dual power input, -40 to 75°C operating temperature, conformal coating	6.627,00 €
TN-5510A-2GLSX-ODC-WV-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 1000 BaseLSX Q-ODC® ports, 24-110 VDC dual power input, -40 to 75°C operating temperature	6.140,00 €
TN-5510A-2GTXP-WV-CT-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector with bypass relay function, 24 to 110 VDC dual power input, -40 to 75°C operating temperature, conformal coating	4.189,00 €
TN-5510A-2GTXP-WV-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector with bypass relay function, 24 to 110 VDC dual power input, -40 to 75°C operating temperature	3.881,00 €
TN-5510A-2GTX-WV-CT-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector, 24 to 110 VDC dual power input, -40 to 75°C operating temperature, conformal coating	4.013,00 €
TN-5510A-2GTX-WV-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector, 24 to 110 VDC dual power input, -40 to 75°C operating temperature	3.713,00 €
TN-5510A-8PoE-2GLSX-ODC-WV-CT-T	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector and 2 GE fiber ports, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	7.001,00 €
TN-5510A-8PoE-2GLSX-ODC-WV-T	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector and 2 GE fiber ports, power input 24 to 110 VDC, -40 to 75°C operating temperature	6.431,00 €
TN-5510A-8PoE-2GTXP-WV-CT-T	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector with bypass function, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	5.169,00 €
TN-5510A-8PoE-2GTXP-WV-T	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector with bypass function, power input 24 to 110 VDC, -40 to 75°C operating temperature	4.816,00 €
TN-5510A-8PoE-2GTX-WV-CT-T	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	4.996,00 €
TN-5510A-8PoE-2GTX-WV-T	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature	4.592,00 €
TN-5516A-8PoE-WV-CT-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	5.347,00 €
TN-5516A-8PoE-WV-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 24-110 VDC, -40 to 75°C operating temperature	4.957,00 €

TN-5516A-WV-CT-T	Layer 2 managed switch with 16 10/100BaseT(X) ports with M12 connector, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	3.998,00 €
TN-5516A-WV-T	Layer 2 managed switch with 16 10/100BaseT(X) ports with M12 connector, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature	3.698,00 €
TN-5518A-2GTXPB-WV-CT-T	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, 2 Gigabit Ethernet ports with bypass relay function, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	4.906,00 €
TN-5518A-2GTXPB-WV-T	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, 2 Gigabit Ethernet ports with bypass relay function, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature	4.541,00 €
TN-5518A-2GTX-WV-CT-T	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	4.819,00 €
TN-5518A-2GTX-WV-T	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, dual power input, 24-110 VDC, -40 to 75°C operating temperature	4.465,00 €
TN-5518A-8PoE-2GTXPB-WV-CT-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) M12 connectors with bypass function, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	6.501,00 €
TN-5518A-8PoE-2GTXPB-WV-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) M12 connectors with bypass function, 24 to 110 VDC, -40 to 75°C operating temperature	6.024,00 €
TN-5518A-8PoE-2GTX-WV-CT-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) M12 connectors, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	6.303,00 €
TN-5518A-8PoE-2GTX-WV-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) with M12 connectors, 24 to 110 VDC, -40 to 75°C operating temperature	5.836,00 €
TN-G4516-8GPoE-2XGPoE-2XGTXPB-WV-CT-T	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 2 10G Ethernet PoE+ ports, 2 10G Ethernet ports with bypass relay, 120 W PoE power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	12.409,00 €
TN-G4516-8GPoE-2XGPoE-2XGTXPB-WV-T	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 2 10G Ethernet PoE+ ports, 2 10G Ethernet ports with bypass relay, 120 W PoE power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature	12.024,00 €
TN-G4516-8GPoE-4XGPoE-WV-CT-T	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 4 10G Ethernet PoE+ ports, 120 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP40, conformal coating	12.544,00 €
TN-G4516-8GPoE-4XGPoE-WV-T	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 4 10G Ethernet PoE+ ports, 120 W PoE power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature	11.629,00 €
TN-G6512-8GPoE-WV-CT-T	Layer 2 Managed Ethernet switch, 8 10/100/1000BaseT(X) with 802.3at PoE+, 4 10/100/1000BaseT(X) M12 connectors, 24 to 110 VDC power input, -40 to 70°C operating temperature, conformal coating model	7.511,00 €
TN-G6512-8GPoE-WV-T	Layer 2 Managed Ethernet switch, 8 10/100/1000BaseT(X) ports with 802.3at PoE+ and 4 10/100/1000BaseT(X) M12 connectors, 24 to 110 VDC power input, -40 to 70°C operating temperature	6.953,00 €
TRC-190-AC	Rack chassis, 2U, single 110 to 240 VAC input, with 19 slots on front panel	933,00 €
TRC-190-DC-48	Rack chassis, 2U, single 36 to 53 VDC input, with 19 slots on front panel	1.178,00 €
TRC-2190-AC	2U rackmount chassis, with a single 110 to 240 VAC input, 18 slots on the front panel, and CSM-MN01 managed module	1.534,00 €
TRC-2190-DC-48V	2U rackmount chassis, with a single 36 to 53 VDC input, 18 slots on the front panel, and CSM-MN01 managed module	1.795,00 €

TSN-G5004	TSN-capable managed Ethernet switch with 4 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	2.245,00 €
TSN-G5008-2GTXSFP	TSN-capable managed Ethernet switch with 6 10/100/1000BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -10 to 60°C operating temperature	3.208,00 €
TSN-G5016-4GS-SoMD-LV-T	TSN-capable managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 4 fixed 1000BaseSFP ports, -40 to 70°C operating temperature	5.606,00 €
TSN-G5016-4XGS-SoMD-LV-T	TSN-capable managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 4 fixed 10GbE SFP+ ports, -40 to 70°C operating temperature	10.424,00 €
TWS-3010-APL-8PS-2GC-T	Managed Ethernet-APL field switch with 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 8 10BASE-T1L spur ports with APL power classes A and C, dual 24/48 VDC power supplies, -40 to 75°C operating temperature	3.585,00 €
TWS-3010-SPE-8PB-2GC-T	Managed single-pair Ethernet switch with 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 8 10BASE-T1L ports with IEC 63171-2 SPE connectors and PoDL power classes 10, 11, and 12, dual 24 VDC power supplies, -40 to 75°C operating temperature	1.832,00 €
UC-1222A	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 60°C operating temperature	1.016,00 €
UC-2101-LX	Mini RISC-based embedded computer with 600 MHz processor, 1 serial port and 1 LAN port	573,00 €
UC-2102-LX	Mini RISC-based embedded computer with 600 MHz processor and 2 LAN ports	573,00 €
UC-2104-LX	Mini RISC-based embedded computer with 600 MHz processor, 1 LAN port, 1 Mini PCIe slot for wireless capability	604,00 €
UC-2111-LX	Compact RISC-based embedded computer with 600 MHz processor, 2 serial ports, 2 LAN ports, 1 microSD slot	699,00 €
UC-2112-LX	Compact RISC-based embedded computer with 1 GHz processor, 2 serial ports, 2 LAN ports (1 Gb Ethernet), and microSD slot	834,00 €
UC-2112-T-LX	Compact RISC-based embedded computer with 1 GHz processor, 2 serial ports, 2 Ethernet ports (1 Gigabit Ethernet), microSD slot and -40 to 75°C operating temperature	935,00 €
UC-2222A-T	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10) , -40 to 75°C operating temperature	1.097,00 €
UC-2222A-T-AP	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot with LTE Cat. 4 module for the Asia-Pacific region preinstalled, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	1.459,00 €
UC-2222A-T-CN	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot for wireless module, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	1.134,00 €
UC-2222A-T-EU	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot with LTE Cat. 4 module for the European region preinstalled, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	1.459,00 €
UC-2222A-T-US	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot with LTE Cat. 4 module for the U.S. region preinstalled, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	1.459,00 €

UC-3100 Antenna Set	4 dBi at 1575 MHz to 1610 MHz, SMA (male), active GPS/GLONASS, adhesive-type antenna with 20-cm cable; 2 4 dBi at 2.4 GHz or 5 dBi at 5 GHz, RP-SMA (female), omnidirectional antennas; 2 1.5 dBi 698 to 960 MHz or 1710 to 2700 MHz, SMA (male), LTE, swivel-type omnidirectional portable antennas	68,00 €
UC-3100 DIN-Rail Kit	DIN-rail kit with screws	14,00 €
UC-3100 Wall-Mounting Kit	Wall-mounting kit with screws	9,00 €
UC-3101-T-AP-LX	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -40 to 70°C operating temperature	1.225,00 €
UC-3101-T-AU-LX	Arm-based computer for the AUS and NZ regions with built-in LTE Cat. 1 module, 1 GHz processor, 512 MB RAM, 4 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -30 to 70°C operating temperature	1.170,00 €
UC-3101-T-EU-LX	Arm-based computer for the EU region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -40 to 70°C operating temperature	1.225,00 €
UC-3101-T-US-LX	Arm-based computer for the U.S. region (AT&T, Verizon) with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -40 to 70°C operating temperature	1.225,00 €
UC-3111-T-AP-LX	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	1.659,00 €
UC-3111-T-AP-LX-NW	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	1.581,00 €
UC-3111-T-AU-LX	Arm-based computer for the AUS and NZ regions with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 512 MB RAM, 4 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -30 to 70°C operating temperature	1.589,00 €
UC-3111-T-EU-LX	Arm-based computer for the EU region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	1.659,00 €
UC-3111-T-EU-LX-NW	Arm-based computer for the EU region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	1.581,00 €
UC-3111-T-US-LX	Arm-based computer for the U.S. region (AT&T, Verizon) with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	1.659,00 €
UC-3111-T-US-LX-NW	Arm-based computer for the U.S. region (AT&T, Verizon) with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	1.581,00 €
UC-3121-T-AP-LX	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	1.587,00 €
UC-3121-T-AU-LX	Arm-based computer for the AUS and NZ regions with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 512 MB RAM, 4 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, -30 to 70°C operating temperature	1.519,00 €
UC-3121-T-EU-LX	Arm-based computer for the EU region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	1.587,00 €
UC-3121-T-US-LX	Arm-based computer for the U.S. region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	1.587,00 €

UC-3420A-T-LTE	Arm® Cortex®-A53 quad-core 64-bit 1.4 GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, built-in LTE Cat. 4 module, 9 to 48 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	1.546,00 €
UC-3424A-T-LTE	Arm® Cortex®-A53 quad-core 64-bit 1.4 GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 2 CAN ports, 1 USB 2.0 port, built-in LTE Cat. 4 module, 9 to 48 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	1.707,00 €
UC-3430A-T-LTE-WiFi	Arm® Cortex®-A53 quad-core 64-bit 1.4 GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, built-in LTE Cat. 4 and Wi-Fi modules, 9 to 48 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	1.760,00 €
UC-3434A-T-LTE-WiFi	Arm® Cortex®-A53 quad-core 64-bit 1.4 GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 2 CAN ports, 1 USB 2.0 port, built-in LTE Cat. 4 and Wi-Fi modules, 9 to 48 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	1.930,00 €
UC-4400A Wall-mounting Kit	Wall-mounting kit with 2 plates (44.8 x 99 x 5.7 mm each) and 5 M3 x 5 mm screws for the UC-4400A Series	24,00 €
UC-4400A-LTE-CAT4-WW	LTE package with a Telit LE910C4-WWxD LTE Cat. 4 mPCIe card for global coverage, 2 thermal pads, 2 heat sinks, 3 M2.5 x 5 mm screws for UC-443xA models	168,00 €
UC-4400A-WLAN22-AX	Wi-Fi 6E package with an EMWICOM WMX7205-1 Wi-Fi 6E M.2 card, 2 thermal pads, 2 heat sinks, 2 M2.5 x 5 mm screws for UC-443xA/445xA models	192,00 €
UC-4410A-T	Arm Cortex-A53 quad-core 1.6 GHz industrial computer with 2 Ethernet ports, 2 serial ports, 1 CAN port, 4 DIs, 4 DOs, -40 to 75°C operating temperature	1.391,00 €
UC-4414A-I-T	Arm Cortex-A53 quad-core 1.6 GHz industrial computer with 2 Ethernet ports, 4 serial ports (2 with 2-kV isolation), 2 CAN ports, 4 DIs, 4 DOs, -40 to 75°C operating temperature	1.736,00 €
UC-4430A-T	Arm Cortex-A53 quad-core 1.6 GHz industrial computer with 2 Ethernet ports, 2 serial ports, 1 CAN port, 4 DIs, 4 Dos, 2 expansion slots (for Wi-Fi 6E and LTE modules), -40 to 70°C operating temperature	1.565,00 €
UC-4434A-I-T	Arm Cortex-A53 quad-core 1.6 GHz industrial computer 2 Ethernet ports, 4 serial ports (2 with 2-kV isolation), 2 CAN ports, 4 DIs, 4 DOs, 2 expansion slots (for Wi-Fi 6E and LTE modules), -40 to 70°C operating temperature	1.913,00 €
UC-4450A-T-5G	Arm Cortex-A53 quad-core 1.6 GHz industrial computer with 2 Ethernet ports, 2 serial ports, 1 CAN port, 4 DIs, 4 DOs, 5G NR module built-in, 1 expansion slot for a Wi-Fi 6E module, -40 to 70°C operating temperature	2.865,00 €
UC-4454A-T-5G	Arm Cortex-A53 quad-core 1.6 GHz industrial computer with 2 Ethernet ports, 4 serial ports (2 with 2-kV isolation, 2 CAN ports, 4 DIs, 4 DOs, 5G NR built-in, 1 expansion slot for a Wi-Fi 6E module, -40 to 70°C operating temperature	3.178,00 €
UC-5101-LX	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 4 DIs, 4 DOs, 1 USB port, -10 to 60°C operating temperature range	1.170,00 €
UC-5101-T-LX	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 4 DIs, 4 DOs, 1 USB port, -40 to 85°C operating temperature range	1.460,00 €
UC-5102-LX	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 4 DIs, 4 DOs, 1 USB port, -10 to 60°C operating temperature	1.388,00 €
UC-5102-T-LX	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 4 DIs, 4 DOs, 1 USB port, -40 to 85°C operating temperature	1.663,00 €
UC-5111-LX	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 2 CAN ports, 4 DIs, 4 DOs, 1 USB port, -10 to 60°C operating temperature range	1.460,00 €

UC-5111-T-LX	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 2 CAN ports, 4 DIs, 4 DOs, 1 USB port, -40 to 85°C operating temperature range	1.756,00 €
UC-5112-LX	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 2 CAN ports, 4 DIs, 4 DOs, 1 USB port, -10 to 60°C operating temperature	1.663,00 €
UC-5112-T-LX	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 2 CAN ports, 4 DIs, 4 DOs, 1 USB port, -40 to 85°C operating temperature	1.960,00 €
UC-8100 LTE-CAT4-EU	Telit LE910C4-EU LTE Cat. 4 mini card with 2 M2 screws for the EMEA region	300,00 €
UC-8100-ME Din-Rail Kit	DIN-rail mounting kit for UC-8100-ME Series	45,00 €
UC-8100-ME Wall Mount Kit	Wall-mounting kit with screws	34,00 €
UC-8112-LX	Arm-based wireless-enabled DIN-rail industrial computer with 1 GHz CPU, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot	881,00 €
UC-8131-LX	Arm-based wireless-enabled DIN-rail industrial computer with 300 MHz CPU, 2 Ethernet, 1 Serial port	689,00 €
UC-8132-LX	Arm-based wireless-enabled DIN-rail industrial computer with 300 MHz CPU, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot	755,00 €
UC-8162-LX	Arm-based wireless-enabled DIN-rail industrial computer with 600 MHz CPU, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot	775,00 €
UC-8200 Wall-mounting Kit	Wall-mounting kit for UC-8200 with 4 M3 screws	39,00 €
UC-8200-WLAN22-AC	Wireless package for UC-8200 V2.0 or later with Wi-Fi module, 2 screws, 2 spacers, 1 heat sink, 1 pad	140,00 €
UC-8210 DIN-rail Mounting Kit	DIN-rail mounting kit for UC-8210 with 4 M3 screws	16,00 €
UC-8210-T-LX-S	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, 1 CAN port, 4 DIs, 4 DOs, -40 to 85°C operating temperature	1.258,00 €
UC-8220 DIN-rail Mounting Kit	DIN-rail mounting kit for UC-8220 with 4 M3 screws	16,00 €
UC-8220-T-LX	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with 2 expansion slots for a Wi-Fi and LTE module, 1 CAN port, 4 DIs, 4 DOs, -40 to 85°C operating temperature	1.554,00 €
UC-8220-T-LX-AP-S	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, Asia-Pacific region LTE Cat. 4 module preinstalled, 1 Mini PCIe expansion slot for a Wi-Fi module, 1 CAN port, 4 DIs, 4 DOs, -40 to 70°C operating temperature	2.089,00 €
UC-8220-T-LX-EU-S	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, EU region LTE Cat. 4 module preinstalled, 1 Mini PCIe expansion slot for a Wi-Fi module, 1 CAN port, 4 DIs, 4 DOs, -40 to 70°C operating temperature	2.089,00 €
UC-8220-T-LX-US-S	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, US region LTE Cat. 4 module preinstalled, 1 Mini PCIe expansion slot for a Wi-Fi module, 1 CAN port, 4 DIs, 4 DOs, -40 to 70°C operating temperature	2.089,00 €
UC-8410A DIN-rail Kit	DIN-rail kit with 6 M3 screws (also included in the UC-8410A Series package)	23,00 €
UC-8410A LTE-CAT4-EU	Telit LE910C4-EU LTE Cat. 4 mini card with 2 M2.5 screws for the EMEA region, compatible with UC-8410A hardware rev. 2.1.0 and higher	300,00 €
UC-8410A-LX	Arm-based wireless-enabled wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 SD slot with 1 GB card preinstalled, 512 MB DDR3L RAM, 8 serial ports, 4 DIs, 4 DOs, 3 Ethernet ports, wireless enabled, 1 mSATA slot, 1 USB port, Debian 8, -10 to 60°C operating temperature	1.732,00 €

UC-8410A-NW-LX	Arm-based wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 GB DDR3L RAM, 8 serial ports, 4 DIs, 4 DOs, 3 Ethernet ports, 1 mSATA slot, 1 USB port, Debian 8, -10 to 60°C operating temperature	1.694,00 €
UC-8410A-NW-T-LX	Arm-based wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 GB DDR3L RAM, 8 serial ports, 4 DIs, 4 DOs, 3 Ethernet ports, 1 mSATA slot, 1 USB port, Debian 8, -40 to 75°C operating temperature	2.131,00 €
UC-8410A-T-LX	Arm-based wireless-enabled wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 SD slot with 1 GB card preinstalled, 512 MB DDR3L RAM, 8 serial ports, 4 DIs, 4 DOs, 3 Ethernet ports, wireless enabled, 1 mSATA slot, 1 USB port, Debian 8, -40 to 75°C operating temperature	2.172,00 €
UC-8600A Din-rail Kit	DIN-rail mounting kit with 1 plate (90 x 45 mm), 1 extension bracket (25 x 16 mm), 5 M3 x 4 mm screws for the UC 8600A Series	25,00 €
UC-8600A-WLAN	EMWICOM WMX7205-1 Wi-Fi 6E M.2 card package for the UC-8600A Series	192,00 €
UC-8620A-LTE	Telit LE910C4-WWxD LTE Cat. 4 mPCIe card package for the UC-8620A models	210,00 €
UC-8620A-M.2 SSD	M.2 SSD thermal package with 3 thermal pads, 1 heat sink, 5 screws for the UC-8620A models	39,00 €
UC-8620A-T	Arm Cortex-A72 dual-core 1.5 GHz box-type computer with 4 Ethernet ports, 8 serial ports, 2 CAN ports, 4 DIs, 4 DOs, 1 M.2 M key socket for SSD, 1 mPCIe slot for the LTE module, -40 to 75°C operating temperature	1.697,00 €
UC-8630A-LTE	Telit LE910C4-WWxD LTE Cat. 4 mPCIe card package for the UC-8630A models	210,00 €
UC-8630A-M.2 SSD	M.2 SSD thermal package with 1 thermal pad, 1 screw for the UC-8630A models	8,00 €
UC-8630A-T	Arm Cortex-A72 dual-core 1.5 GHz box-type computer with 4 Ethernet ports, 8 serial ports, 2 CAN ports, 4 DIs, 4 DOs, 1 M.2 M key socket for SSD, 1 mPCIe slot for the LTE module, 1 M.2 E key socket for Wi-Fi module, -40 to 70°C operating temperature	1.892,00 €
UC-LTE-CAT1-EU	LTE cellular module with 2 M2 and 2 M2.5 mounting screws for EMEA bands 1, 3, 7, 8, 20, 28A	296,00 €
UC-WiFi-USB	802.11 a/b/g/n/ac, 2.4/5 GHz Wi-Fi module with 2 each of M2 and M2.5 screws	107,00 €
UPort 1110	1-port RS-232 USB-to-serial converter	58,00 €
UPort 1130	1-port RS-422/485 USB-to-serial converter	105,00 €
UPort 1130I	1-port RS-422/485 USB-to-serial converter with 2 kV optical isolation	200,00 €
UPort 1150	1-port RS-232/422/485 USB-to-serial converter	156,00 €
UPort 1150I	1-port RS-232/422/485 USB-to-serial converter with optical isolation protection	265,00 €
UPort 1250-G2	2-port RS-232/422/485 USB-to-serial converter, 0 to 60°C operating temperature	228,00 €
UPort 1250-G2-T	2-port RS-232/422/485 USB-to-serial converter, -40 to 75°C operating temperature	283,00 €
UPort 1250I-G2	2-port RS-232/422/485 USB-to-serial converter with 2 kV isolation protection, 0 to 60°C operating temperature	400,00 €
UPort 1250I-G2-T	2-port RS-232/422/485 USB-to-serial converter with 2 kV isolation protection, -40 to 75°C operating temperature	504,00 €
UPort 1410-G2	USB to 4-port RS-232 converter, 0 to 60°C operating temperature	355,00 €
UPort 1450-G2	USB to 4-port RS-232/422/485 converter, 0 to 60°C operating temperature	431,00 €
UPort 1450-G2-T	USB to 4-port RS-232/422/485 converter, -40 to 75°C operating temperature	541,00 €
UPort 1450I-G2	USB to 4-port RS-232/422/485 converter with 2 kV isolation protection, 0 to 60°C operating temperature	789,00 €
UPort 1450I-G2-T	USB to 4-port RS-232/422/485 converter with 2 kV isolation protection, -40 to 75°C operating temperature	985,00 €
UPort 1610-16	USB to 16-port RS-232 serial hub	967,00 €
UPort 1610-8-G2	USB to 8-port RS-232 converter, 0 to 60°C operating temperature	504,00 €
UPort 1650-16	USB to 16-port RS-232/422/485 serial hub	1.335,00 €
UPort 1650-8-G2	USB to 8-port RS-232/422/485 converter, 0 to 60°C operating temperature	756,00 €

UPort 1650-8-G2-Hub	USB to 8-port RS-232/422/485 converter with 3 extra downstream USB ports, 0 to 60°C operating temperature	977,00 €
UPort 1650-8-G2-T	USB to 8-port RS-232/422/485 converter, -40 to 75°C operating temperature	942,00 €
UPort 1650I-8-G2	USB to 8-port RS-232/422/485 converter with 2 kV isolation protection, 0 to 60°C operating temperature	1.357,00 €
UPort 1650I-8-G2-T	USB to 8-port RS-232/422/485 converter with 2 kV isolation protection, -40 to 75°C operating temperature	1.699,00 €
UPort 204	4-port entry-level USB hub, adaptor included	265,00 €
UPort 204A	4-port general-purpose USB 3.2 hubs	283,00 €
UPort 207	7-port entry-level USB hub, adaptor included	321,00 €
UPort 207A	7-port general-purpose USB 3.2 hubs	342,00 €
UPort 2210	2-port RS-232 USB-to-serial converter	226,00 €
UPort 2410	4-port RS-232 USB-to-serial converter	296,00 €
UPort 404	4-port industrial USB hub, adaptor included, 0 to 60°C operating temperature	380,00 €
UPort 404A	4-port industrial-grade USB 3.2 hubs, 0 to 60°C operating temperature	397,00 €
UPort 404A-T	4-port industrial-grade USB 3.2 hubs, -40 to 85°C operating temperature	535,00 €
UPort 404-T w/o Adapter	4-port industrial USB hub, without adapter, -40 to 85°C operating temperature	473,00 €
UPort 407	7-port industrial USB hub, adaptor included, 0 to 60°C operating temperature	451,00 €
UPort 407A	7-port industrial-grade USB 3.2 hubs, 0 to 60°C operating temperature	480,00 €
UPort 407A-T	7-port industrial-grade USB 3.2 hubs, -40 to 85°C operating temperature	627,00 €
UPort 407-T w/o Adapter	7-port industrial USB hub, without adapter, -40 to 85°C operating temperature	577,00 €
V1200 Desk-mounting Kit	Desk-mounting kit with 2 plates (44.8 x 99 x 5.7 mm), 4 screws (M3 x 5 mm) for the V1200 Series	51,00 €
V1200 Din-rail Kit	DIN-rail mounting kit with 1 plate, 5 screws (M3 x 4 mm) for the V1200 Series	41,00 €
V1200-5G	Telit FN990A28W 5G module, 5 coaxial cables (I-PEX MHF male connector to QMA female connector), 2 thermal pads, 1 heat sink for the V1200 Series	1.201,00 €
V1200-LTECat4-GL	Telit LE910C4 LTE Cat. 4 mPCIe card, 3 coaxial cables (I-PEX MHF male connector to QMA female connector), 2 thermal pads, 1 heat sink for the V1200 Series	308,00 €
V1200-WLAN22-AX	Wi-Fi 6 (802.11ax) module, 2 coaxial cables (I-PEX 4 MHF male connector to QMA female connector), 1 thermal pad, 1 heat sink for the V1200 Series	246,00 €
V1202-CT-T	Arm-based compact rail computer with 2 GbE ports, 1 USB port, 1 microSD slot, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	2.377,00 €
V1222-CT-T	Arm-based compact rail computer with 2 GbE ports, 2 serial ports, 1 USB port, 1 microSD slot, Wi-Fi 6 and 5G expansion and dual-SIM support, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	2.566,00 €
V1222-W-CT-T	Arm-based compact rail computer with 2 GbE ports, 2 serial ports, 1 USB port, 1 microSD slot, preinstalled Wi-Fi 6 and 5G modules, dual-SIM support, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	4.631,00 €
V2201 Wi-Fi mini Card	SparkLAN WPEA-252NI Wi-Fi mini card with 4 black screws	410,00 €
V2201-E1-T	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, -40 to 85°C operating temperature	3.012,00 €
V2201-E1-T-LX	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, Linux Debian 8 preinstalled, -40 to 85°C operating temperature	3.442,00 €
V2201-E1-W-T	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, Wi-Fi and cellular antenna SMA-type connectors, -40 to 85°C operating temperature	3.221,00 €

V2201-E2-T	x86 embedded computer with Intel Atom® E3826 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, -40 to 85°C operating temperature	3.150,00 €
V2201-E2-W-T	x86 embedded computer with Intel Atom® E3826 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, 5 wireless SMA connectors, -40 to 85°C operating temperature	3.263,00 €
V2201-E4-T	x86 embedded computer with Intel Atom® E3845, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, -40 to 70°C operating temperature	3.296,00 €
V2201-E4-W-T	x86 embedded computer with Intel Atom® E3845 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, 5 wireless SMA connectors, -40 to 70°C operating temperature	3.469,00 €
V2201-E4-W-T-LX	x86 embedded computer with Intel Atom® E3845 processor, 4 GB RAM, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot with 16 GB card preinstalled, 1 mSATA slot with 32 GB preinstalled, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, 5 wireless SMA connectors, Linux Debian 8 preinstalled, -40 to 70°C operating temperature	3.362,00 €
V2400 Cover-DB9	Dual DB9 expansion cover, 4 male hex standoff spacer pillars	24,00 €
V2400 Isolated Wall Mount Kit	Wall-mounting kit with isolation protection, 2 wall-mounting brackets, 4 screws	67,00 €
V2400-WLAN22-AC	SparkLAN WPEQ-261ACNI (BT) Wi-Fi mini card, 4 black screws	169,00 €
V2403C-KL1-T	x86 computer with Intel® 7th Gen Celeron® 3965U 2.2 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	3.790,00 €
V2403C-KL3-T	x86 computer with Intel® 7th Gen Core™ i3-7100U 2.4 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2,5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	4.374,00 €
V2403C-KL5-T	x86 computer with Intel® 7th Gen Core™ i5-7300U 3.5 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	5.097,00 €
V2403C-KL7-T	x86 computer with Intel® 7th Gen Core™ i7-7600U 3.9 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	5.673,00 €
V2403C-LTECat4-AP	Telit LE910C4 LTE Cat. 4 mini card for the Asia-Pacific region, 3 SMA antenna cables	255,00 €
V2403C-LTECat4-EU	Telit LE910C4 LTE Cat. 4 mini card for Europe, 3 SMA antenna cables	255,00 €
V2403C-LTECat4-NF	Telit LE910C4 LTE Cat. 4 mini card for North America, 3 SMA antenna cables	255,00 €
V2406C TPM2.0 CT Module	SLB9665XT2.0 TPM 2.0 module with conformal coating	56,00 €
V2406C TPM2.0 Module	SLB9665XT2.0 TPM 2.0 module without conformal coating	52,00 €
V2406C Wall mount kit	Single-bracket wall-mounting kit for the V2406C Series with 8 M3 x 6 mm screws	52,00 €
V2406C-KL1-CT-T	x86 computer with Intel® 7th Gen Celeron® 3965U 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature, conformal coating	6.655,00 €

V2406C-KL1-T	x86 computer with Intel® 7th Gen Celeron® 3965U 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	5.546,00 €
V2406C-KL3-T	x86 computer with Intel® 7th Gen Core™ i3-7100U 2.4 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	6.379,00 €
V2406C-KL5-T	x86 computer with Intel® 7th Gen Core™ i5-7300U 2.6 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	7.348,00 €
V2406C-KL7-CT-T	x86 computer with Intel® 7th Gen Core™ i7-7600U 2.8 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature, conformal coating	10.385,00 €
V2406C-KL7-T	x86 computer with Intel® 7th Gen Core™ i7-7600U 2.8 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	8.663,00 €
V2406C-LTECat4-AP	Telit LE910C4 LTE Cat. 4 mini card for the Asia-Pacific region	255,00 €
V2406C-LTECat4-EU	Telit LE910C4 LTE Cat. 4 mini card for European region	255,00 €
V2406C-LTECat4-NF	Telit LE910C4 LTE Cat. 4 mini card for the North American region	255,00 €
V2406C-WL1-CT-T	x86 computer with Intel 8th Celeron 4305UE 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature, conformal coating	5.673,00 €
V2406C-WL1-T	x86 computer with Intel 8th Gen Celeron 4305UE 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature	4.704,00 €
V2406C-WL3-T	x86 computer with Intel 8th Gen Core™ i3-8145UE 3.90 GHz processor, 1 HDMI port, 1 VGA port, 2 Gigabit Ethernet ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature	5.455,00 €
V2406C-WL5-T	x86 computer with Intel 8th Gen Core™ i5-8365UE 4.1 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature	6.308,00 €
V2406C-WL7-CT-T	x86 computer with Intel 8th Gen Core™ i7-8665UE 4.4 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature, conformal coating	9.063,00 €
V2406C-WL7-T	x86 computer with Intel 8th Gen Core™ i7-8665UE 4.4 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature	7.547,00 €
V3200-LTECat4-GL	Telit LE910C4 LTE Cat. 4 mPCIe card, 3 coaxial cables (I-PEX MHF male connector to QMA female connector, 160 mm), 1 thermal pad	301,00 €
V3200-WLAN22-AC	Wi-Fi 5 (802.11ac) module, 1 mPCIe adapter bracket with 4 screws, 2 coaxial cables (I-PEX MHF male connector to QMA female connector, 160 mm), 1 thermal pad	301,00 €

V3200-WLAN22-AX	Wi-Fi 6 (802.11ax) module, 2 coaxial cables (I-PEX 4 MHF male connector to QMA female connector, 160 mm), 1 thermal pad	430,00 €
V3210-TL1-4L-T	x86 computer with Intel® Celeron® 6305E processor, 4 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD/HDD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature	5.873,00 €
V3210-TL1-8L-CT-T	x86 computer with Intel® Celeron® 6305E processor, 8 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	6.874,00 €
V3210-TL3-4L-CT-T	x86 computer with Intel® Core™ i3-1115G4E processor, 4 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	6.588,00 €
V3210-TL3-4L-T	x86 computer with Intel® Core™ i3-1115G4E processor, 4 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature	6.302,00 €
V3210-TL5-8L-CT-T	x86 computer with Intel® Core™ i5-1145G7E processor, 8 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	7.803,00 €
V3210-TL7-4L-T	x86 computer with Intel® Core™ i7-1185GRE processor, 4 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature	8.703,00 €
V3210-TL7-8L-CT-T	x86 computer with Intel® Core™ i7-1185GRE processor, 8 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	10.375,00 €
V3210-TL7-8L-TSN-CT-T	x86 computer with Intel® Core™ i7-1185GRE processor, 8 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, native TSN support, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	10.518,00 €
V3400-5G-GL	Telit FN990A 5G module, 5 coaxial cables (I-PEX MHF male connector to QMA female connector), 2 thermal pads for the V3400 Series	1.201,00 €
V3400-LTECat4-GL	Telit LE910C4 LTE Cat. 4 mPCIe card, 3 coaxial cables (I-PEX MHF male connector to QMA female connector), 2 thermal pads, 1 heat sink for the V3400 Series	308,00 €
V3400-WLAN22-AC	Wi-Fi 5 (802.11ac) module, 1 mPCIe adapter bracket with 4 screws, 2 coaxial cables (I-PEX MHF male connector to QMA female connector), 2 thermal pads for the V3400 Series	241,00 €
V3400-WLAN22-AX	Wi-Fi 6 (802.11ax) module, 2 coaxial cables (I-PEX 4 MHF male connector to QMA female connector), 2 thermal pads for the V3400 Series	246,00 €
V3404-TL3-W-CT-T	x86 computers with Intel® Core™ i3-1115G4E processor, 4 GbE ports, 2 serial ports, 2 DIs, 2 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 VGA port, 2 hot-swappable HDD/SSD slots, multiple expansion slots for wireless modules, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	9.239,00 €
V3404-TL7-W-CT-T	x86 computers with Intel® Core™ i7-1185G7E processor, 4 GbE ports, 2 serial ports, 2 DIs, 2 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 VGA port, 2 hot-swappable HDD/SSD slots, multiple expansion slots for wireless modules, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	11.054,00 €
V3408-TL3-W-CT-T	x86 computers with Intel® Core™ i3-1115G4E processor, 8 GbE ports, 2 serial ports, 2 DIs, 2 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 VGA port, 2 hot-swappable HDD/SSD slots, multiple expansion slots for wireless modules, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	10.082,00 €
V3408-TL7-W-CT-T	x86 computers with Intel® Core™ i7-1185G7E processor, 8 GbE ports, 2 serial ports, 2 DIs, 2 DOs, 2 USB 3.0 ports, 1 HDMI port, 1 VGA port, 2 hot-swappable HDD/SSD slots, multiple expansion slots for wireless modules, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	11.897,00 €

VP-06TC1L	Top cover of VPort P06-1MP-M12 (LED)	46,00 €
VP-06TC2CS	Top cover of VPort 06-2L, coating dome cover, smoked dome	78,00 €
VP-DP01	silica gel dry pack (2 x 0.6 g) with sticker	7,00 €
VP-DP02	15 g dry pack with hook-and-loop fastener	7,00 €
VP-FMK1	Flush-mounting kit for the VPort P16	171,00 €
VP-FP1	Fixed plate for mounting the VPort P06-1MP-M12	21,00 €
VP-FP2	Fixed plate for mounting the VPort 06	20,00 €
VPort 06-2L28M	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, 24 VDC, 2.8 mm lens, -25 to 55°C operating temperature	1.266,00 €
VPort 06-2L28M-T	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, 24 VDC, 2.8 mm lens, -40 to 70°C operating temperature	1.494,00 €
VPort 06-2L36M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 3.6 mm lens, -25 to 55°C operating temperature	1.268,00 €
VPort 06-2L36M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 3.6 mm lens, -40 to 70°C operating temperature	1.456,00 €
VPort 06-2L42M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 4.2 mm lens, -25 to 55°C operating temperature	1.268,00 €
VPort 06-2L42M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 4.2 mm lens, -40 to 70°C operating temperature	1.456,00 €
VPort 06-2L60M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 6.0 mm lens, -25 to 55°C operating temperature	1.251,00 €
VPort 06-2L60M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 6.0 mm lens, -40 to 70°C operating temperature	1.456,00 €
VPort 06-2L80M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 8.0 mm lens, -25 to 55°C operating temperature	1.268,00 €
VPort 06-2L80M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 8.0 mm lens, -40 to 70°C operating temperature	1.456,00 €
VPort 06-2M28M	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, 24 VDC, 2.8 mm lens, -25 to 55°C operating temperature	1.328,00 €
VPort 06-2M28M-T	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, 24 VDC, 2.8 mm lens, -40 to 70°C operating temperature	1.522,00 €
VPort 06-2M36M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 3.6 mm lens, -25 to 55°C operating temperature	1.371,00 €
VPort 06-2M36M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 3.6 mm lens, -40 to 70°C operating temperature	1.557,00 €
VPort 06-2M42M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 4.2 mm lens, -25 to 55°C operating temperature	1.371,00 €
VPort 06-2M42M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 4.2 mm lens, -40 to 70°C operating temperature	1.557,00 €
VPort 06-2M60M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 6.0 mm lens, -25 to 55°C operating temperature	1.371,00 €
VPort 06-2M60M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 6.0 mm lens, -40 to 70°C operating temperature	1.557,00 €
VPort 06-2M80M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 8.0 mm lens, -25 to 55°C operating temperature	1.371,00 €
VPort 06-2M80M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 8.0 mm lens, -40 to 70°C operating temperature	1.557,00 €
VPort 06EC-2V36M	EN50155, 1080P, day and night outdoor IP camera, 3.6 mm lens, -25 to 55°C operating temperature	2.685,00 €
VPort 06EC-2V36M-CT	EN50155, 1080P, day & night outdoor IP camera, 3.6 mm lens, -25 to 55°C operating temperature, conformal coating	3.228,00 €
VPort 06EC-2V36M-CT-T	EN50155, 1080P, day & night outdoor IP camera, 3.6 mm lens, -40 to 70°C operating temperature, conformal coating	3.464,00 €
VPort 06EC-2V36M-T	EN50155, 1080P, day & night outdoor IP camera, 3.6 mm lens, -40 to 70°C operating temperature	2.886,00 €

VPort 06EC-2V42M	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -25 to 55°C operating temperature	2.685,00 €
VPort 06EC-2V42M-CT	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -25 to 55°C operating temperature, conformal coating	3.228,00 €
VPort 06EC-2V42M-CT-T	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -40 to 70°C operating temperature, conformal coating	3.464,00 €
VPort 06EC-2V42M-T	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -40 to 70°C operating temperature	2.886,00 €
VPort 06EC-2V60M	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -25 to 55°C operating temperature	2.685,00 €
VPort 06EC-2V60M-CT	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -25 to 55°C operating temperature, conformal coating	3.228,00 €
VPort 06EC-2V60M-CT-T	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -40 to 70°C operating temperature, conformal coating	3.464,00 €
VPort 06EC-2V60M-T	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -40 to 70°C operating temperature	2.886,00 €
VPort 06EC-2V80M	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -25 to 55°C operating temperature	2.685,00 €
VPort 06EC-2V80M-CT	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -25 to 55°C operating temperature, conformal coating	3.228,00 €
VPort 06EC-2V80M-CT-T	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -40 to 70°C operating temperature, conformal coating	3.464,00 €
VPort 06EC-2V80M-T	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -40 to 70°C operating temperature	2.886,00 €
VPort 461A	Full Motion, 1-ch industrial video encoder, 2 10/100BaseT(X) Ethernet ports, -25 to 60°C operating temperature	1.085,00 €
VPort 461A-T	Full Motion, 1-ch industrial video encoder, 2 10/100BaseT(X) Ethernet ports, -40 to 75°C operating temperature	1.287,00 €
VPort 464	4-channel H.264/MJPEG industrial video encoder, 2 10/100/1000BaseT(X) Ethernet ports, -25 to 60°C operating temperature	2.278,00 €
VPort 464-T	4-channel H.264/MJPEG industrial video encoder, 2 10/100/1000BaseT(X) Ethernet ports, -40 to 75°C operating temperature	2.469,00 €
VPort P06-1MP-M12-CAM28	EN 50155, HD image, compact IP camera, M12 connector, 1 audio input, PoE, 2.8 mm lens, -25 to 55°C operating temperature	1.023,00 €
VPort P06-1MP-M12-CAM28-T	EN 50155, HD image, compact IP camera, M12 connector, 1 audio input, PoE, 2.8 mm lens, -40 to 70°C operating temperature	1.225,00 €
VPort P06-1MP-M12-CAM36	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 3.6 mm lens, -25 to 55°C operating temperature	1.032,00 €
VPort P06-1MP-M12-CAM36-T	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 3.6 mm lens, -40 to 70°C operating temperature	1.236,00 €
VPort P06-1MP-M12-CAM42	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 4.2 mm lens, -25 to 55°C operating temperature	1.032,00 €
VPort P06-1MP-M12-CAM42-T	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 4.2 mm lens, -40 to 70°C operating temperature	1.236,00 €
VPort P06-1MP-M12-CAM60	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 6.0 mm lens, -25 to 55°C operating temperature	1.032,00 €
VPort P06-1MP-M12-CAM60-T	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 6.0 mm lens, -40 to 70°C operating temperature	1.236,00 €

VPort P06-1MP-M12-CAM80	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 8.0 mm lens, -25 to 55°C operating temperature	1.032,00 €
VPort P06-1MP-M12-CAM80-T	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 8.0 mm lens, -40 to 70°C operating temperature	1.236,00 €
VPort P06-2L28M	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, PoE, 2.8 mm lens, -25 to 55°C operating temperature	1.266,00 €
VPort P06-2L28M-T	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, PoE, 2.8 mm lens, -40 to 70°C operating temperature	1.459,00 €
VPort P06-2L36M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 3.6 mm lens, -25 to 55°C operating temperature	1.251,00 €
VPort P06-2L36M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 3.6 mm lens, -40 to 70°C operating temperature	1.456,00 €
VPort P06-2L42M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 4.2 mm lens, -25 to 55°C operating temperature	1.251,00 €
VPort P06-2L42M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 4.2 mm lens, -40 to 70°C operating temperature	1.456,00 €
VPort P06-2L60M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 6.0 mm lens, -25 to 55°C operating temperature	1.251,00 €
VPort P06-2L60M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 6.0 mm lens, -40 to 70°C operating temperature	1.456,00 €
VPort P06-2L80M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 8.0 mm lens, -25 to 55°C operating temperature	1.251,00 €
VPort P06-2L80M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 8.0 mm lens, -40 to 70°C operating temperature	1.456,00 €
VPort P06-2M28M	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, PoE, 2.8 mm lens, -25 to 55°C operating temperature	1.370,00 €
VPort P06-2M28M-T	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, PoE, 2.8 mm lens, -40 to 70°C operating temperature	1.564,00 €
VPort P06-2M36M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 3.6 mm lens, -25 to 55°C operating temperature	1.371,00 €
VPort P06-2M36M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 3.6 mm lens, -40 to 70°C operating temperature	1.558,00 €
VPort P06-2M42M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 4.2 mm lens, -25 to 55°C operating temperature	1.371,00 €
VPort P06-2M42M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 4.2 mm lens, -40 to 70°C operating temperature	1.558,00 €
VPort P06-2M60M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 6.0 mm lens, -25 to 55°C operating temperature	1.371,00 €
VPort P06-2M60M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 built-in mic, PoE, 6.0 mm lens, -40 to 70°C operating temperature	1.557,00 €
VPort P06-2M80M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 8.0 mm lens, -25 to 55°C operating temperature	1.371,00 €
VPort P06-2M80M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 8.0 mm lens, -40 to 70°C operating temperature	1.558,00 €
VPort P06HC-1V28M	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 2.8 mm lens, -40 to 55°C operating temperature	1.070,00 €
VPort P06HC-1V28M-CT	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 2.8 mm lens, -40 to 55°C operating temperature, conformal coating	1.173,00 €
VPort P06HC-1V36M	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 3.6 mm lens, -40 to 55°C operating temperature	1.070,00 €
VPort P06HC-1V36M-CT	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 3.6 mm lens, -40 to 55°C operating temperature, conformal coating	1.173,00 €
VPort P06HC-1V42M	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 4.2 mm lens, -40 to 55°C operating temperature	1.070,00 €

VPort P06HC-1V42M-CT	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 4.2 mm lens, -40 to 55°C operating temperature, conformal coating	1.173,00 €
VPort P06HC-1V60M	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 6.0 mm lens, -40 to 55°C operating temperature	1.070,00 €
VPort P06HC-1V60M-CT	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 6.0 mm lens, -40 to 55°C operating temperature, conformal coating	1.173,00 €
VPort P06HC-1V80M	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 8.0 mm lens, -40 to 55°C operating temperature	1.070,00 €
VPort P06HC-1V80M-CT	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 8.0 mm lens, -40 to 55°C operating temperature, conformal coating	1.173,00 €
VPort P07-3L24M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 2.4 mm lens, -40 to 55°C	1.261,00 €
VPort P07-3L24M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 2.4 mm lens, -40 to 70°C	1.471,00 €
VPort P07-3L36M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 3.6 mm lens, -40 to 55°C	1.261,00 €
VPort P07-3L36M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 3.6 mm lens, -40 to 70°C	1.471,00 €
VPort P07-3L42M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 4.2 mm lens, -40 to 55°C	1.261,00 €
VPort P07-3L42M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 4.2 mm lens, -40 to 70°C	1.471,00 €
VPort P07-3L60M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 6.0 mm lens, -40 to 55°C	1.261,00 €
VPort P07-3L60M-T	EN 50155, 3-megapixels, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 6.0 mm lens, -40 to 70°C	1.471,00 €
VPort P07-3L80M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 8.0 mm lens, -40 to 55°C	1.261,00 €
VPort P07-3L80M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 8.0 mm lens, -40 to 70°C	1.471,00 €
VPort P07-3M24M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 2.4 mm lens, -40 to 55°C	1.291,00 €
VPort P07-3M24M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 2.4 mm lens, -40 to 70°C	1.486,00 €
VPort P07-3M36M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 3.6 mm lens, -40 to 55°C	1.291,00 €
VPort P07-3M36M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 3.6 mm lens, -40 to 70°C	1.486,00 €
VPort P07-3M42M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 4.2 mm lens, -40 to 55°C	1.291,00 €
VPort P07-3M42M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 4.2 mm lens, -40 to 70°C	1.486,00 €
VPort P07-3M60M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 6.0 mm lens, -40 to 55°C	1.291,00 €
VPort P07-3M60M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 6.0 mm lens, -40 to 70°C	1.486,00 €
VPort P07-3M80M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 8.0 mm lens, -40 to 55°C	1.291,00 €
VPort P07-3M80M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 8.0 mm lens, -40 to 70°C	1.486,00 €
VPort P16-2MR36M	EN50155, day & night, IR, 1080P IP Camera, 3.6 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	1.675,00 €
VPort P16-2MR36M-T	EN50155, day & night, IR, 1080P IP Camera, 3.6 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	1.845,00 €
VPort P16-2MR42M	EN50155, day & night, IR, 1080P IP Camera, 4.2 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	1.675,00 €

VPort P16-2MR42M-T	EN50155, day & night, IR, 1080P IP Camera, 4.2 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	1.845,00 €
VPort P16-2MR60M	EN50155, day & night, IR, 1080P IP Camera, 6.0 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	1.675,00 €
VPort P16-2MR60M-T	EN50155, day & night, IR, 1080P IP Camera, 6.0 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	1.845,00 €
VPort P16-2MR80M	EN50155, day & night, IR, 1080P IP Camera, 8.0 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	1.675,00 €
VPort P16-2MR80M-T	EN50155, day & night, IR, 1080P IP Camera, 8.0 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	1.845,00 €
VP-SC02	Side-cable-out adapter for surface mounting a VPort 06-2	10,00 €
VP-SC01	Side-cable-out adapter for mounting the VPort P06-1MP-M12	11,00 €
VP-SScrew	VPort P06-1MP series security screw 1000 pcs	418,00 €
WAC-1001	Industrial wireless access controller, 0 to 60°C operating temperature	3.658,00 €
WAC-1001-T	Industrial wireless access controller, -40 to 75°C operating temperature	4.385,00 €
WAC-2004A	Industrial wireless access controller with EU power cord, 0 to 50°C operating temperature	30.856,00 €
WAC-M300	L2 industrial wireless access controller for TAP-M310R Series, 0 to 50°C operating temperature	31.354,00 €
WALLMOUNT-8100-01	Wall-mounting kit for the UC-8100 with screws	48,00 €
WiFi-BGN	802.11ac/a/b/g/n Wi-Fi module x1, i-PEX MHF male connector to RP-SMA female connector x2, ANT-WDB-ARM-02 x1, M2 screw x2	125,00 €
Wi-Fi-BGN(252NI)	Wi-Fi module with 2 antennas, antenna cables and connectors, 2 black screws, 2 lock washers, 2 nuts, 1 thermal pad	573,00 €
WK-112-01	Wall-mounting kit, 2 plates, 8 screws	35,00 €
WK-160-01	Wall-mounting kit with 1 plate (160 x 89 x 2.0 mm), 4 screws, black	83,00 €
WK-160-02	Wall-mounting kit with 1 plate (160 x 89 x 2.0 mm), 4 screws, gray	83,00 €
WK-178-01	Wall-mounting kit with 1 plate (178 x 25 x 1.5 mm), 3 M3 x 5 mm screws	15,00 €
WK-18	Wall-mounting kit, 1 plate (18 x 120 x 8.5 mm)	11,00 €
WK-195	Wall Mounting Kit for PT-7710 series modular Ethernet Switches	81,00 €
WK-20-02	Wall-mounting kit, 3 screws, 20 x 140 x 2 mm	28,00 €
WK-24-01	Wall-mounting kit with 1 plate (178 x 24 x 10.5 mm)	22,00 €
WK-25	Wall-mounting kit, 2 plates, 4 screws, 25 x 43 x 2 mm	42,00 €
WK-30	Wall-mounting kit, 2 plates, 4 screws, 30 x 66.8 x 2 mm	9,00 €
WK-30-02	Wall-mounting kit, 2 plates, 4 screws, 30 x 66.8 x 2 mm	20,00 €
WK-32-01	Wall-mounting kit with 2 plates (32 x 29.5 mm), 4 M3 x 6 mm screws	9,00 €
WK-33-01	Wall-mounting kit with 2 plates (98.6 x 33.8 x 5 mm), 4 TMS M3 4-mm screws	20,00 €
WK-35-01	Wall-mounting kit with 2 plates (35 x 44 x 2.5 mm) and 6 screws	18,00 €
WK-35-02	Wall-mounting kit with 2 plates (35 x 24 x 1.2 mm) and 6 screws	18,00 €
WK-35-04	Wall-mount kit with 2 plates (35 x 44 x 2.5 mm), 6 screws (FTS x 6 M3 x 4 mm)	18,00 €
WK-35-05	Wall-mounting kit with 2 plates (35 x 44 x 2.5 mm), 6 NYLOK screws	15,00 €
WK-36-02	DIN-rail/wall-mounting kit, 2 plates, 6 screws	39,00 €
WK-40-01	Wall-mounting kit, 2 plates, 6 screws, 40 x 58 x 2 mm	18,00 €
WK-41-01	Wall-mounting kit with 1 plate (41 x 144 x 7.5 mm)	58,00 €
WK-44-01	Rack-mounting kit, 2 L-shaped plates, 8 screws, 44 x 57.5 x 1.6 mm	18,00 €
WK-45-01	Rack-mounting kit, 2 L-shaped plates, 8 screws, 45 x 57 x 2.5 mm	24,00 €
WK-46	Wall-mounting kit, 2 plates, 8 screws, 46.5 x 66.8 x 1 mm	9,00 €
WK-46-01	Wall-mounting kit, 2 plates, 8 screws, 46 x 66.8 x 2 mm	14,00 €
WK-51-01	Wall mounting kit with 2 plates (51.6 x 67 x 2 mm) and 6 screws	21,00 €
WK-55	Wall mounting kit with 2 plates (55 x 34.5 x 2.5 mm) and 6 screws	21,00 €
WK-56-01	Wall-mounting kit with 2 plates (56 x 33.3 x 2 mm) and 4 screws	15,00 €
WK-60-01	Wall-mounting kit, 2 plates, 6 screws, 60 x 70 x 2 mm	18,00 €
WK-71-01	Wall-mounting kit with 2 plates (each 71 x 44.8 x 5.7 mm) and 5 M3 x 5 mm screws	35,00 €
WK-75	Wall-mounting kit, 2 plates, 8 screws, 75 x 90 x 2.5 mm	35,00 €
WK-90-01	Wall-mounting kit, 2 plates, 6 screws, 90 x 62 x 2.5 mm	30,00 €

WK-TN-4900	WK-TN-4900	68,00 €
WK-TN-5308A	Transition wall-mounting kit with 1 plate (197 x 60 x 4 mm) for the TN-5308A Series to adapt to the existing TN-5308 Series mounting holes	32,00 €
WK-UP-14168	Wall-mounting kit with 2 plates (35 x 44 mm), 6 screws (FMS M3 x 4 mm) for the UPort 1400 and 1600-8 models	14,00 €
WK-UP200A-BAK-SI	Rear-panel wall-mounting kit for the UPort 200A Series, 60 x 27 x 2 mm (2.36 x 1.06 x 0.08 in) with 2 plates and 6 M3 x 5 mm screws	24,00 €
WK-UP200A-BOT-SI	Bottom-panel wall-mounting kit for the UPort 200A Series, 43 x 30 x 2 mm (1.69 x 1.18 x 0.08 in), with 2 plates and 6 M3 x 5 mm screws	21,00 €
WK-UP400A-BAK-BK	Rear-panel wall-mounting kit for the UPort 400A, 60 x 27 x 2 mm (2.36 x 1.06 x 0.08 in), with 2 plates and 6 M3 x 5 mm screws	24,00 €
WK-UP400A-BOT-BK	Bottom-panel wall-mounting kit for the UPort 400A/1400-G2/1600-G2 Series with 2 plates (43 x 30 x 2 mm or 1.69 x 1.18 x 0.08 in), 6 M3 x 5 mm screws	21,00 €
WM-UC-5000	Wall-mounting kit with screws for the UC-5000 Series	24,00 €
WP-MOD-W-SparkLAN-Wi-Fi 5	Wireless package for MIL3 supported UC computers with Wi-Fi 5 mPCIe card, 2 antenna cables, 2 thermal pads, 1 heatsink, 2 M2 x 3 mm screws (attach Wi-Fi bracket to PCB), 3 M3 x 6 mm screws (attach heatsink to PCB)	134,00 €
XM-4000-16GSFP	Gigabit Ethernet module with 16 1000BaseSFP ports	3.418,00 €
XM-4000-16GTx	Gigabit Ethernet module with 16 1000BaseT(X) ports	3.418,00 €
XM-4000-16QGSFP	2.5 Gigabit Ethernet module with 16 1000/2500BaseSFP ports	6.828,00 €
XM-4000-16QGTx	2.5 Gigabit Ethernet module with 16 1000/2500BaseT(X) ports	6.828,00 €
XM-4000-FAN-R	Exhaust fan module for MRX switches	362,00 €